

	CORPORATE PURCHASING SPECIFICATION	AA54103 Rev No. 04 PAGE 1 of 2												
HYDRO CHLORIC ACID - TECHNICAL														
1 GENERAL This specification governs the quality requirements of Hydrochloric acid, technical grade. 2 APPLICATION For use in laboratory. 3 COMPLIANCE WITH NATIONAL STANDARDS The acid shall comply with the requirements of the following National standard and also meet the requirements of this specification: IS 265-1993: Hydrochloric acid 4 TEST SAMPLES As per IS 265 4.1 To draw a representative sample, the contents of the container selected for sampling shall be mixed as thoroughly as possible by shaking or stirring or both or by rolling, so as to bring all portions into uniform distribution. 4.2 The samples shall be taken in a suitable, clean, dry air-tight glass bottle of one litre capacity. It should be almost but not completely filled by the sample. 4.3 In case of failure of first sample, two samples shall be drawn from other two drums of the same consignment at random and failure of the second sample in complying with the specification will lead to the rejection of the whole consignment. 5 VISUAL INSPECTION The material shall be a clear, colourless or light yellow liquid free from dirt and other visible impurities. 6 CHEMICAL PROPERTIES When tested as per the relevant clauses of IS 264, the acid shall show the following properties: <table style="width: 100%; margin-top: 10px;"> <tr> <td style="width: 40%;">i) Total acidity (as HCl)</td> <td style="width: 10%;">:</td> <td style="width: 50%;">30%, min. by mass</td> </tr> <tr> <td>ii) Residue on ignition</td> <td>:</td> <td>0.1%, max. by mass</td> </tr> <tr> <td>iii) Sulphates (as H₂ SO₄)</td> <td>:</td> <td>0.1%, max. by mass</td> </tr> <tr> <td>iv) Iron (as Fe)</td> <td>:</td> <td>0.005%, max. by mass</td> </tr> </table>			i) Total acidity (as HCl)	:	30%, min. by mass	ii) Residue on ignition	:	0.1%, max. by mass	iii) Sulphates (as H ₂ SO ₄)	:	0.1%, max. by mass	iv) Iron (as Fe)	:	0.005%, max. by mass
i) Total acidity (as HCl)	:	30%, min. by mass												
ii) Residue on ignition	:	0.1%, max. by mass												
iii) Sulphates (as H ₂ SO ₄)	:	0.1%, max. by mass												
iv) Iron (as Fe)	:	0.005%, max. by mass												
Revisions: As per clause 44.3.a) of MOM of MRC-CPO+NM		APPROVED: INTERPLANT MATERIAL RATIONALISATION COMMITTEE – MRC(CPO+NM)												
Rev No.04	Amd No.	Reaffirmed												
Dt:26-08-2011	Dt:	Year:2015												
Prepared HEP, Bhopal		Issued Corp.R&D												
		Dt. of 1 st Issue 01-01-1985												

AA54103	CORPORATE PURCHASING SPECIFICATION 
Rev No. 04	
PAGE 2 of 2	

7
TYPE TESTS

Whenever specified, the following tests shall be conducted and the acid shall show the properties mentioned below:

i) Free chlorine and Bromine (as Cl)	:	0.001% max., by mass
ii) Mercury (as Hg)	:	3 ppm max., by mass
iii) Sulphite (as SO ₃)	:	0.05%, max., by mass

8
TEST CERTIFICATE

Three copies of the test certificates shall be supplied unless otherwise started in the order. In addition, the supplier make sure to send one copy of test certificate along with despatch documents to facilitate quick clearance of the material.

The test certificates shall bear the following information:

BHEL's Reference:

BHEL Order No:

AA54103, Rev No. 04: HYDRO CHLORIC ACID - TECHNICAL

Supplier's Reference:

Manufacturer's/Supplier's Name:

Batch / Lot No.:

Date of manufacture and expiry, if any

Test Results:

Results of clauses 5 and 6.

9
PACKING AND MARKING

As per IS 265

10
ENVIRONMENTAL REQUIREMENTS

The supplier shall furnish Material Safety Data Sheet (MSDS) covering all information relating to human safety and environmental impacts of the hazardous materials particularly during their transportation, storage, handling and disposal along with each supply. Each container shall be marked with corresponding symbol and minimum worded cautionary notice for flammable / corrosive / toxic / harmful / irritant and oxidizing etc. as applicable.

11
REFERRED STANDARDS (Latest Publications Including Amendments)

NIL