



SPECIFICATION OF CATALYST (P-200)

1. Scope

This specification describes Catalyst (P-200) (hereafter abbreviated P-200) to be used for hardener of multifunctional epoxy resin (HEW290).

2. Quality

Quality of P-200 is given in Table 1.

Table 1

No.	Item	Unit	Quality	Remarks (Test method)
1	Melting point	°C	100±20	Microscopic test method
2	Alkalinity	meq/g	2.0~3.5	Indicator titration method
3	Water content	wt%	≤1.0	Karl Fisher method
4	Solubility in methanol	-	To melt completely	Visual method

3. Shelf life

Shelf life of P-200 is 10 months when kept in sealed container at normal condition ($20\pm 15^{\circ}\text{C}$, $65\pm 20\%$ RH).

4. Package

Standard package of P-200 is 10 kg.

Revisions: 01
SPEC. NO. WAS TME 89137
(AO 271)
Date : 12-02-93.

Distribution

TXM

Qty.

2

Approved:

R.P. Tiwari
R.P. TIWARI
Prepared

Outland
Checked

12-02-93
Date

COPYRIGHT AND CONFIDENT

The information on this document is the property of SHARAT HEAVY ELECTRICALS LTD.
It must not be used directly or indirectly in any way detrimental to the interest of the company.