

(Reaffirmed 2013)

IS : 12086 - 1987
(Reaffirmed 1997)

Indian Standard

**SPECIFICATION FOR
HYDRAZINE HYDRATE**

(First Reprint OCTOBER 2000)

UDC 547.234 : 54-162.32

© Copyright 1987

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Gr 3


November 1987

AMENDMENT NO. 1 SEPTEMBER 1991
TO
IS 12086 : 1987 SPECIFICATION FOR
HYDRAZINE HYDRATE

(Page 7, clauses A-0 to A-3.1) — Substitute the following for the existing clauses:

A-0 PRINCIPLE

A-0.1 Hydrazine reacts with potassium iodate under the usual Andrew's conditions as follows:



A-1 REAGENTS

A-1.1 Potassium Iodate Solution — 0.025 M. Dissolve exactly 5.35 g of dried potassium iodate in one litre of de-oxygenated water.

A-1.2 Carbon Tetrachloride

A-2 PROCEDURE

A-2.1 Weigh accurately about 0.08 to 0.1 g of hydrazine hydrate. Add a mixture of 30 ml of concentrated hydrochloric acid and 20 ml of de-oxygenated water. Shake well. Add 5 ml of carbon tetrachloride. Titrate against potassium iodate solution, with continuous shaking. At first the colourless organic layer of carbon tetrachloride changes to blood red and then just decolourises at the end point.

A-3 CALCULATION

A-3.1 Purity of hydrazine hydrate, percent =
$$\frac{0.00125 \times V_1 \times 100}{M}$$

where

V_1 = volume in ml of potassium iodate solution, and

M = mass in g of the sample.

IS : 12086 - 1987

Indian Standard

SPECIFICATION FOR HYDRAZINE HYDRATE

Boiler Water Sectional Committee, CDC 57

<i>Chairman</i>	<i>Representing</i>
SHRI P. C. D. G. SAMUEL	Madras Refineries Ltd, Madras
<i>Members</i>	
SHRI J. N. BHOWMIK	West Bengal State Electricity Board, Calcutta
SHRI B. K. SANTRA (<i>Alternate</i>)	
SHRI T. M. BALASUBBAMANIAN	Central Electrochemical Research Institute (CSIR), Karaiykudi
DR G. VENKATACHARI (<i>Alternate</i>)	
SHRI R. N. BANERJEE	Development Consultants Pvt Ltd, Calcutta
SHRI S. K. CHATTERJEE (<i>Alternate</i>)	
SHRI D. CHATTERJEE	Delta Enterprises Pvt Ltd, Calcutta
CHEMIST & METALLURGIST II, RDSO, LUCKNOW	Railway Board (Ministry of Railways)
CHEMIST & METALLURGIST (W. R.) (<i>Alternate</i>)	
SHRI SOMENATH GHOSE	Jai Guru Engineering Co (India), Calcutta
SHRI ANANDAMOY GHOSE (<i>Alternate</i>)	
SHRI VIJAY KUMAR GOEL	Ministry of Industry (Department of Industrial Development), New Delhi
SHRI G. T. JADEJA	Tata Hydro-Electric Power Supply Co Ltd, Bombay
SHRI B. K. GANDHI (<i>Alternate</i>)	
SHRI J. JHA	Central Electrical Authority, New Delhi
SHRI KSHIRSAGAR	Maharashtra State Electricity Board, Bombay
DR V. M. KELKAR	Engineers India Ltd, New Delhi
SHRI K. RUDBRAJ (<i>Alternate</i>)	
SHRI K. R. KRISHNASWAMY	Central Power Research Institute, Bangalore
SHRI G. UDATABHASKAR (<i>Alternate</i>)	
SHRI S. MAHADEVAN	Chemical Consultants, Madras
DR P. K. MATHUR	Indira Gandhi Centre for Atomic Research (BARC), Kalpakkam
SHRI R. NATARAJAN	Bharat Heavy Electricals Ltd, Tiruchchirappalli
SHRI T. R. NAGARAJAN (<i>Alternate</i> I)	
DR A. PRABHAKAR RAO (<i>Alternate</i> II)	
SHRI R. NATARAJAN	Hindustan Dorr-Oliver Ltd, Bombay
SHRI SUBASH VERMA (<i>Alternate</i>)	
SHRI ANIL G. PANDIT	Thermax Pvt Ltd, Pune

(Continued on page 2)

© Copyright 1987

BUREAU OF INDIAN STANDARDS

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS : 12086 - 1987

(Continued from page 1)

<i>Members</i>	<i>Representing</i>
SHRI C. L. PATEL	Gujarat Electricity Board, Ukai (Gujarat)
SHRI R. G. MANDAN (<i>Alternate</i>)	
SHRI RAM GOPAL	National Thermal Power Corporation Ltd, New Delhi
SHRI R. K. DWIVEDI (<i>Alternate</i>)	
SHRI N. RAMACHANDRAN	Ion Exchange (India) Ltd, Bombay
SHRI A. B. TONGAONKAR (<i>Alternate</i>)	
DR S. K. ROY	IEL Limited, Calcutta
SHRI N. B. SAINANI	Indian Farmers Fertilizer Co-operative Ltd, New Delhi
SHRI G. H. JOSHI (<i>Alternate</i>)	
SHRI M. V. SASTRY	IAEC Ltd, Bombay
SHRI A. K. SENGUPTA	Hindustan Fertilizer Corporation Ltd, Durgapur
SHRI A. K. BHATTACHARJEE (<i>Alternate</i>)	
DR V. K. SETH	Projects & Development India Ltd, Sindri
SHRI D. P. SINGH	Delhi Electric Supply Undertaking, New Delhi
SHRI K. B. CHHABRA (<i>Alternate</i>)	
SHRI G. P. SINGH	Steel Authority of India Ltd, New Delhi
SHRI A. P. SINHA (<i>Alternate</i>)	
SHRI R. SWAMINATHAN	National Organic Chemical Industries Ltd, Bombay
SHRI M. D. VIJAYARANGAM	Tamil Nadu State Electricity Board, Madras
SHRI V. TULASIRAMAN (<i>Alternate</i>)	
SHRI SATISH CHANDER, Director (Chem)	Director General, BIS (<i>Ex-officio Member</i>)
	<i>Secretary</i>
	SHRI S. ARAVAMUDHAN
	Joint Director (Chem), BIS

Chemicals for Boiler System Subcommittee, CDC 57 : 3

<i>Convener</i>	
SHRI S. MAHADEVAN	Chemical Consultants, Madras
<i>Members</i>	
SHRI B. B. AJMANI	Railway Board (Ministry of Railways)
SHRI C. D. DIXIT (<i>Alternate</i>)	
SHRI ANANDAMOT GHOSE	Jai Guru Engineering Co (India), Calcutta
SHRI SOMENATH GHOSE (<i>Alternate</i>)	
SHRI S. CHANDRASEKHAR	Ion Exchange (India) Ltd, Bombay
SHRI N. RAMACHANDRAN (<i>Alternate</i>)	
SHRI D. CHATTERJEE	Delta Enterprises Pvt Ltd, Calcutta
SHRI A. K. ROY (<i>Alternate</i>)	
SHRI G. R. DUBEY	Gwalior Rayon Silk Mfg (Wvg) Co Ltd, Birlagram
SHRI G. B. KHER (<i>Alternate</i>)	
SHRI S. N. GOSWAMI	Shriram Foods & Fertilizer Industries, New Delhi

(Continued on page 9)

Indian Standard
**SPECIFICATION FOR
HYDRAZINE HYDRATE**

0. FOREWORD

0.1 This Indian Standard was adopted by the Indian Standards Institution on 1 January 1987, after the draft finalized by the Boiler Water Sectional Committee had been approved by the Chemical Division Council.

0.2 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS : 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard prescribes the requirements and methods of sampling and test for hydrazine hydrate.

2. TERMINOLOGY

2.1 For the purpose of this standard, definitions given in IS : 11671-1985† shall apply.

3. REQUIREMENTS

3.1 The material shall be colourless liquid free from visible impurities and suspended particles.

3.2 The material shall comply with the requirements given in Table 1.

4. PACKING AND MARKING

4.1 Packing — The material shall be packed in mild steel drums suitably lined with plastic material or in PVC carboys.

*Rules for rounding off numerical values (revised).

†Glossary of terms relating to boiler water.

TABLE 1 REQUIREMENTS FOR HYDRAZINE HYDRATE

(Clause 3.2)

Sl. No.	CHARACTERISTIC	REQUIREMENT	METHODS OF TEST, REF TO
(1)	(2)	(3)	(4)
i)	Purity (as hydrazine hydrate), percent by mass, <i>Min</i>	80	Appendix A
ii)	Relative density, 20°C/20°C, <i>Min</i>	1.05	IS : 3025 (Part 12)-1983*
iii)	pH of 1 percent solution at 20°C, <i>Min</i>	10.5	IS : 3025 (Part 11)-1983†
iv)	Boiling range	115 to 119°C	IS : 5298-1983‡
v)	Colour, Hazen Units, <i>Max</i>	10	IS : 3025 (Part 4)-1983§
vi)	Residue on evaporation, percent by mass, <i>Max</i>	0.01	10 of IS : 3025-1964
vii)	Ash content, g/100 ml, <i>Max</i>	0.003	11 of IS : 3025-1964
viii)	Ammonia content (as NH ₃), <i>Max</i> , percent by mass	0.3	5 of IS : 2488 (Part 4)-1974¶
ix)	Iron (as Fe), ppm, <i>Max</i>	5	32 of IS : 3025-1964
x)	Copper (as Cu), ppm, <i>Max</i>	5	36 of IS : 3025-1964
xi)	Silica (as SiO ₂), ppm, <i>Max</i>	5	30 of IS : 3025-1964
xii)	Chloride (as Cl), ppm, <i>Max</i>	5	24 of IS : 3025-1964
xiii)	Sulphates (as SO ₄), ppm, <i>Max</i>	5	21 of IS : 3025-1964
xiv)	Water insoluble matter, percent by mass, <i>Max</i>	0.005	Appendix B

*Methods of sampling and test (physical and chemical) for water and waste water: Part 12 Density (*first revision*).

†Methods of sampling and test (physical and chemical) for water and waste water: Part 11 pH Value (*first revision*).

‡Method for determination of distillation range and of distillation yield (*first revision*).

§Methods of sampling and test (physical and chemical) for water and waste water: Part 4 Colour (*first revision*).

||Methods of sampling and test (physical and chemical) for water used in industry.

¶Methods of sampling and test for industrial effluents, Part 4.

4.2 Marking — The containers shall be marked with the following:

- Name of the material;
- Net volume or mass;
- Batch number;
- Name of the manufacturer or his registered trade-mark, if any; and
- Suitable cautionary note as follows:

NOTE — It has been known that hydrazine hydrate is likely to have some carcinogenic properties. Hydrazine hydrate as a product should not be used in boilers, the steam from which will be used in a process industry, processing food and/or skin products.

4.2.1 The containers may also be marked with the Standard Mark.

NOTE — The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers, may be obtained from the Bureau of Indian Standards.

5. SAMPLING

5.1 General Requirements of Sampling

5.1.1 In drawing, preparing, storing and handling samples, the following precautions and directions shall be observed.

5.1.2 The sampling instruments shall be clean and dry.

5.1.3 Precautions shall be taken to protect the samples, the material being sampled, the sampling instruments and the containers for samples from adventitious contamination. To draw a representative sample from a container, the material shall be mixed thoroughly by suitable means before sampling.

5.1.4 The sample shall be placed in clean and air-tight glass bottles or other suitable containers on which the material has no action and which have been previously washed several times with the material to be sampled.

5.1.5 The sample containers shall be of such a size that they are filled by the sample leaving an ullage of not more than five percent.

5.1.6 Each sampling container shall be sealed air-tight after filling, and marked with full details of sampling, the date of sampling and the year of manufacture of the materials.

5.2 Scale of Sampling

5.2.1 *Lot* — All containers in a single consignment of the material drawn from a single batch of manufacture shall constitute a lot. If a consignment is declared or known to consist of different batches of manufacture, the batches shall be marked separately and the groups of containers in each batch shall constitute separate lots.

5.2.2 For ascertaining conformity of the material in a lot to the requirements of this specification, samples shall be tested for each lot separately. The number of containers to be selected at random from lots of different sizes shall be in accordance with Table 2.

TABLE 2 NUMBER OF CONTAINERS TO BE SELECTED FOR SAMPLING
(Clause 5.2.2)

LOT SIZE N	SAMPLE SIZE n
(1)	(2)
3 to 15	3
16 to 40	4
41 to 65	5
66 to 110	7
111 and above	10

5.2.2.1 In order to ensure randomness of selection, the following procedure shall be adopted:

Arrange all the containers in the lot in a systematic manner and starting from any one, count them as 1, 2, 3,..... up to r , where r is the integral part of N/n (N and n being the lot size and sample size respectively). Every r th container thus counted shall be withdrawn to constitute the test sample.

5.3 Preparation of Test Samples

5.3.1 From each of the containers selected according to 5.2.2.1, equal portions of the material shall be taken out so that the total quantity collected from all the containers is about 3 litres. This shall be the composite sample.

5.3.2 The composite sample shall be divided into 3 test samples not less than 1 litre each. These test samples shall be transferred immediately to clean dry bottles which are sealed air-tight with glass stoppers and marked with the particulars of sampling as given in 5.1.6. One test sample shall be sent to the purchaser and one to the supplier. The third test sample bearing the seals of the purchaser and the supplier shall constitute the referee sample, to be used in case of dispute.

5.3.3 Tests for determination of all characteristics shall be conducted on the composite sample.

5.4 Criteria for Conformity

5.4.1 The lot shall be declared as conforming to the requirements of this specification if all the test results on the composite sample satisfy the corresponding requirements.

6. TESTS

6.1 Tests shall be conducted as prescribed in col 4 of Table 1.

6.2 Quality of Reagents — Unless otherwise specified, pure chemicals and distilled water (*see* IS : 1070-1977*) shall be employed in tests.

NOTE — 'Pure chemicals' shall mean chemicals that do not contain impurities.

APPENDIX A

[Table 1, Sl No. (i)]

DETERMINATION OF PURITY OF HYDRAZINE HYDRATE

A-0. PRINCIPLE

A-0.1 The sample is treated with hydrochloric acid and heated to 60°C and titrated against standard potassium bromate-bromide solution.

A-1. REAGENTS

A-1.1 Standard Potassium Bromate-Bromide Solution — 0.1 N. Dissolve 2.7836 g of potassium bromate, and 10 g of potassium bromide in 1000 ml of water.

A-1.2 Hydrochloric Acid — Concentrated (*see* : 265-1976†).

A-1.3 Methyl Orange Indicator — *See* IS : 2263-1979‡.

A-2. PROCEDURE

A-2.1 Take one gram of the sample in a 250-ml conical flask. Add 20 ml of concentrated hydrochloric acid and heat up to 60°C. Add 3 to 4 drops of indicator. Titrate the contents of the flask against standard potassium bromate-bromide solution till the red colour changes into yellow.

A-3. CALCULATION

A-3.1 The hydrazine hydrate content,
percent by mass $= 0.0125 \times V_1$

where

V_1 = volume in ml of standard potassium bromate-bromide solution

*Specification for water for general laboratory use (*second revision*).

†Methods for preparation of indicator solutions (*first revision*).

‡Specification for hydrochloric acid (*second revision*).

IS : 12086 - 1987

APPENDIX B

[Table 1, Sl No. (xiv)]

DETERMINATION OF WATER INSOLUBLE MATTER

B-1. PROCEDURE

B-1.1 Weigh accurately about 10 g of the material in a beaker and add equal quantity of water. Mix well with a glass rod. Filter the contents of the beaker quantitatively through a previously weighed sintered glass crucible No. 4. Wash the beaker with water and filter this also. Similarly wash the crucible a few times with water. Dry the crucible in an air oven at $105 \pm 2^\circ\text{C}$. Weigh the dried crucible for constant weight.

B-2. CALCULATION

B-2.1 Water insoluble matter, percent by mass = $\frac{M_1}{M_2} \times 100$

where

M_1 = mass in g of the residue after drying, and

M_2 = mass in g of the sample taken for test.

(Continued from page 2)

<i>Members</i>	<i>Representing</i>
SHRI K. R. KRISHNASWAMY	Central Power Research Institute, Bangalore
KUMARI P. S. RAJALAKSHMI (<i>Alternate</i>)	
SHRI S. M. C. PILLAI	National Thermal Power Corporation Ltd, New Delhi
SHRI S. DASGUPTA (<i>Alternate</i>)	
SHRI S. N. RAYCHOUHARY	Hindustan Lever Ltd, Bombay
SHRI H. N. CHAKRABORTY (<i>Alternate</i>)	
DR SANDIP ROY	IEL Limited, Calcutta
SHRI R. BHARGAVA (<i>Alternate</i>)	
SHRI M. V. SUBRAMANIAM	Tata Hydro-Electric Power Supply Co Ltd, Bombay
SHRI L. N. INDURKAR (<i>Alternate</i>)	
DR A. K. WAGLE	Thermax Pvt Ltd, Pune
DR U. D. DATAR (<i>Alternate</i>)	

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002
 Telephones: 323 0131, 323 3375, 323 9402 Fax :+ 91 011 3234062, 3239399, 3239382
 E - mail : bis@vsnl.com. Internet : http://wwwdel.vsnl.net.in/bis.org

Central Laboratory :

Plot No. 20/9, Site IV, Sahibabad Industrial Area, Sahibabad 201010 **Telephone**
 77 00 32

Regional Offices:

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002 323 76 17

*Eastern : 1/14 CIT Scheme VII, V.I.P. Road, Kankurgachi, CALCUTTA 700054 337 86 62

Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160022 60 38 43

Southern : C.I.T. Campus, IV Cross Road, CHENNAI 600113 235 23 15

†Western : Manakalaya, E9, MIDC, Behind Marol Telephone Exchange, 832 92 95
 Andheri (East), MUMBAI 400093

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 380001 550 13 48

‡Peenya Industrial Area, 1st Stage, Bangalore-Tumkur Road, 839 49 55
 BANGALORE 560058

Commercial-cum-Office Complex, Opp. Dushera Maidan, E-5 Arera Colony, 72 34 52
 Bittan Market, BHOPAL 462016

62/63, Ganga Nagar, Unit VI, BHUBANESWAR 751001 40 36 27

Kalai Kathir Building, 670 Avinashi Road, COIMBATORE 641018 21 01 41

Plot No. 43, Sector 16 A, Mathura Road, FARIDABAD 121001 28 88 01

Savitri Complex, 116 G.T. Road, GHAZIABAD 201001 71 19 98

53/5 Ward No.29, R.G. Barua Road, 5th By-lane, GUWAHATI 781003 54 11 37

5-8-56C, L.N. Gupta Marg, Nampally Station Road, HYDERABAD 500001 320 10 84

E-52, Chitrangan Marg, C- Scheme, JAIPUR 302001 37 38 79

117/418 B, Sarvodaya Nagar, KANPUR 208005 21 68 76

Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kishore Road, 21 89 23
 LUCKNOW 226001

NIT Building, Second Floor, Gokulpat Market, NAGPUR 440010 52 51 71

Patliputra Industrial Estate, PATNA 800013 26 28 08

Institution of Engineers (India) Building, 1332 Shivaji Nagar, PUNE 411005 32 36 35

'Sahajanand House' 3rd Floor, Bhaktinagar Circle, 80 Feet Road, 36 85 86
 RAJKOT 360002

T.C. No. 14/1421, University P. O. Palayam, THIRUVANANTHAPURAM 695034 32 21 04

*Sales Office is at 5 Chowringhee Approach, P.Q. Princep Street, 27 10 85
 CALCUTTA 700072

†Sales Office is at Novelty Chambers, Grant Road, MUMBAI 400007 309 65 28

‡Sales Office is at 'F' Block, Unity Building, Narashimaraja Square, 222 39 71
 BANGALORE 560002

Reprography Unit, BIS, New Delhi, India