

TD-201 Rev No. 00 Form No.	 HYDERABAD	PRODUCT STANDARD PROJECT ENGINEERING HYDERABAD		PY 55098																																																																												
				Rev No. 02																																																																												
				Page 1 of 10																																																																												
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED, It must not be used directly or indirectly in any way detrimental to the interest of the company.	<u>TECHNICAL SPECIFICATION FOR LOW TENSION POWER XLPE CABLES</u> 1.0 INTENT OF SPECIFICATION: 1.1 This specification governs the requirements of design, manufacture, testing packing at manufacturer's work and delivery at site and complete in all respects of this specification. 2.0 APPLICABLE STANDARDS: The equipment to be furnished under this specification shall be in accordance with the applicable section of the latest versions of below standards. <table border="0"> <tr> <td>IS 7098-1</td> <td>:</td> <td>Specification for XLPE insulated (Heavy duty) Electric Cables.</td> </tr> <tr> <td>IS 209</td> <td>:</td> <td>Specification for Zinc</td> </tr> <tr> <td>IS-8130</td> <td>:</td> <td>Conductors for insulated electric cables and flexible cords.</td> </tr> <tr> <td>IS 3975</td> <td>:</td> <td>Standard for Mild steel wires, strips & tapes for Armoring.</td> </tr> <tr> <td>IS 10810(Pt-41):</td> <td></td> <td>Method of test for cables: Mass of zinc coating on steel armour.</td> </tr> <tr> <td>IS 10462(Pt-1) :</td> <td></td> <td>Fictitious calculation method for determination of Dimensions of protective coverings of cables: Part-1 Electrometric and thermoplastic insulated cables.</td> </tr> <tr> <td>IS 10418</td> <td>:</td> <td>Drums for electric cables.</td> </tr> <tr> <td>IS 10810(Pt-58):</td> <td></td> <td>Oxygen Index test.</td> </tr> <tr> <td>IS 10810(Pt-61):</td> <td></td> <td>Flame Retardant test.</td> </tr> <tr> <td>IS 10810(Pt-62):</td> <td></td> <td>Fire resistance test for bunched cables.</td> </tr> <tr> <td>IEC 60332-3</td> <td>:</td> <td>Tests on electric cables under fire conditions.</td> </tr> <tr> <td>ASTM-D2863</td> <td>:</td> <td>Standard for critical oxygen index and temperature index test.</td> </tr> <tr> <td>ASTM-D2843</td> <td>:</td> <td>Standard for smoke generation test.</td> </tr> <tr> <td>IEC-754-1</td> <td>:</td> <td>Standard for Acid gas generation test.</td> </tr> <tr> <td>IEC-332-1</td> <td>:</td> <td>Standard for Flammability test.</td> </tr> <tr> <td>SS 424 1475</td> <td>:</td> <td>Standard for Flammability test.</td> </tr> <tr> <td>Class F3</td> <td></td> <td></td> </tr> <tr> <td>IEEE 383</td> <td>:</td> <td>Standard for type test of class IE electric cables, field splices, and connections for Nuclear power generating stations.</td> </tr> <tr> <td>IS 5831</td> <td>:</td> <td>Standard for PVC Insulation & Sheath of electric cables.</td> </tr> <tr> <td>IS 3961(Pt-2)</td> <td>:</td> <td>Recommended current ratings for Cables</td> </tr> <tr> <td>NEMA – WC 70:</td> <td></td> <td>Standard for Non-shielded power cables rated 2000Volts or less for the distribution of electrical energy.</td> </tr> <tr> <td>NEMA – WC 53:</td> <td></td> <td>Standard test methods for extruded dielectric power, control, instrumentation and portable cables for test.</td> </tr> <tr> <td>DIN 53387:</td> <td></td> <td>Artificial weathering and ageing of plastics and elastomers by exposure to Filtered Xenon arc radiation</td> </tr> <tr> <td>ASTM-G-154:</td> <td></td> <td>Standard practice for operating fluorescent light apparatus for UV exposure of non-metallic materials.</td> </tr> <tr> <td>BS: 7846:</td> <td></td> <td>Electric cables -600/1000V armoured fire resistant cables having thermosetting insulation and low emission of smoke and corrosive gases when affected by fire.</td> </tr> </table> The cables shall also conform to the provisions of Indian electricity rules and other statutory regulations as applicable.					IS 7098-1	:	Specification for XLPE insulated (Heavy duty) Electric Cables.	IS 209	:	Specification for Zinc	IS-8130	:	Conductors for insulated electric cables and flexible cords.	IS 3975	:	Standard for Mild steel wires, strips & tapes for Armoring.	IS 10810(Pt-41):		Method of test for cables: Mass of zinc coating on steel armour.	IS 10462(Pt-1) :		Fictitious calculation method for determination of Dimensions of protective coverings of cables: Part-1 Electrometric and thermoplastic insulated cables.	IS 10418	:	Drums for electric cables.	IS 10810(Pt-58):		Oxygen Index test.	IS 10810(Pt-61):		Flame Retardant test.	IS 10810(Pt-62):		Fire resistance test for bunched cables.	IEC 60332-3	:	Tests on electric cables under fire conditions.	ASTM-D2863	:	Standard for critical oxygen index and temperature index test.	ASTM-D2843	:	Standard for smoke generation test.	IEC-754-1	:	Standard for Acid gas generation test.	IEC-332-1	:	Standard for Flammability test.	SS 424 1475	:	Standard for Flammability test.	Class F3			IEEE 383	:	Standard for type test of class IE electric cables, field splices, and connections for Nuclear power generating stations.	IS 5831	:	Standard for PVC Insulation & Sheath of electric cables.	IS 3961(Pt-2)	:	Recommended current ratings for Cables	NEMA – WC 70:		Standard for Non-shielded power cables rated 2000Volts or less for the distribution of electrical energy.	NEMA – WC 53:		Standard test methods for extruded dielectric power, control, instrumentation and portable cables for test.	DIN 53387:		Artificial weathering and ageing of plastics and elastomers by exposure to Filtered Xenon arc radiation	ASTM-G-154:		Standard practice for operating fluorescent light apparatus for UV exposure of non-metallic materials.	BS: 7846:		Electric cables -600/1000V armoured fire resistant cables having thermosetting insulation and low emission of smoke and corrosive gases when affected by fire.
	IS 7098-1	:	Specification for XLPE insulated (Heavy duty) Electric Cables.																																																																													
IS 209	:	Specification for Zinc																																																																														
IS-8130	:	Conductors for insulated electric cables and flexible cords.																																																																														
IS 3975	:	Standard for Mild steel wires, strips & tapes for Armoring.																																																																														
IS 10810(Pt-41):		Method of test for cables: Mass of zinc coating on steel armour.																																																																														
IS 10462(Pt-1) :		Fictitious calculation method for determination of Dimensions of protective coverings of cables: Part-1 Electrometric and thermoplastic insulated cables.																																																																														
IS 10418	:	Drums for electric cables.																																																																														
IS 10810(Pt-58):		Oxygen Index test.																																																																														
IS 10810(Pt-61):		Flame Retardant test.																																																																														
IS 10810(Pt-62):		Fire resistance test for bunched cables.																																																																														
IEC 60332-3	:	Tests on electric cables under fire conditions.																																																																														
ASTM-D2863	:	Standard for critical oxygen index and temperature index test.																																																																														
ASTM-D2843	:	Standard for smoke generation test.																																																																														
IEC-754-1	:	Standard for Acid gas generation test.																																																																														
IEC-332-1	:	Standard for Flammability test.																																																																														
SS 424 1475	:	Standard for Flammability test.																																																																														
Class F3																																																																																
IEEE 383	:	Standard for type test of class IE electric cables, field splices, and connections for Nuclear power generating stations.																																																																														
IS 5831	:	Standard for PVC Insulation & Sheath of electric cables.																																																																														
IS 3961(Pt-2)	:	Recommended current ratings for Cables																																																																														
NEMA – WC 70:		Standard for Non-shielded power cables rated 2000Volts or less for the distribution of electrical energy.																																																																														
NEMA – WC 53:		Standard test methods for extruded dielectric power, control, instrumentation and portable cables for test.																																																																														
DIN 53387:		Artificial weathering and ageing of plastics and elastomers by exposure to Filtered Xenon arc radiation																																																																														
ASTM-G-154:		Standard practice for operating fluorescent light apparatus for UV exposure of non-metallic materials.																																																																														
BS: 7846:		Electric cables -600/1000V armoured fire resistant cables having thermosetting insulation and low emission of smoke and corrosive gases when affected by fire.																																																																														
Ref. Doc	Revisions : Refer to record of revisions :	Prepared : -SD- M.Ganesh	Checked : -SD- K.Venkatesh	Approved : -SD- P.Chandrasekhar	Date : 28.11.14																																																																											



Form No.	 HYDERABAD	PRODUCT STANDARD PROJECT ENGINEERING HYDERABAD	PY 55098
			Rev No. 02
			Page 2 of 10
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.		3.0 CABLE REQUIREMENTS:	
		a) Voltage grade : 650/1100 V b) The conductors (heavy duty type, Copper (Cu.)) shall be solid for conductor of nominal area up to and including 6 sqmm and stranded beyond 6 sqmm. Conductors of nominal area less than 16sq.mm shall be circular only. Conductor of nominal area 16 sqmm and above may be circular or shaped as per IS 8130. Cables with reduced neutral conductor shall have sizes as per table 1 of IS 7098(part-I). c) Insulation: The core insulation shall be with cross linked polyethylene (XLPE) insulating compound, applied by extrusion. It shall be free from voids and shall withstand all mechanical and thermal stress under steady state and transient operating conditions. It shall conform to the properties given in table-1 of IS: 7098(Pt-1). The Core identification shall be as per IS: 7098-I. d) Inner sheath : The inner sheath shall be applied over the laid up cores and shall be of PVC compound by extrusion and shall conform to the requirements of type ST 2 compound of IS: 5831. The extruded inner sheath shall be of uniform thickness. Single core cables shall have no innersheath. e) Armoring: For single core cables , the armouring shall be of non-magnetic material. For multi core cables armoring shall be by galvanised steel wires where the calculated diameter below armouring doesn't exceed 13mm and by galvanized steel strips where this dimension is greater than 13mm. Requirement and methods of tests for armour material and uniformity of galvanization shall be as per IS -3975, IS -10810(Part-41). The dimensions of armour shall be as per method (b) of IS-7098 (Part-1). For single core cables, the armouring shall be with H4 grade hard drawn aluminium round wire of 2.5 mm diameter. f) Outer sheath : The outer sheath of the cables shall be applied by extrusion over the armouring and shall be of PVC FRLS compound conforming to the requirements of type ST 2 compound of IS: 5831. The minimum and average thickness of outer sheath for unarmoured cables and minimum thickness of outer sheath for armoured cables shall be as per IS: 7098. (Part-1). g) The thickness of the insulation, inner sheath & outer sheath shall be governed by values given in IS: 7098 (Part-1). h) Outer sheath of all cables shall be black in color and the minimum value of oxygen index shall be 29 at 27 ± 2° C. In addition suitable chemicals shall be added into the PVC compound of outer sheath to protect the cable against rodent and terminate attack. Outer sheath of unarmored cables shall be green color. i) All cables covered in this specification shall be flame retardant low smoke (FRLS). The outer sheath of PVC cables shall posses flame propagation properties meeting requirements as per IS-10810 (Part-62) category AF. FRLS cable shall be identified by appropriate legend i.e., "FRLS category-C2" throughout the cable length. FRLS properties shall be as per IS-10810 Part 61 and Part62, IEC 60332 Part1 and Part3, IEEE-383, IEC-61034, IEC-60754 Part1, ASTM-D-2863. j) On the outer sheath of cable, necessary information such as vendor's name, type, size, voltage grade of the cable, cable code, FRLS category-C2, BHEL Material code shall be embossed. Sequential marking of the length of the cable in meters shall be provided on the outer sheath at every one meter. The embossing shall be legible and indelible.	
Ref. Doc			



Form No.	 HYDERABAD	PRODUCT STANDARD PROJECT ENGINEERING HYDERABAD	PY 55098
			Rev No. 02
			Page 3 of 10
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.		k) The overall diameter of the cables shall be strictly as per the values declared by the vendor in the technical information subject to a maximum tolerance of $\pm 2\text{mm}$ up to overall diameter of 60mm and $\pm 3\text{mm}$ for beyond 60mm. l) The joints in armor wire/strips shall be made by brazing or welding and any surface irregularities shall be removed. A joint in any wire/strip shall be at least 300mm from the nearest joint in any wire/strip in the complete cable. m) Flexible cables shall be of Copper conductor of Class-V type as per IS 8130. with XLPE Insulation as per IS 7098-1 and PVC ST2 sheathed FRLS type. 4.0 TESTS: 4.1 The Cables shall be subjected to Type, Routine, Acceptance tests and Special tests as detailed below. BHEL/End User reserves the right to witness all tests with sufficient advance notice from vendor. 4.2 Cables offered shall have valid Type test certificates of recognized testing house such as CPRI, CMRI, PTB, BASEEFA, UL or equivalent. 4.3 The cables shall be tested and inspected at the vendor's works. All the materials employed in manufacture of the cable shall be subjected, both before and after manufacture, to examination, testing and approval by BHEL/End User. 4.4 Vendor shall furnish all necessary information concerning the supply to BHEL. 4.5 The inspector shall have free access to the vendor's works for the purpose of inspecting the process of manufacture in all its stages and will have the power to reject any material, which appears to be of unsuitable description or of unsatisfactory quality. 4.6 The vendor shall give at least 2 weeks advance notice to the purchaser, regarding the date of testing to enable him or his representative to witness the tests. 4.7 Type Tests and Special tests to be conducted/Valid Certificates to be submitted shall be governed by below clauses. If Type tests certificates and Special Tests Certificates (applicable for UV test, Accelerated water absorption test) are not available for any size of cable, same shall be conducted by vendor at his own cost in any recognized laboratory. If in-house test facilities are to be used then the testing equipments shall be calibrated (valid calibration certificates shall be produced during inspection) and traced back to National Calibration standards. The reports shall be submitted for BHEL's approval before dispatch of the cables. There shall not be any delivery and commercial implications on account of this. 4.8 Routine Tests: All Routine tests on each size of cable as per IS 7098-I & approved data sheet shall be conducted. The Test reports shall be submitted for review to BHEL/BHEL's representative and annexed to the Inspection Report. 4.9 Acceptance Tests: All Acceptance tests on each size of cable as per IS 7098-I & approved data sheet shall be conducted in the presence of BHEL's representative. The Test reports shall be annexed to the Inspection Report. 4.10 Type Tests: Type test certificates for the type tests as per IS 7098-I & IS 5831 of not older than 5 years (as on date of enquiry) issued by any recognized laboratory for the Size of cable shall be furnished for BHEL's review alongwith Technical data sheets. If Type test certificates are not available refer above clause no. 4.7.	
Ref.	Doc		



Form No.	 HYDERABAD	PRODUCT STANDARD PROJECT ENGINEERING HYDERABAD	PY 55098
			Rev No. 02
			Page 4 of 10
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED . It must not be used directly or indirectly in any way detrimental to the interest of the company.	4.11 SPECIAL TESTS: 4.11.1 Ultra Violet radiation Test: Test for Resistance to Ultra Violet Radiation should be carried as per ASTM-G-53(latest) or ASTM-G-154(latest) on outer sheath. The retention values of tensile strength and ultimate elongation after the test shall be minimum 60% of tensile strength and ultimate elongation before the test. Test certificates to this test <u>(not older than one year) from</u> recognized testing laboratory to be furnished <u>for review by BHEL</u> alongwith Technical Data sheets. In case the Test certificates are not available, refer above clause no. 4.7. Sampling for this test is to be done randomly once for each order, provided outer sheath remains same. 4.11.2 Accelerated water absorption test: Accelerated water absorption test for insulation as per NEMAWC-53(latest):Test certificates with respect to this test <u>(not older than one year)</u> from recognized testing laboratory to be furnished for review by BHEL alongwith Technical Data sheets. In case test certificates are not available, refer above clause no. 4.7. Sampling for this is to be done randomly once for each order, provided type of insulation remains same. 4.11.3 Oxygen Index Test: The test shall be carried out as per IS-10810(Part-58). Sampling to be done for every offered lot/size as per sampling plan. 4.11.4 Flammability test: The test shall be carried out on finished cable as per IS: 10810 (part61& 62). Sampling for these tests to be done randomly once for each order. The acceptance criteria for tests conducted shall be as under: Part-61-The cable meets the requirement if there is no visible damage on the test specimen within 300mm from its upper end. Part-62-The maximum extent of the charred portion measured on the test sample should not have reached a height exceeding 2.5m above the bottom edge of the burner at the front of the ladder. 4.11.5 Rodent and Termite repulsion test: Test for rodent and termite repulsion property shall be carried out. The vendors shall furnish the test details to analyze the property by chemical method for BHEL's review/information. Sampling to be done for every offered lot/size as per sampling plan. 4.12 FRLS Tests: Following FRLS tests on each size (minimum one sample per size) of cable shall be conducted in the presence of BHEL's representative & reports shall be annexed to Inspection report. - Oxygen index test as per ASTM D-2863 and minimum oxygen index shall be 29 at 27+/-2degC. - Temperature index test as per ASTM D-2863 and minimum temp index shall be 250degC. - Acid gas generation test as per IEC-60754(1) and Maximum acid gas generation shall be 20% by weight. - Smoke generation test as per ASTM D-2843 and Maximum smoke density rating shall be 60%. - Flammability Test: For Cables with OD >35: as per IEEE-383. For Cables with OD <=35: as per Clause F3 of SS: 4241475/88.		
	Ref. Doc		



Form No.	 HYDERABAD	PRODUCT STANDARD PROJECT ENGINEERING HYDERABAD	PY 55098																								
			Rev No. 02																								
			Page 5 of 10																								
5.0 <u>PACKING AND DESPATCH:</u> 5.1 Cables shall be dispatched in non-returnable Steel drums of suitable barrel diameter, securely battened, with the take-off end fully protected against mechanical damage. Ferrous parts used shall be treated with a suitable rust preventive finish or coating to avoid rusting during transit or storage. 5.2 PVC/Rubber end caps shall be supplied free of cost for each drum with a minimum of eight per thousand meter length. In addition, ends of the cables shall be properly sealed with caps to avoid ingress of water during transportation and storage. 5.3 On the flange of the drum, necessary information such as project title, vendor's name, type, size, voltage grade of the cable, length of the cable in meters, drum no., cable code, BIS certification mark, gross weight etc. shall be printed. An arrow shall be printed on the drum with suitable instructions to show the direction of the rotation of the drum. 5.4 Cables shall be supplied as per following drum lengths: <table border="0"> <tr> <td>Multicore Power cables up to 10 mm²</td> <td>:</td> <td>2000 m</td> </tr> <tr> <td>Multicore Power cables from 10 mm² up to 70 mm²</td> <td>:</td> <td>1000 m</td> </tr> <tr> <td>Multicore Power Cables from 95 mm² up to 300 mm²</td> <td>:</td> <td>500 m</td> </tr> <tr> <td>Single core Power cables up to 630 mm²</td> <td>:</td> <td>1000 m</td> </tr> </table> A tolerance of +3 % (No Negative tolerance) shall be permissible for each drum and overall quantity. 6.0 <u>DOCUMENTATION:</u> 6.1 DRAWINGS, DATA AND MANUAL: 6.1.1 To be submitted along with bid Technical data sheets. Datasheets as per relevant formats given shall be furnished. Separately typed vendor datasheets are NOT acceptable. - Type Test Certificates - Certificates of Special Tests Type - Bidder shall furnish NO Deviations - Check list for Bid Submission. 6.1.2 To be submitted in 6 sets after award of contract <table border="1"> <thead> <tr> <th>Sl.No.</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1.</td> <td>Completely filled in technical data sheets Datasheets as per relevant formats given shall be furnished. Separately typed vendor datasheets are NOT acceptable.</td> </tr> <tr> <td>2.</td> <td>Transport/Shipping dimension drawing</td> </tr> <tr> <td>3.</td> <td>Type Test Certificates</td> </tr> <tr> <td>4.</td> <td>Erection manual</td> </tr> <tr> <td>5.</td> <td>Catalogues</td> </tr> </tbody> </table> <u>No. of copies to be submitted for each submission shall be as follows</u> ➤ For Approval & Review documents shall be in 6 copies.				Multicore Power cables up to 10 mm ²	:	2000 m	Multicore Power cables from 10 mm ² up to 70 mm ²	:	1000 m	Multicore Power Cables from 95 mm ² up to 300 mm ²	:	500 m	Single core Power cables up to 630 mm ²	:	1000 m	Sl.No.	Description	1.	Completely filled in technical data sheets Datasheets as per relevant formats given shall be furnished. Separately typed vendor datasheets are NOT acceptable.	2.	Transport/Shipping dimension drawing	3.	Type Test Certificates	4.	Erection manual	5.	Catalogues
Multicore Power cables up to 10 mm ²	:	2000 m																									
Multicore Power cables from 10 mm ² up to 70 mm ²	:	1000 m																									
Multicore Power Cables from 95 mm ² up to 300 mm ²	:	500 m																									
Single core Power cables up to 630 mm ²	:	1000 m																									
Sl.No.	Description																										
1.	Completely filled in technical data sheets Datasheets as per relevant formats given shall be furnished. Separately typed vendor datasheets are NOT acceptable.																										
2.	Transport/Shipping dimension drawing																										
3.	Type Test Certificates																										
4.	Erection manual																										
5.	Catalogues																										
Ref.																											
Doc																											

COPYRIGHT AND CONFIDENTIAL
 The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED.
 It must not be used directly or indirectly in any way detrimental to the interest of the company.



	Form No.	 HYDERABAD	PRODUCT STANDARD PROJECT ENGINEERING HYDERABAD	PY 55098 Rev No. 02 Page 6 of 10																														
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company. <u>7.0 DEVIATION SCHEDULE</u> <u>Enquiry No.:</u> <u>Name of Bidder:</u> <u>Offer Ref. No.:</u> <u>DEVIATION FORMAT</u> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 5%;">Sl. No.</th> <th style="width: 15%;">Clause no. & Spec. no.</th> <th style="width: 30%;">Description as per Specification</th> <th style="width: 15%;">Deviation taken</th> <th style="width: 15%;">Nature of Deviation</th> <th style="width: 20%;">Remarks</th> </tr> </thead> <tbody> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </tbody> </table> NOTES: 1. Technical offer of the bidder will be evaluated only on the basis of Deviation Schedule. Deviation Schedule constitutes this sheet (with these Notes) duly signed and stamped. 2. Deviations, if any, shall be clearly brought out only in this format. Deviations mentioned / taken elsewhere or in any other format will be ignored. 3. Additional sheets in the same format can be attached by the vendor, if necessary. 4. Nature of Deviations shall only be of Design / Manufacturing constraints and non-availability of items / components / makes in market. 5. No price implications shall be entertained for deviations withdrawn during the technical scrutiny. If any deviations are accepted by BHEL during technical scrutiny then also there will be no price implication. Hence, in no case there will be consideration of Price implications. 6. Reasons for the deviations shall be specified in the Remarks column. 7. If there are no deviations from the specifications, bidder still has to submit the Deviation Schedule by writing "NO Deviations" in this format. 8. If the "Deviation Schedule" is not submitted along with the offer, the bidder's offer is likely to be rejected without any further interaction with the bidder. 9. Only the accepted deviations in conjunction with the original tender shall constitute the contract document for the award of job to the bidder. SIGNATURE OF BIDDER NAME DESIGNATION COMPANY SEAL _____ _____ _____ _____					Sl. No.	Clause no. & Spec. no.	Description as per Specification	Deviation taken	Nature of Deviation	Remarks																								
Sl. No.	Clause no. & Spec. no.	Description as per Specification	Deviation taken	Nature of Deviation	Remarks																													
Ref.	Doc																																	



Form No.	 HYDERABAD	PRODUCT STANDARD PROJECT ENGINEERING HYDERABAD		PY 55098	
				Rev No. 02	
				Page 7 of 10	
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED . It must not be used directly or indirectly in any way detrimental to the interest of the company.		8.0 GENERAL:			
		8.1 CHECKLIST FOR BID SUBMISSION (TO BE FILLED BY BIDDER AND SUBMITTED ALONG WITH OFFER)			
		Sl. No.	Description	Bidder Confirmation	Comments/ Remarks
		1	Technical offer is conforming to technical specification PY55098 & its associated Annexures (if any), pre-bid clarifications (if any) etc., Bidder to confirm (Yes / No).		
		2	Bidder confirms that they have read the provisions of the Deviation Schedule and have included the deviation Schedule in the Offer after agreeing to the said Provisions (Yes/No).		
		3	Bidder confirms that Prices for all items have been Quoted. Unpriced & Priced Schedules are included in the Techno-commercial Offer and Priced Offer respectively.(Yes/NO)		
4	As per specification, bidder confirms that complete set of test certificates have been included along with the Offer. In case bidder has not submitted test certificates, bidder confirms to conduct the tests as per cl.no 4.7 and submit the report to BHEL/customer for approval. (YES/NO)				
Notes: Offer received without affirmative confirmation against any of the above points may not be considered for evaluation.		(Signature and stamp of bidder with date)			
Ref. Doc					



Form No.	 HYDERABAD	PRODUCT STANDARD PROJECT ENGINEERING HYDERABAD	PY 55098																																																																																																																																																																															
			Rev No. 02																																																																																																																																																																															
			Page 8 of 10																																																																																																																																																																															
8.2 Quantities mentioned are tentative requirement. Based on the actual requirement, quantity can be increased or decreased by about 15% on overall qty. Final BOQ will be informed before price bid opening. Unit rates shall be applicable for the revised BOQ also. 8.3 GUIDELINES TO VENDORS FOR PREPARATION OF QUALITY ASSURANCE PLAN: REFER ANNEXURE-I 8.4 “Vendors should not be part of EIL holiday List. Package vendors will not source the items from sub-vendors who are part of EIL' holiday list”																																																																																																																																																																																		
TABLE-1 - MATERIAL CODIFICATION <table border="1"> <thead> <tr> <th>Sl. No</th> <th>Cable size</th> <th>Armouring</th> <th>Cond, Insulation & Outer sheath matl.</th> <th>BHEL Material Code</th> </tr> </thead> <tbody> <tr><td>01</td><td>2 C x 4</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098008</td></tr> <tr><td>02</td><td>3 C x 4</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098016</td></tr> <tr><td>03</td><td>3 C x 6</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098024</td></tr> <tr><td>04</td><td>3 C x 10</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098032</td></tr> <tr><td>05</td><td>3 C x 16</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098040</td></tr> <tr><td>06</td><td>3 C x 25</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098059</td></tr> <tr><td>07</td><td>3 C x 35</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098067</td></tr> <tr><td>08</td><td>3 C x 50</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098075</td></tr> <tr><td>09</td><td>3 C x 70</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098083</td></tr> <tr><td>10</td><td>3 C x 95</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098091</td></tr> <tr><td>11</td><td>3 C x 120</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098105</td></tr> <tr><td>12</td><td>3 C x 150</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098113</td></tr> <tr><td>13</td><td>3 C x 185</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098121</td></tr> <tr><td>14</td><td>3 C x 240</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098130</td></tr> <tr><td>15</td><td>3 C x 300</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098148</td></tr> <tr><td>16</td><td>3 C x 400</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098156</td></tr> <tr><td>17</td><td>3.5 C x 35</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098164</td></tr> <tr><td>18</td><td>3.5 C x 50</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098172</td></tr> <tr><td>19</td><td>3.5 C x 70</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098180</td></tr> <tr><td>20</td><td>3.5 C x 95</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098199</td></tr> <tr><td>21</td><td>3.5 C x 120</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098202</td></tr> <tr><td>22</td><td>3.5 C x 150</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098210</td></tr> <tr><td>23</td><td>3.5 C x 185</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098229</td></tr> <tr><td>24</td><td>3.5 C x 240</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098237</td></tr> <tr><td>25</td><td>3.5 C x 300</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098245</td></tr> <tr><td>26</td><td>3.5 C x 400</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098253</td></tr> <tr><td>27</td><td>4 C x 4</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098261</td></tr> <tr><td>28</td><td>4 C x 6</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098270</td></tr> <tr><td>29</td><td>4 C x 10</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098288</td></tr> <tr><td>30</td><td>4 C x 16</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098296</td></tr> <tr><td>31</td><td>1 C x 120</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098300</td></tr> <tr><td>32</td><td>1 C x 240</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098318</td></tr> <tr><td>33</td><td>1 C x 6</td><td>Un Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098326</td></tr> <tr><td>34</td><td>1 C x 10</td><td>Un Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098334</td></tr> </tbody> </table>				Sl. No	Cable size	Armouring	Cond, Insulation & Outer sheath matl.	BHEL Material Code	01	2 C x 4	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098008	02	3 C x 4	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098016	03	3 C x 6	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098024	04	3 C x 10	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098032	05	3 C x 16	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098040	06	3 C x 25	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098059	07	3 C x 35	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098067	08	3 C x 50	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098075	09	3 C x 70	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098083	10	3 C x 95	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098091	11	3 C x 120	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098105	12	3 C x 150	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098113	13	3 C x 185	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098121	14	3 C x 240	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098130	15	3 C x 300	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098148	16	3 C x 400	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098156	17	3.5 C x 35	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098164	18	3.5 C x 50	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098172	19	3.5 C x 70	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098180	20	3.5 C x 95	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098199	21	3.5 C x 120	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098202	22	3.5 C x 150	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098210	23	3.5 C x 185	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098229	24	3.5 C x 240	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098237	25	3.5 C x 300	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098245	26	3.5 C x 400	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098253	27	4 C x 4	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098261	28	4 C x 6	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098270	29	4 C x 10	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098288	30	4 C x 16	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098296	31	1 C x 120	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098300	32	1 C x 240	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098318	33	1 C x 6	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098326	34	1 C x 10	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098334
Sl. No	Cable size	Armouring	Cond, Insulation & Outer sheath matl.	BHEL Material Code																																																																																																																																																																														
01	2 C x 4	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098008																																																																																																																																																																														
02	3 C x 4	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098016																																																																																																																																																																														
03	3 C x 6	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098024																																																																																																																																																																														
04	3 C x 10	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098032																																																																																																																																																																														
05	3 C x 16	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098040																																																																																																																																																																														
06	3 C x 25	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098059																																																																																																																																																																														
07	3 C x 35	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098067																																																																																																																																																																														
08	3 C x 50	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098075																																																																																																																																																																														
09	3 C x 70	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098083																																																																																																																																																																														
10	3 C x 95	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098091																																																																																																																																																																														
11	3 C x 120	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098105																																																																																																																																																																														
12	3 C x 150	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098113																																																																																																																																																																														
13	3 C x 185	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098121																																																																																																																																																																														
14	3 C x 240	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098130																																																																																																																																																																														
15	3 C x 300	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098148																																																																																																																																																																														
16	3 C x 400	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098156																																																																																																																																																																														
17	3.5 C x 35	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098164																																																																																																																																																																														
18	3.5 C x 50	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098172																																																																																																																																																																														
19	3.5 C x 70	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098180																																																																																																																																																																														
20	3.5 C x 95	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098199																																																																																																																																																																														
21	3.5 C x 120	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098202																																																																																																																																																																														
22	3.5 C x 150	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098210																																																																																																																																																																														
23	3.5 C x 185	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098229																																																																																																																																																																														
24	3.5 C x 240	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098237																																																																																																																																																																														
25	3.5 C x 300	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098245																																																																																																																																																																														
26	3.5 C x 400	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098253																																																																																																																																																																														
27	4 C x 4	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098261																																																																																																																																																																														
28	4 C x 6	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098270																																																																																																																																																																														
29	4 C x 10	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098288																																																																																																																																																																														
30	4 C x 16	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098296																																																																																																																																																																														
31	1 C x 120	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098300																																																																																																																																																																														
32	1 C x 240	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098318																																																																																																																																																																														
33	1 C x 6	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098326																																																																																																																																																																														
34	1 C x 10	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098334																																																																																																																																																																														
Ref. Doc																																																																																																																																																																																		

COPYRIGHT AND CONFIDENTIAL

The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED .
It must not be used directly or indirectly in any way detrimental to the interest of the company.



Form No.	 HYDERABAD	PRODUCT STANDARD PROJECT ENGINEERING HYDERABAD				PY 55098																																																																																																																																																																
						Rev No. 02																																																																																																																																																																
						Page 9 of 10																																																																																																																																																																
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.		<table border="1"> <tr><td>35</td><td>1 C x 25</td><td>Un Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098342</td></tr> <tr><td>36</td><td>1 C x 35</td><td>Un Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098350</td></tr> <tr><td>37</td><td>1 C x 50</td><td>Un Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098369</td></tr> <tr><td>38</td><td>1 C x 70</td><td>Un Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098377</td></tr> <tr><td>39</td><td>1 C x 150</td><td>Un Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098385</td></tr> <tr><td>40</td><td>1 C x 300</td><td>Un Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098393</td></tr> <tr><td>41</td><td>1 CX630</td><td>Armoured</td><td>Cu. Cond. XLPE/FRLS PVC Cable</td><td>PY9755098407</td></tr> <tr><td>42</td><td>1 CX1000</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098415</td></tr> <tr><td>43</td><td>3 CX2.5</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098423</td></tr> <tr><td>44</td><td>3.5CX25</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098431</td></tr> <tr><td>45</td><td>1CX120</td><td>Un Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098500</td></tr> <tr><td>46</td><td>4CX2.5</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098518</td></tr> <tr><td>47</td><td>1CX25</td><td>Un Armoured</td><td>Cu. Cond XLPE/FRLS PVC Flexible Cable</td><td>PY9755098526</td></tr> <tr><td>48</td><td>2CX2.5</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098534</td></tr> <tr><td>49</td><td>2CX4</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098542</td></tr> <tr><td>50</td><td>2CX6</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098550</td></tr> <tr><td>51</td><td>2CX10</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098569</td></tr> <tr><td>52</td><td>2CX16</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098577</td></tr> <tr><td>53</td><td>2CX25</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098585</td></tr> <tr><td>54</td><td>2CX35</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098593</td></tr> <tr><td>55</td><td>2CX50</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098607</td></tr> <tr><td>56</td><td>2CX70</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098615</td></tr> <tr><td>57</td><td>2CX95</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098623</td></tr> <tr><td>58</td><td>2CX120</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098631</td></tr> <tr><td>59</td><td>2CX150</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098640</td></tr> <tr><td>60</td><td>2CX185</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098658</td></tr> <tr><td>61</td><td>2CX240</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098666</td></tr> <tr><td>62</td><td>2CX300</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098674</td></tr> <tr><td>63</td><td>1CX70</td><td>Un Armoured</td><td>Cu. Cond XLPE/FRLS PVC Flexible Cable</td><td>PY9755098682</td></tr> <tr><td>64</td><td>1CX150</td><td>Un Armoured</td><td>Cu. Cond XLPE/FRLS PVC Flexible Cable</td><td>PY9755098690</td></tr> <tr><td>65</td><td>1CX35</td><td>Un Armoured</td><td>Cu. Cond XLPE/FRLS PVC Flexible Cable</td><td>PY9755098704</td></tr> <tr><td>66</td><td>1CX300</td><td>Armoured</td><td>Cu. Cond. XLPE /FRLS PVC Cable</td><td>PY9755098712</td></tr> </table>					35	1 C x 25	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098342	36	1 C x 35	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098350	37	1 C x 50	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098369	38	1 C x 70	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098377	39	1 C x 150	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098385	40	1 C x 300	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098393	41	1 CX630	Armoured	Cu. Cond. XLPE/FRLS PVC Cable	PY9755098407	42	1 CX1000	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098415	43	3 CX2.5	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098423	44	3.5CX25	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098431	45	1CX120	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098500	46	4CX2.5	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098518	47	1CX25	Un Armoured	Cu. Cond XLPE/FRLS PVC Flexible Cable	PY9755098526	48	2CX2.5	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098534	49	2CX4	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098542	50	2CX6	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098550	51	2CX10	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098569	52	2CX16	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098577	53	2CX25	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098585	54	2CX35	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098593	55	2CX50	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098607	56	2CX70	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098615	57	2CX95	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098623	58	2CX120	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098631	59	2CX150	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098640	60	2CX185	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098658	61	2CX240	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098666	62	2CX300	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098674	63	1CX70	Un Armoured	Cu. Cond XLPE/FRLS PVC Flexible Cable	PY9755098682	64	1CX150	Un Armoured	Cu. Cond XLPE/FRLS PVC Flexible Cable	PY9755098690	65	1CX35	Un Armoured	Cu. Cond XLPE/FRLS PVC Flexible Cable	PY9755098704	66	1CX300	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098712
		35	1 C x 25	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098342																																																																																																																																																																
		36	1 C x 35	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098350																																																																																																																																																																
37	1 C x 50	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098369																																																																																																																																																																		
38	1 C x 70	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098377																																																																																																																																																																		
39	1 C x 150	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098385																																																																																																																																																																		
40	1 C x 300	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098393																																																																																																																																																																		
41	1 CX630	Armoured	Cu. Cond. XLPE/FRLS PVC Cable	PY9755098407																																																																																																																																																																		
42	1 CX1000	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098415																																																																																																																																																																		
43	3 CX2.5	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098423																																																																																																																																																																		
44	3.5CX25	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098431																																																																																																																																																																		
45	1CX120	Un Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098500																																																																																																																																																																		
46	4CX2.5	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098518																																																																																																																																																																		
47	1CX25	Un Armoured	Cu. Cond XLPE/FRLS PVC Flexible Cable	PY9755098526																																																																																																																																																																		
48	2CX2.5	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098534																																																																																																																																																																		
49	2CX4	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098542																																																																																																																																																																		
50	2CX6	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098550																																																																																																																																																																		
51	2CX10	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098569																																																																																																																																																																		
52	2CX16	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098577																																																																																																																																																																		
53	2CX25	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098585																																																																																																																																																																		
54	2CX35	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098593																																																																																																																																																																		
55	2CX50	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098607																																																																																																																																																																		
56	2CX70	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098615																																																																																																																																																																		
57	2CX95	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098623																																																																																																																																																																		
58	2CX120	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098631																																																																																																																																																																		
59	2CX150	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098640																																																																																																																																																																		
60	2CX185	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098658																																																																																																																																																																		
61	2CX240	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098666																																																																																																																																																																		
62	2CX300	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098674																																																																																																																																																																		
63	1CX70	Un Armoured	Cu. Cond XLPE/FRLS PVC Flexible Cable	PY9755098682																																																																																																																																																																		
64	1CX150	Un Armoured	Cu. Cond XLPE/FRLS PVC Flexible Cable	PY9755098690																																																																																																																																																																		
65	1CX35	Un Armoured	Cu. Cond XLPE/FRLS PVC Flexible Cable	PY9755098704																																																																																																																																																																		
66	1CX300	Armoured	Cu. Cond. XLPE /FRLS PVC Cable	PY9755098712																																																																																																																																																																		
Ref.																																																																																																																																																																						
Doc																																																																																																																																																																						



