

Allgemeine Anforderungen / GENERAL REQUIREMENTS:

Spannung:	24 V GS
VOLTAGE:	24 V DC
Spannungstoleranz:	min. +10 / -15%
VOLTAGE TOLERANCE:	min. +10 / -15%
Schutzart:	min. IP65 / NEMA 4
ENCLOSURE RATING:	min. IP65 / NEMA 4
Elektr. Anschluss:	mit Klemmkasten
ELECTRICAL CONNECTION:	VIA TERMINAL BOX
Temperaturbereich:	+5°C bis +70°C (+41°F bis +158°F)
TEMPERATURE RANGE:	+5°C to +70°C (+41°F to +158°F)

Magnetventil / SOLENOID VALVE:

Relative Einschaltdauer:	100%
ENERGIZED TIME:	CONSTANT RATED
Spulen-Isolationsklasse:	F
COIL ISOLATION CLASS:	F
Nennstrom	≤ 1 A
NOMINAL CURRENT	≤ 1 A

Stellungsgeber / POSITION TRANSMITTER:

Typ:	induktiv
TYPE:	INDUCTIVE
Schaltelementfunktion:	PNP Schließer
SWITCHING ELEMENT FUNCTION:	PNP NORMAL OPEN
Anschluss:	3-polig
CONNECTION:	3-POLE
Schirmung:	nicht erforderlich, aber verdrahtet wenn vorhanden
SHIELD:	NOT REQUIRED, BUT WIRED IF AVAILABLE

Klemmkasten / TERMINAL BOX:

Klemmkasten:	siehe Allgemeine Anforderungen
TERMINAL BOX:	SEE GENERAL REQUIREMENTS

Alles Equipment ist gemäß Anschlussplan auf dem Klemmkasten zu verkabeln
ALL EQUIPMENT TO BE WIRED ON THE TERMINAL BOX ACC. TO WIRING DIAGRAM

Reg. No:		DCC:		UNID:	
Project Code:					
Content Code:					
A		2010-02-19		First issue	
Rev.		Date		Description of Change	
© Siemens AG 2005 All Rights Reserved		The drawing contains information Confidential to Siemens Power Generation ; It is submitted in confidence and is to be used solely for the Purpose for which it s furnished and returned upon request. This drawing and such information is not to be reproduced. Transmitted disclosed or used otherwise, in whole or in part. Without written authorization from Siemens Power Generation.			
Protection Class: Confidential		Scale:		Specification: KUN 351.00	
Drawn: 2010-02-19 W. Schmidt		Title:			
Checked: 2010-02-19 B. Leu		Electr. Spec. Solenoid Valve/ Term Box/ 24V DC/ Indoor			
Released: 2010-02-19 M. Moser		E. Vorschrift Pneu. Magnetventil/KleKast/ 24V GS/ Innenaufstellung			
Siemens Power Generation		Lang. 000	Drawing No. / Identifier		Rev.
			DSPPG-0124555		
			A0000-002650/221		A
				Sheet 1-1	
				A4	

Do not scale work to dimensions shown