

Sl. No.	Pre –Qualification Criteria	Bidder remarked
1	Bidder shall be a manufacturer of the Quoted Submerged Arc Welding Wire and Flux (as a family)/ an authorized dealer of the same. If the offer is quoted by agent, letter of authorization and agreement duly signed by the manufacturer is required to consider the offer	
2	Bidder shall have successfully supplied the Submerged Arc welding Wire and Flux (as a family) to any govt. Organizations/ PSUs/ Public Ltd./ Company/Reputed Industries with minimum 1000 Kg. Purchase orders copies (2012 or later is only acceptable) to be submitted along with offer	
3	Bidder shall have successful experience for supplying Grade 92 - SAW Consumables to any govt. Organizations/ PSUs/ Public Ltd./ Company/Reputed Industries for SAW Grade 92 Wire and Flux (as a family). Purchase orders copies and related material test certificates to be submitted along with offer to consider the offer. Note: Successful experience means – supplied and accepted	
4	Quoted Welding Consumables brand name shall be provided along with offer.	
5	Mill (Manufacturing) address shall be provided along with offer.	
6	Mill capacity shall be provided along with offer	
7	BHEL/Authorized agencies reserves the right to inspect the item ordered at vendor's works.	

Sl. No.	Pre –Qualification Criteria	Bidder remarked						
8	Manufacturer shall submit manufacturing process flow chart (Raw material to finished product) along with offer.							
9	Manufacturer shall submit a valid ISO 9001 certificate or Quality management system certificate or Written down procedure.							
10	Bidder (Principle Supplier) shall have capacity to meet tender requirement.							
11	Creep data shall be provided for the quoted SAW Grade 92 Wire and Flux (as a family). <table border="1"> <thead> <tr> <th>Testing hours (minimum)</th><th>Testing Temperature (°C)</th><th>Stress Value (Mpa)</th></tr> </thead> <tbody> <tr> <td>1000</td><td>600</td><td>120</td></tr> </tbody> </table>	Testing hours (minimum)	Testing Temperature (°C)	Stress Value (Mpa)	1000	600	120	
Testing hours (minimum)	Testing Temperature (°C)	Stress Value (Mpa)						
1000	600	120						

Sign and seal of authorized person