

FORMAT OF PRICE BID

ANNEXURE-III

SL. NO.	DESCRIPTION OF ITEM	QUANTITY	UNIT	RATES (INR)/UNIT	TOTAL VALUE(RS.)	REMARKS
1	SUPPLY AND INSTALLATION OF COLOR COATED GALVALUME STEEL SHEET OF 0.50MM(MIN)TCT, HIGH STRENGTH (550 MPA YIELD STRESS MINIMUM) ANTI-CORROSIVE,COATED WITH ALLOY OF 55%(MIN) AL., 43.5%(MIN) ZINC AND FINISHED WITH RESIN COAT ON BOTH SURFACES TO (MIN)150 GRAMS SQM PAINT TYPE - SMP CONFORMING TO IS-14247, SIZE 1100MM(COV.)X4880MM	3797	Sqm			VARIATION IN LENGTH + 900MM & WIDTH + 180MM MAY BE ACCEPTABLE. JINDAL, JSW, TATA, EVEREST, BHUSHAN STEEL, ESSAR, CHARMINAR, KAMDHENU BRANDS
2	SUPPLY AND INSTALLATION OF GUTTERS GIRTH - 610MM COLOR COATED GALVALUME STEEL GUTTERS OF 0.50MM(MIN) TCT, HIGH STRENGTH (550MPA YIELD STRESS MINIMUM)ANTI-CORROSIVE COATED WITH ALLOY OF 55%(MIN) AL., 43.5%(MIN) ZINC AND FINISHED WITH RESIN COAT ON BOTH SURFACES TO 150 GRAMS SQM GRAMS PAINT TYPE - SMP	971	RM			JINDAL, JSW, TATA SHAKTI, BHUSHAN STEEL, CHARMINAR BRANDS
3	SUPPLY AND INSTALLATION OF RIDGES GIRTH-0 TO 610MM COLOR COATED GALVALUME STEEL RIDGES OF 0.50MM(MIN) TCT, HIGH STRENGTH (550 MPA YIELD STRESS MINIMUM) ANTI-CORROSIVE COATED WITH ALLOY OF 55%(MIN) AL.,43.5%(MIN) ZINC AND FINISHED WITH RESIN COAT ON BITH SURFACES TO 150 GRAMS SQM GRAMS PAINT TYPE - SMP	500	RM			JINDAL, JSW, TATA SHAKTI, BHUSHAN STEEL, CHARMINAR BRANDS
4	SUPPLY AND INSTALLATION OF DOWN TAKE PIPES GIRTH 400MM SQUIRE CONSTRUCTION COLOR COATED GALVALUME STEEL DOWN TAKE PIPES OF 0.50MM(MIN) TCT, HIGH STRENGTH(550MPA YIELD STRESS MINIMUM)ANTI-CORROSIVE, COATED WITH ALLOY OF 55%(MIN) AL.,43.5%(MIN) ZINC AND FINISHED WITH RESIN COAT ON BOTH SURFACES TO 150 GRAMS SQM GRAMS PAINT TYPE - SMP	385	Rm			JINDAL, JSW, TATA SHAKTI, BHUSHAN STEEL, CHARMINAR BRANDS
5	SUPPLY AND INSTALLATION OF DAY & LIGHT PANEL (FRP) OF 2MM THICK FRP OF SIZE 1.0M X 3.0M (FIBER SHEET) CONFORMING TO IS-14856, SIZE 1100MM(COVERING)X4880MM	714	Sqm			INTEC FRP, FIBRE TECH, EVEREST COMPOSITE, KANSAL COLOUR, SHRIYA FRP BRANDS
6	SUPPLY AND INSTALLATION OF PUFF PANEL TOP SHEET PROFILED WITH CREST - 32 MM, PITCH - 251 MM, SUPPLY WIDTH -1090 MM, PAINT TYPE -RMP BOTTAM SHEET PLAIN BOTH SHEETS ARE 0.50 MM COLOR COATED GALVALUME SHEETS OF 0.50 MM TCT, HIGH STRENGTH (550 MPA YIELD STRESS MINIMUM) ANTI-CORROSIVE GALVALUME STEEL SHEETS COATED WITH ALLOY OF 55% ALUMINUM, 43.5% ZINC AND FINISHED WITH RESIN COAT ON BOTH SURFACES TO 150 GRAMS SQM GRAMS MASS OF COATING (TOTAL BOTH SIDE AS PER ASTM-A792) WITH SILICON 1.5 %. IN MIDDLE (POLY URETHENE FOAM) PUFF WITH DENSITY OF 40 KG/M3. CONFORMING TO IS-14247, SIZE 1100MM(COV.)X4880MM	660	Sqm			JINDAL, JSW, TATA SHAKTI, BHUSHAN STEEL, CHARMINAR BRANDS
7	SUPPLY AND INSTALLATION OF 24" TURBO VENTILATOR ALONG WITH BASE SHEET BY REPLACING OF EXISTING SHEET (ASBESTOS OR GALVALUME)	26	Nos.			24" (NECK DIA) TURBO VENTILATOR (SEALED DOUBLE BALL BEARING) (42 VANES) ALONG WITH PROFILE BASE SHEET. AIR CREATIONS INDIA, GISCO, KANSAL COLOUR & SHRIYA FRP BRANDS.
	TOTAL AMOUNT					-
	GST@18%					-
	GROSS AMOUNT					-