

BHARAT HEAVY ELECTRICALS LIMITED
HPEP, RAMACHANDRAPURAM, HYDERABAD-32
(Township Administration Department)

Tender Notice No: HY/TA/OT-16/2020-21, Date: 26.12.2020

Name of Work: Maintenance of Road Works in Township Area-Rate Contract.

S.No	Description	Unit	Qty	Unit Rate	Amount (Rs)
1	2	3	4	5	6=4*5
1	Preparation and consolidation of sub grade with power road roller of 8 to 12 tonnes capacity after excavating earth to an average of 22.5cm depth dressing to camber and consolidating with road roller including making good the undulations etc. and re-rolling the sub grade and disposal of surface earth lead upto 50mtr	Sq.m	1050	48.45	50874.13
2	Extra for compaction of earth work in embankment under optimum moisture conditions to give at least 95% of the maximum dry density (proctor density)	Sq.m	1	6.13	6.13
3	Supplying and stacking at site				
a	90mm to 45mm size stone aggregate	Cu.m	22	768.85	16914.72
b	63mm to 45mm size stone aggregate	Cu.m	55	837.02	46036.08
c	53mm to 22.4mm size stone aggregate	Cu.m	85	905.13	76935.67
d	Good earth	Cu.m	85	206.21	17527.77
e	moorum	Cu.m	150	476.14	71420.32
4	Laying spreading and compacting stone aggregate of specified sizes to WBM specifications including spreading in uniform thickness hand picking rolling with 3 wheeled road/ vibratory roller 8-10 tonnes in stages to proper grade and camber applying and brooming requisite type of screening / binding material to fill up interstices of coarse aggregate watering and compacting to the required density.	Cu.m	210	261.14	54839.17
5	Scarifying metallised (water bound) road surface including disposal of rubbish lead upto 50m and consolidation of the aggregate received from scarifing with power road roller of 8 to 10 tonnes capacity	Sq.m	2	8.62	17.24
6	Dry stone pitching 22.5cm thick including supply of stones and preparing surface completes	Sq.m	4	262.04	1048.15
7	Cutting road and making good the same including supply of extra quantities of material ie aggregate moorum screening red bajri and labour required. Water bound macadam	Cu.m	2	773.09	1546.19
8	Engraving letters in hard Granite stone	per cm ht per letter	100	2.37	237.19
9	Providing and fixing precast reinforced cement concrete 1:1.5:3(1cement 1.5 coarse sand 3 graded stone aggregate 20mm nominal size) kilometres stones as per standard design including finishing smooth in 1:3 cement mortar (1cement fine sand) but excluding the cost of earth work concrete in foundation painting and lettering etc. which shall be paid for separately				
a	50x152.5x25cm size	Each	1	1794.69	1794.69
10	Cement concrete 1:2:4(1cement 2 coarse sand 4 grade stone aggregate 40mm nominal size) in pavements laid to required slope and camber in panels as required including consolidation finishing and tamping complete	Cu.m	1	2030.05	2030.05
11	Providing and laying design mix cement concrete in roads taxi tracks and runways having a minimum works test beam flexural strength of 30 kg per cm ² at 28days using not less than 430kg. Of cement per cum of finished concrete coarse sand and grade stone aggregate of 40mm nominal size in appropriate proportions as per specified design criteria approved by engineer in charge mechanically vibrated using needle and surface vibrators including steel form work with sturdy MS channel sections including curing and approved joint filler and filling construction joints and dummy joints with approved joint filler and primer including rounding of the edges and filling the grooves 10x25mm deep at top for construction joints and 10mmx50mm deep at top for dummy joints with joint sealing compound (conforming to grade B of IS 1834) including making necessary arrangements for expansion joints etc. all complete with readymix concrete.	Cu.m	1	1305.84	1305.84
12	Extra for providing and mixing hard crete of approved quality as per manufactures specification in cement concrete	Ltr	1	32.55	32.55

Signature of Tenderer

Accepting Authority

S.No		Description		Unit	Qty	Unit Rate	Amount (Rs)
1		2		3	4	5	6=4*5
13		Painting runway/ taxi track/ apron marking with adequate no of coats to give uniform finish with road marking paint of superior make as approved by the engineer in charge i/c cleaning the surface of all dirt scales oil grease and other foreign material etc., and lining out complete					
	a	New work (two or more coats)		Sq.m	259	73.18	18954.68
	b	Old work(one or more coats)		Sq.m	20	45.52	910.31
14		Painting road surface marking with adequate no of coats to give uniform finish with ready mixed road marking paint conforming to IS 164 on bituminous surface in white / yellow/black shade including cleaning the surface of all dirt scales oil grease and foreign material etc. complete					
	a	New work (two or more coats)		Sq.m	2	75.03	150.07
	b	Old work(one or more coats)		Sq.m	2	48.70	97.40
15		making bell mouth opening/ entrance of size 100x50x50cm for drainage pipe under footpath including providing cement concrete 1:3:6(1cement 3 coarse sand 6 grade stone aggregate 20mm nominal size) for shape of bell mouth including plastering providing and fixing precast RCC/SFRC slab including plastering with cement mortar 1:3(1 cement 3 fine sand) of 6 mm thickness on exposed surface of the slab and bell mouth including centring shuttering and neat cement punning inside the bell mouth etc. all completee		Each	1	858.15	858.15
16		Providing and fixing glow studs of size 100x20mm made of heavy duty body shall be moulded ASA (acrylic styrene acryloretite) or HIP (high impact polystyrene) or ABC having electronically welded micro prismatic lens with abrasion resistant coating as approved by engineer in charge. the cats eye shall support a load of 13635kg tested in accordance with ASTM D 4280. the slope of retro- reflective surface shall be 35 +/-5 degress to base. the reflective panels on both sides with at least 12cm of reflective area up each side. the luminance intensity should be as per the specification and shall be tested as described in ASTM I:809 as recommended in BS 873 part 4 :1973. the studs shall be fixed to the road surface using the adhesive conforming to IS as per procedure recommended by the manufacturer complete and as per direction of engineer in charge		Each	1	177.98	177.98
17		Providing and fixing concertina coil fencing with required dia 610mm(having 15nos round per 6metre length) up to 3m height of wall with existing angle iron Y shape placed 2.4m or 3.00m apart and with 9 horizontal RBT stud tied with GI staples and GI clips to retain horizontal including necessary bolts or GI barbed wire tied to angle iron all complete as per direction of engineer in charge with reinforced barbed tape(RBT) / spring core (2.5mm thick) wire of high tensile strength of 165kg/ sqmm with tape (0.52mm thick) and weight 43.478gm / metre (cost of MS angle CC blocks shall be paid separately)		Mts	1	204.47	204.47
18		Manufacturing supplying and fixing retro reflective sign boards made upof 2mm thick aluminium sheet, face to be fully covered with high intensityencapsulated type heat activated retro reflective sheeting conforming tototype - IV of ASTM-D 4956-01 in blue and silver white or other colourcombination including subject matter, message (bi-lingual), symbols andborders etc. as per IRC ; 67:2001, pasted on substrate by an adhesivebacking which shall be activated by applying heat and pressureconforming to class -2 of ASTM-D-4956-01 and fixing the same withsuitable sized aluminium alloy rivets @ 20 cm c/c to back support frameof M.S. angle iron of size 25x25x3 mm along with theft resistantmeasures, mounted and fixed with 2 Nos. M.S. angles of size 35x35x5mm to a vertical post made up to M.S. Tee section ISMT 50x50x6 mmwelded with base plate of size 100x100x5 mm at the bottom end andincluding making holes in pipes, angles flats, providing & fixing M.S.message plate of required size steel work to be painted with two or morecoats of synthetic enamel paint of required shade and of approved brand& manufacture over priming coat of zinc chromate yellow primer (verticalMS-Tee support to be painted in black and white colours).Backside of aluminium sheet to be painted with two or more coats of epoxy paint overand including appropriate priming coat including all leads and lifts etc.complete as per drawing , specification and direction of Engineer in charge					
Signature of Tenderer						Accepting Authority	

S.No		Description		Unit	Qty	Unit Rate	Amount (Rs)
1		2		3	4	5	6=4*5
	a	Mandatory / Regulatory sign boards of 900mm dia metre with part as length of 3750mm		Sq.m	1	3478.85	3478.85
	b	cautionary / warning sign boards of equilateral triangular shape having each side of 900mm with support length of 3650mm		Sq.m	1	2460.43	2460.43
19		Manufacturing supplying and fixing retro reflective overhead signage boards made up of 2mm thick aluminium sheet face to be fully covered with high intensity and encapsulated lens type heat activated retroreflective sheeting conforming to type - III of ASTM-D-4956-01 as approved by Engineer-in-charge letters, borders etc. as per IRC : 67-2001 in silver white with blue colour back ground and with high intensity grade, pasted on substrate by pressure sensitive adhesive backing which shall be activated by applying pressure conforming to class II of ASTM-D-4956-01 and fixing the same to the plate of structural frame work by means of suitable sized aluminium alloys, rivets or bolts & nuts @ 300mm centre to centre all along the periphery as well as in two vertical rows along with theft resistant measures including the cost of painting with two or more coats of epoxy paint in grey colour on the back side of aluminium sheet including appropriate priming coat. The rate includes the cost of rounding off the corners, lowering down the structural frame work from the gantry, fixing and erecting the same in position all complete as per drawings, specification and direction of the engineer-in-charge. (Structural frame work including M.S. plate to be provided separately. Rectangular area of the sheet only shall be measured for payment).					
	a	Overhead informative road signage	Sq.m	1	3438.71	3438.71	
20		Providing Retro-reflective regulatory sign board of size 900mm diameter made out of 2mm thick aluminium sheet, face to be fully covered with high intensity encapsulated lens type retro-reflective sheeting as approved by Engineer-in-charge. Letter, symbols, borders etc. will be as per IRC - 67 with required colour scheme on the boards and with the high intensity grade A. The aluminium sheet to be riveted to M.S. frame of angle iron of size 40x40x4mm. The boards will be fixed to 1 No. 50x50mm square post made of M.S. angle 50x50x4m, 4m long welded to the frame with adequate anti-theft arrangement. Sheet work to be painted with two or more coats of synthetic enamel paint over an under coat (primer) and back side of aluminium sheet to be painted with two or more coats of epoxy paint including appropriate priming coat complete in all respects as per direction of Engineer-in-charge.	Sq.m	1	3859.32	3859.32	
21		Providing and applying 2.5mm thick road marking strips (retro reflective) of specified shade / colour using hot thermoplastic material by fully / semi automatic thermoplastic paint applicator machine fitted with profile shoe glass beads dispenser propane tank heater and profile shoe heater driven by experienced operator on road surface including cost of material labour T & P cleaning the road surface of all dirt seals oil grease and foreign material etc. complete as per direction of engineer in charge and accordance with applicable specification	Sq.m	1	386.39	386.39	
22		providing and fixing post delineators (made of ABS body fitted with 2 nos 100mm dia) reflective and reflectors are mounted on MS pipe of 65mm dia duly power coated anti rust and theft steel not to be installed as per direction of engineer in charge	Each	1	432.71	432.71	
23		providing and laying 60mm thick factory made cement concrete interlocking paver block of M-30 grade made by block making machine with strong vibratory compaction and of approved size and design / shape laid in required colour and pattern over and including 50mm thick compacted as per the direction of engineer in charge	Sq.m	1	409.03	409.03	
24		Providing and laying at or near ground level factory made kerb stone of M-25 grade cement in position to the required line level and curvature jointed with cement mortar 1:3(1 cement 3 coarse sand) including making joints with or without grooves (thickness of joints except at sharp curve shall not be more than 5mm) including making drainage opening wherever required complete etc. as per direction of engineer in charge (length of finished kerb edgeing shall be measured for payment) precast CC kerb stone shall be approved by engineer in charge	Cu.m	1	3956.95	3956.95	
Signature of Tenderer				Accepting Authority			
25		Supplying and stacking of hard stone (for stone pitching) 22.5cm thick at site	Cu.m	1	463.95	463.95	

S.No		Description		Unit	Qty	Unit Rate	Amount (Rs)
1		2		3	4	5	6=4*5
26		Dry stone pitching 22.5mm thick laid in courses and required profile with hammer dressed stones having no side less than 15cm with minimum depth of 20cm including preparing the bedding surfaces etc, all complete(payment for stone to be made separately)		Sq.m	1	143.20	143.20
27		75mm thick back filling for pitching including supplying of required materials and consolidation etc. complete with				0.00	
	a	moorum		Sq.m	10	39.76	397.58
	b	stone aggregate 20mm nominal size		Sq.m	10	80.22	802.16
	c	Stone aggregate 40mm nominal size		Sq.m	10	74.19	741.87
28		Providing and laying CC pavement of mix M25 with ready mixed concrete from batching plant . The ready mixed concrete shall be laid and finished with screed board vibrator vacum dewatering process and finally finished by floating brooming with wire brush etc. complete as per specification and directions of engineer in charge (the panel shuttering work shall be paid for separately)		Cu.m	1	4763.59	4763.59
29		Deduct for using of M20 grade concrete instead of M25 grade concrete in CC pavement		Cu.m	1	130.28	130.28
30		Scarifying the existing bitumen road surface to a depth of 50mm and disposal of scarified material within all lifts and lead upto 1000mtr (by mechanical means)		Sq.m	1	2.30	2.30
31		Providing and laying Bituminous Macadam using crushed stone aggregates of specified grading premixed with bituminous binder and filler,transporting the hot mix to work site by tippers,laying with paver finisher equiped with lectronic sensor to the required grade,level and alignment and rolling with smooth wheeled,vibratory and tandem rollers to achieve the desired compaction and density, as per specifications,complete and as per directions of Engineer in charge.					
	a	40/50 mm compacted thickness with bitumen of grade VG-30(60/70 grade)@ 5.5% (Percentage by weight of total mix) and lime filler @ 3% (percentage by weight of aggregate) prepared in batch type Hot mix plant of 100-120 TPH capacity.etc. complete all as directed by Engineer-in-charge.		Cu.m	70	6003.48	420243.47
32		2.5 cm premix carpet surfacing (hot mix plant) with 2.25 cum and 1.12 cum of granite stone chippings of 13.2 mm and 11.2 mm size respectively per 100 sqm. and 52 kgs and 56 kgs of Hot Bitumen per cum of stone chippings of 13.2 mm and 11.2 mm size respectively including a tack coat with hot straight run bitumen including consolidation with road roller of 6 to 9 tonne capacity etc. complete. (tack coat to be paid for separately),with paving asphalt grade VG-10(80/100 grade) heated and then mixed with solvent at the rate of 70 gms per kg of asphalt all as directed by Engineer-in-charge.		Sq.m	1500	113.41	170118.54
33		Providing and applying tack coat using bitumen emulsion (Rapid setting) conforming with IS 8887-1995, on W.B.M./W.M.M. surface @ 0.40 kg/sqm by using emulsion pressure distributor including preparing the road surface and cleaning with mechanical broom etc., complete all as directed by Engineer-in-charge.		Sq.m	1300	6.64	8625.57
34		Providing and applying tack coat using hot straight run bitumen of grade VG- 10(80/100 grade), including heating the bitumen , spraying the bitumen with mechanically operated spray unit fitted on bitumen boiler, cleaning and preparing the existing road surface as per specifications. On bituminous surface @0.50 kg/Sqm all as directed by Engineer-in-charge.		Sq.m	400	18.67	7468.87
35		Providing,laying,spreading and compacting graded stone aggregate (size range 53 mm to 0.075 mm) to wet mix macadam(WMM) specification including premixing the material with water at OMC in mechanical mix plant,carriage of mixed material by tipper to site,for all leads & lifts,laying in uniform layers with mechanical paver finisher in sub-base/base course on well prepared surface and compacting with vibratory roller of 8 to 10 tonne capacity to achieve the desired density,complete as per specifications and directions of Engineer in charge.		Cu.m	1	1504.92	1504.92
36		Taking out existing kerb stones of all types from footpath/central verge ,including removal of mortar etc,disposal of unserviceable material to the dumping ground ,for which payment shall be made separately and stacking of serviceable material within 50 metre lead and as per direction of Engineer in charge.		Rmt	1	8.55	8.55
Signature of Tenderer				Accepting Authority			

S.No		Description		Unit	Qty	Unit Rate	Amount (Rs)
1		2		3	4	5	6=4*5
37		laying at or near ground level old kerb stones of all types in position to the required line,level and curvature,jointing with cement mortar 1:3 (1 cement : 3 coarse aggregate) including making joints with or without grooves (thickness of joints,except at sharp curve,shall not be more than 5 mm) including making drainage opening eherever required etc complete as per direction of Engineer in charge.(Length of finished kerb edging shall be measured for payment).(Old kerb stone shall be supplied by the department free of cost)		Rmt	1	11.78	11.78
38		Providing and laying at or near ground level factory made kerb stone of M-25 grade cement in position to the required line level and curvature jointed with cement mortar 1:3(1 cement 3 coarse sand) including making joints with or without grooves (thickness of joints expect at sharp curve shall not to more than 5mm) including making drainage opening wherever required complete etc. as per direction of engineer incharge(lenght of finished kerb edgeing shall be measured for payment) precast CC kerb stone shall be approved by engineer in charge		Rmt	1	3979.78	3979.78
39		Providing and laying premix bituminous macadam base course with stone aggregate of quality size and grading as specified in CPWD specification and straight run bitumen of grade 80/100 @ 4% by weight of total mix including hot mixing of stone aggregate and bitumen in hot mix plant, transporting mixed material and laying mixed material with paver finisher to the required level and grade, rolling with road roller of 8 to 10 tonne capacity to achieve the required compaction and densit of any thickness etc complete all as directed by Engineer-in-charge.		Cu.m	1	8039.39	8039.39
40		Providing and laying seal coat over prpared surface of road with bitumen heated in bitumen boiler fitted with the spray set spraying using 98 kg of bitumen of grade 80/100 and blinding surface with 0.90 cm of stone aggregate of 6.7 mm size (Passing 11.2 mm sieve and retained on 2.36 mm sievel per 100 sqm of road surgace including rolling and finishing with power road roller etc complete, all as directed by Engineer-in-charge.		Sq.m	1	55.29	55.29
41		Supply and fixing of kerb stones os size 1.00 M x 0.15 m x 0.30 m twice dressed exposed faces and pointing with CM 1:3 including necessary excavation and refilling the gaps etc., complete all as directed by Engineer-in-charge.		Rmt	1	506.23	506.23
42		supply of JCB		Hrs	20	632.79	12655.71
43		Conveyance by Manual or Mechanical means of Lime, Murram, building Rubbish including loading un-loading with lift of 50 m upto lead mentioned below all complete all as directed by Engineer in charge				0.00	
a		1 Km		Cu.m	9	52.39	471.52
b		2 Km		Cu.m	23	59.44	1367.21
c		3 Km		Cu.m	9	66.43	597.91
44		Providing radium sticker letters and arrow marks of approved colour and design and size. The base board will be supplied by the department and as directed by the Engineer-in-charge.		Sq.m	1	2278.52	2278.52
45		Painting with synthetic enamel paint of approved brand and manufacture to give an even shade (Iron work/Plastered surface/Signboards frames/wood work/Road speed breakers etc.)				0.00	
a		Two or more coats on new work		Sq.m	1200	41.88	50255.03
46		providing and laying 60mm thick factory made cement concrete interlocking paver block of M-30 grade made by block making machine with strong vibratory compaction and of approved size and design / shape laid in required colour and pattern over and including 50mm thick compacted as per the direction of engineer in charge		Sq.m	9	409.03	3681.29
47		Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centering shuttering finishing and reinforcement All work up to plinth level					
a		1:1.5:3(1cement 1.5 coarse sand 3 grade stone aggrigate 20mm nominal size)		Cu.m	4	2138.36	8553.43
b		1:2:4(1cement 2 coarse sand 4 grade stone aggrigate 20mm nominal size)		Cu.m	4	2194.08	8776.32
Signature of Tenderer		Reinforcement for RCC work including straightening, cutting bending placing in position and binding all complete.					Accepting Authority
a		Cold twisted bars		Kgs	45	5.83	262.37

S.No	Description		Unit	Qty	Unit Rate	Amount (Rs)						
1	2		3	4	5	6=4*5						
b	Hot rolled deformed bars		Kgs	9	5.83	52.47						
			Total Amount = Rs.		1099300.44							
Tender %	In Words		Figures									
Excess												
Less												
Estimate												
Notes:												
1	<i>Agency has to quote his prices by considering consolidated wages /Bonus payable to workers/ BHEL wages (which consists of state Govt. minimum wages and additional payments), allowances, materials involved in agency scope and other statutory dues payable to workers</i>											
2	Agency supervisor shall control the deployed work force. All the complaints shall be attend on priority basis as per the direction of Engineer-in-charge, shall not cause any damage to other areas. It is the agency responsibility to replace any damaged material / equipment with its own cost.											
3	Agency supervisor shall look after the working areas where the work has been carried out.											
4	The Agency supervisor shall do frequent checking.											
5	Agency supervisor is the overall in-charge of the work. Single Point of Contact (SPOC) during the work.											
6	Agency supervisor is to ensure workers are posted in their respective posts as per the directions of BHEL officer in-charge and record to be submitted daily.											
7	To ensure all the communication given by BHEL officer is to be passed to the workers promptly.											
8	To ensure required guidance, training etc. is provided to the workers at their respective works beside the regular briefing etc.											
9	Custodian of the daily attendance.											
10	Supervisor shall stay at the site until he total work is done and ensures the same for the workers too.											
11	Any incidents occurred during the work has to bring it to the notice of the BHEL officer in-charge and if necessary depends on the situation report has to submitted to the police station.											
12	Monitor the performance of the workers and their quality of service.											
13	Report of the daily work done shall be submitted daily with duly signed with stamp.											
14	Workers to alert and inform his superiors about any suspicious materials found within the Township Premises.											
15	Supervisor has to check each work area and alert the workers who are working at their respective place to perform their works as instructed by BHEL Engineer-in-charge.											
16	Supervisor along with supporting workers has to report to BHEL Officer in-charge and they have to follow the instructions given by the BHEL Officer in-charge.											
17	During any public functions / festivals / sports events / school events / BHEL Management events / any VIP visits / any elections etc., Supervisor has to follow the guidelines given by the BHEL Officer In-charge for performing the works.											
18	All group gathering by engaged work force / drunk & drive / accidents / group fighting / rash driving etc., has to be taken monitor by the Supervisor.											
19	Employees who are staying in Township area and given information about their Tanks shall be attend immediately as per the instructions of BHEL Officer In-charge.											
20	Frequent checking of work spot as per the requirement need to done. Proper report need to submit by the supervisor.											
21	As per the time-to-time instructions given by the BHEL management, supervisor along with their staff has to work with the given instructions.											
22	During the execution of contract, if required, agency shall work on Sundays and holidays also as per the direction of Engineer-in-charge.											
23	Penalty as per the NIT clause 2.1.36 shall be applicable.											