

1. 2 X 500 MW NTPC MOUDA ST-I FGD
2. 3 X 660 MW NORTH KARANPURA FGD
3. 3 X 660 MW NTPC BARH ST-I FGD
4. 3 X 660 MW NPGCPL NABINAGAR STPP -FGD
5. 2 X 660 MW NTPC BARH ST-II FGD
6. 2x250 MW NSPCL BHILAI TPP FGD
7. 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD
8. 3X200+3X500+1X500 MW NTPC KORBA TPP FGD
9. 4X250 MW BRBCL NABINAGAR FGD

VOLUME – II

**TECHNICAL SPECIFICATION FOR
DISTRIBUTION BOARDS**

SPECIFICATION NO: PE-RC-999-558-E005, REV-0



**BHARAT HEAVY ELECTRICALS LIMITED
POWER SECTOR
PROJECT ENGINEERING MANAGEMENT
NOIDA, UTTAR PRADESH, INDIA – 201301**

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		CONTENTS SHEET	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
		SHEET 1 OF 1	

CONTENTS

<u>S. NO.</u>	<u>DESCRIPTION</u>	<u>NO. OF SHEETS</u>
01	SECTION - I	
	COMPLIANCE CERTIFICATE	2
	SPECIFIC TECHNICAL REQUIREMENT	4
	ATTACHMENT I - DOCUMENTS REQUIRED AFTER AWARD OF LOI	1
	DATA SHEET-A	10
	SUB-VENDOR LIST	5
	DATA SHEET-C	8
02	SECTION - II	
	GENERAL TECHNICAL REQUIRMENTS	22
	QUALITY PLAN	2

TOTAL NUMBER OF SHEETS: 55

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
		SHEET 1 OF 20	

SECTION – I

SPECIFIC TECHNICAL REQUIREMENTS

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
		SHEET 2 OF 20	

COMPLIANCE CERTIFICATE

The bidder shall confirm compliance to the following by signing/ stamping this compliance certificate and furnishing same with the offer.

1. The scope of supply, technical details, construction features, design parameters etc. shall be as per technical specification & there are no exclusion/ deviation with regard to same.
2. There are no deviation with respect to specification other than those furnished in the 'schedule of deviations'.
3. Only those technical submittals which are specifically asked for in NIT to be submitted at tender stage shall be considered as part of offer. Any other submission, even if made, shall not be considered as part of offer.
4. Any comments/ clarifications on technical/ inspection requirements furnished as part of bidder's covering letter shall not be considered by BHEL, and bidder's offer shall be construed to be in conformance with the specification.
5. Any changes made by the bidder in the price schedule with respect to the description/ quantities from those given in BOQ-Cum-Price schedule of the specification shall not be considered (i.e. technical description & quantities as per specification shall prevail).

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
SHEET 3 OF 20			

1.0 SCOPE OF SUPPLY

- 1.1 Design, manufacture, assembly, inspection & testing at vendor's/ sub-vendor's works, proper packing and delivery to site of LIGHTING DB/ WELDING DB & LIGHTING PANELS as mentioned in different sections of this specification, complete with all accessories for efficient and trouble-free operation.
- 1.2 Standard technical requirements of LIGHTING DBs/ WELDING DBs & LIGHTING PANELS are indicated in Section-II. Project specific requirements/changes are listed in Section-I.
- 1.3 The stipulations of Section-I, followed by those of Data Sheet-A shall prevail and govern in case of conflict between the corresponding requirements of Section-I and Section-II.
- 1.4 Review of sub-vendor's documents by the vendor shall not relieve the vendor from the responsibility of design & supply as per contract / relevant standards.
- 1.5 The documents shall be in English language and MKS system of units.

2.0 BILL OF QUANTITIES:

- 2.1 Quantity requirements shall be as per BOQ-cum-price schedule as part of NIT.
- 2.2 Clause 10.2 of Section II to be read as below: -

Erection & commissioning spares are included in the bidder's scope of supply. Bidder to furnish list of E&C spares in the relevant schedules of the Bid Form and Price Schedules. (if applicable).

3.0 SPECIFIC TECHNICAL REQUIREMENTS

S.no	Reference clause no of section-II (if any)	Specific requirement / change
1	Clause no 3.1.3 : Lighting / Welding transformer	Each AC Lighting Distribution Board (LDB) shall be fed from 415V / 415V, 50kVA(minimum) isolating transformer & Each Welding Distribution Board (LDB) shall be fed from 415V / 415V, 100kVA isolating transformer. The lighting / welding

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
SHEET 4 OF 20			

		transformer may, preferably, be located inside the LDB / Welding DB panel itself. Lighting / Welding transformers shall be dry type, natural air cooled with class B insulation or better. Impedance of lighting / Welding transformer shall be so selected that the fault level of lighting /Welding system shall be reduced to 3 to 5 KA. Lighting / Welding transformers shall be tested as per IS: 2026. Off circuit tap changer with $\pm 2.5\%$ and $\pm 5\%$ tapping shall be provided. The transformer terminal box shall have IP-52 degree of protection.
2	Clause no 3.2.1 : General requirements of lighting panel	Add: (a) Lighting panels shall be constructed out of 2 mm thick CRCA sheet steel. The door shall be hinged and the panel shall be gasketed to achieve specified degree of protection. Lighting panels shall be powder coated with color shade RAL9002. Lighting panels shall have min. IP55 degree of protection. (b) All MCBs/isolators/Switches/Contactors etc. shall be mounted inside the panel and a fibre glass sheet shall be provided inside the main door such that the operating knobs of MCBs etc., shall project out of it for safe operation against accidental contact. (c) Terminal blocks shall be 1100 V grade, clip-on stud type, made up of polyamide 6.6 or better suitable for terminating multicore 35 or 70 Sq. mm. stranded aluminium conductor incoming cable and 10 Sq. mm. stranded aluminium conductor for each outgoing circuits voltage. All terminals shall be shrouded, numbered and provided with identification strip for the feeders. (d) MCB's shall be current limiting type with magnetic and thermal release suitable for manual closing and automatic tripping under fault condition. MCB's shall have short circuit

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020 SHEET 5 OF 20

	interrupting capacity of 9 KA rms. MCB knob shall be marked with ON/OFF indication. A trip free release shall be provided to ensure tripping on fault even if the knob is held in ON position. MCB terminal shall be shrouded to avoid accidental contact. (e) Contactors of AC Lighting panels shall be 3 no's, 32 A, 3 pole continuous duty MCB, load make-break type suitable for 415 V, 3 phase 4 wire system. HRC fuses with suitable mounting base of 125A shall be provided in the incomer of Contactors in the LP. (f) DC switches shall be rotary type, 2 pole, continuous duty, load break type, quick make quick break, suitable for 220 V DC, 2 wire system. Switch knob shall be provided with ON/OFF indication. (g) Programmable Digital Timer shall be Electronic Astronomical Almanac Time switch with battery back-up of min. TEN years, 4 Digit LED display, 24 hours range, manual override facility, 10 Amp 3 relay output, with NO/NC Contacts suitable for operation on 240V single phase AC supply.
--	---

4 Inspection & Testing

Standard Quality Plan is enclosed. Inspection shall be carried out as per Quality Plan without any implication on cost and delivery. There shall be no commercial implication to BHEL on account of any changes in QP during contract stage.

All equipment to be supplied shall be of type tested design. During detail engineering, the contractor shall submit for Owner's approval the reports of all the type tests as listed in this specification and carried out within last ten years from date of bid **opening (Mouda : 26.02.18; Barh-I : 01.08.18 ; Barh-II : 26.02.18; 3x660 MW Nabinagar : 22.12.17; North Karanpura : 22.06.18 , Korba : 14.02.19, Ramagundam : 14.02.19, Bhilai : 04.12.18, 4x 250 MW Nabinagar : 22.12.17)** . These reports should be for the test conducted on the equipment similar to those proposed to be supplied under this contract and the test(s) should have been either conducted at an

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
		SHEET 6 OF 20	

independent laboratory or should have been witnessed by a client.

However if the contractor is not able to submit report of the type test(s) conducted within last ten years from the date of bid opening, or in the case of type test report(s) are not found to be meeting the specification requirements, the contractor shall conduct all such tests under this contract at no additional cost to the owner either at third party lab or in presence of client/owners representative and submit the reports for approval.

All acceptance and routine tests as per the specification and relevant standards shall be carried out. Charges for these shall be deemed to be included in the equipment price.

Selection of samples for type test, acceptance test & routine test and acceptance criteria for all the items shall be as per relevant I.S

GALVANISING TESTS:

The quality of galvanizing shall be smooth, continuous, free from flux stains and shall be inspected visually.

In addition following tests shall be conducted as acceptance tests.

(a) Uniformity of coating - The coating of any article shall withstand for one (1) minute dips in standard copper sulphate solution without the formation of an adherent red spot of metallic copper upon the basic metal.

(b) The quality of cadmium/zinc plating on items with screw threads shall be free from visible defects such as unplated areas, blisters and modules and shall be inspected visually.

(c) In addition, the plating thickness shall be determined microscopically/ chemically or electronically.

5.0 DOCUMENTATION

5.1 Documents required after award of contract shall be as per Attachment-I (to be submitted by successful bidder).

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
		SHEET 7 OF 20	

ATTACHMENT – I

DOCUMENTS REQUIRED AFTER AWARD OF LOI

SL. No.	DOCUMENT TITLE	DOCUMENT NO.	CATEGORY
1	TECHNICAL DATASHEET OF LIGHTING DISTRIBUTION BOARDS	PE-V0-XXX-558-E501	PRIMARY
2	QUALITY PLAN OF LIGHTING DISTRIBUTION BOARDS	PE-V0-XXX-558-E902	PRIMARY
3	GA DRAWING OF LIGHTING DISTRIBUTION BOARDS	PE-V0-XXX-558-E502	PRIMARY
4	SCHEME DRAWING OF LIGHTING DISTRIBUTION BOARDS	PE-V0-XXX-558-E503	PRIMARY
5	DATASHEET OF LIGHITNG PANEL	PE-V0-XXX-558-E504	PRIMARY
6	QUALITY PLAN OF LIGHTING PANEL	PE-V0-XXX-558-E904	PRIMARY
7	GA DRAWING OF LIGHTING PANEL	PE-V0-XXX-558-E505	PRIMARY
8	SCHEME DRAWING OF LIGHTING PANEL	PE-V0-XXX-558-E506	PRIMARY
9	GA DRAWING OF LIGHITNG TRANSFORMER	PE-V0-XXX-558-E507	PRIMARY
10	QUALITY PLAN OF LIGHITNG TRANSFORMER	PE-V0-XXX-558-E903	PRIMARY
11	TYPE TEST REPORTS FOR LIGHTING DISTRIBUTION BOARDS	PE-V0-XXX-558-E508	SECONDARY
12	TYPE TEST REPORTS FOR LIGHTING PANEL	PE-V0-XXX-558-E509	SECONDARY
13	TYPE TEST REPORTS FOR LIGHTING TRANSFORMER	PE-V0-XXX-558-E510	SECONDARY

***XXX IN THE DOCUMENT NUMBER PERTAINS TO FOLLOWING:**

NORTH KARANPURA: 441
 BARH-I: 442
 BARH-II: 443
 MOUDA: 444
 NABINAGAR (3 X 660) 457
 RAMAGUNDAM 467
 KORBA 466

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
		SHEET 8 OF 20	

NABINAGAR(4X250) 463
BHILAI 468

Note:

1. The above list of drawings and documents is indicative.
2. Document submission and resubmission shall be done through document management system (DMS).
3. R-0 submission within 14 days from PO & subsequent revisions within 10 days of comments received from BHEL.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
SHEET 9 OF 20			

DATA SHEET -A

S. No.	Description	Unit	Value	
1.0	SYSTEM DESIGN DATA			
1.1	Design ambient	°C	50	
1.2	AC Supply			
a)	Rated voltage	V	415	
b)	Rated frequency	Hz	50	
c)	Voltage variation (permissible)	%	+10% to -10%	
d)	Frequency variation (permissible)	%	+5% to -5%	
e)	Combined voltage & frequency variation (sum of absolutes permissible)	%	10%	
f)	System fault level & duration	kA, sec.	50kA for 1 sec.	
1.3	DC Supply			
a)	Rated voltage	V	220	
b)	Voltage variation (permissible)	%	+10% to -15%	
c)	System fault level and duration	kA, Sec	20kA for 1 sec.	
2.0	APPLICABLE STANDARDS			
	IS 60947	Low voltage switchgear and controlgear		
	IS 11171	Dry type transformers		
	IS 13703	Low voltage fuses for voltages not exceeding 1000V AC or 1500 V		
	IS 10118	Code of practice for selection, installation and maintenance of switchgear and controlgear		
	IS 60898	Electrical Accessories - circuit breakers for over protection for household and similar installations		
	IS 1901	Visual indicator lamps		

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
SHEET 10 OF 20			

	IS 60079 IS 5572 IS:2551	Explosive atmospheres Classification of hazardous areas (other than mines) having flammable gases and vapours for electrical installation Danger notice plates					
3.0	LIGHTING/ WELDING DISTRIBUTION BOARDS						
3.1	Operational Front		Single Front				
3.2	Type of execution of modules (functional unit)		☒ Fixed ☐ Draw out				
3.3	Type of sheet steel		CRCA				
3.4	Sheet metal thickness (minimum)						
a)	Non-load bearing covers	mm	2.0 mm				
b)	Non-load bearing partitions	mm	2.0 mm				
c)	Load bearing members	mm	2.0 mm				
d)	Frames	mm	2.0 mm				
e)	Door	mm	2.0 mm				
f)	Withdrawable unit (if applicable)	mm	2.0 mm				
3.5	Cable alley width (minimum)	mm	400				
3.6	Bus bar material		☒ Aluminium grade E 91E				
3.7	Earth bus bar material		☒ GI Strip ☐ Aluminium ☐ Copper				
3.8	Degree of Protection						
a)	Main Panel		IP-54				
b)	Transformer cubicle		IP-42 , IP-52 for transformer terminal box.				
3.9	Gland plate thickness	mm	3.0				
3.10	AC LDB/ WDB						

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
		SHEET 11 OF 20	

a)	No. of Incomers		☐ One ☒ Two			
b)	Bus coupler required		☒ Yes ☐ No			
c)	Incomer and Bus coupler rating	A	As per transformer rating			
d)	Type of Incomer and Bus coupler		☒ TPN SFU ☐ MCCB			
e)	Type of Outgoing Feeders		☒ TPN SFU ☐ MCCB			
f)	Outgoing feeders rating	A	63			
g)	Cable entry		☒ Bottom ☐ Top			
3.11	Lighting Transformer					
a)	Rating	kVA	100 / 50			
b)	Type of cooling		Air natural			
c)	Voltage ratio	V	415/433 or 415/415 (* Refer note 1)			
d)	Rated frequency	Hz	50			
e)	No. of phases		3			
f)	Vector group		Dyn1 (* refer note-1)			
g)	Off circuit taps					
	Tap range, steps	%	+5% to -5% in steps of 2.5%			
	Voltage of each tap	V	As per manufacturer's data			
h)	Impedance at rated current, frequency at 75 °C	%	As per IS			
i)	Rated current					
	Primary	A	As per manufacturer's data			
	Secondary	A	As per manufacturer's data			
j)	Transformer type		☐ Cast resin ☒ Encapsulated (Applicable for Mouda Project only : 4 no 50 kVA & 4 no 100 kVA) ☒ Non-Encapsulated			

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
SHEET 12 OF 20			

k)	Transformer winding insulation		Class-B or better	
l)	Transformer winding insulation temperature rise limit		90 degree C above 50 degree C. ambient	
n)	Type of ventilation arrangement provided for transformer enclosure		As per manufacturer's data	
o)	Winding conductor material		Copper	
p)	Iron loss at 50 Hz and 100% rated voltage	kW	As per manufacturer's data	
q)	Copper loss at rated load at 75 °C	kW	As per manufacturer's data	
r)	Regulation at full load at 75 °C and 0.8 p.f. lagging		As per manufacturer's data	
s)	Weight	kg	As per manufacturer's data	
3.12	DC LDB			
a)	No of incomers		☒ One ☐ Two	
b)	DC incomer type		DP Switch fuse unit with contactor	
c)	DC incomer rating		125	
d)	AC incomer type		NA	
e)	AC incomer rating		NA	
f)	Buscoupler required		☐ Yes ☒ No	
g)	Incomer and bus coupler rating	A	125	
h)	Type of bus coupler		☐ SFU ☐ DP MCCB	
i)	Type of outgoing feeders		☒ DP SFU ☐ MCCB ☐ DP MCB	
j)	Outgoing feeders rating	A	32	
k)	Changeover required in DC LDB		☐ Yes (Converter for Conversion of AC to DC) ☒ No	
l)	Provision of manual override		☐ Yes ☐ No	

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
		SHEET 13 OF 20	

m)	Cable entry		☒ Bottom	☐ Top	
4.0	LIGHTING PANELS				
4.1	Application		☐ Indoor	☐ Outdoor	☒ Both
4.2	Type of sheet steel		CRCA		
4.3	Sheet metal thickness (minimum)		2.0		
3.4	Degree of Protection				
a)	Indoor panel		IP-55		
b)	Outdoor panel		IP-55, Weatherproof		
c)	Canopy in outdoor panel		☒ Yes	☐ No	
4.5	Bus bar material		☒ Aluminium	☐ Copper	
4.6	Earth bus bar required		☒ Yes	☐ No	
4.7	Earth bus bar material (if applicable)		☒ GI Strip	☐ Aluminium	☐ Copper
4.8	Gland Plate	mm	3.0		
4.9	Earthing studs required		☒ Yes	☐ No	
4.10	Hinged door with locking facility		☒ Yes	☐ No	
4.11	AC Lighting Panel				
a)	Incomer rating	A	63A for LP and SLP		
b)	Type of Incomer		☒ TPN SFU ☒ TPN MCB ☒ TP MCB (* Refer note 1)		
c)	Earth Leakage Circuit Breaker (ELCB) in incomer required		☒ Yes	☒ No (Applicable for North Karanpura Project only)	
d)	Type of Outgoing Feeders (non-flameproof panel)		☒ SPN MCB	☐ TPN MCB	☒ SP MCB (* Refer note 1)
e)	Timer required for indoor		☒ Yes	☐ No	

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
SHEET 14 OF 20			

	panel						
f)	Timer required for outdoor panel		☒ Yes	☐ No			
g)	Timer required Street Light panel/ High mast feeder pillar		☒ Yes	☐ No			
h)	Photocell required for Street Light panel/ High mast feeder pillar		☒ Yes	☐ No			
i)	Outgoing feeders rating	A	20				
4.12	DC Lighting panel						
a)	Incomer rating	A	32				
b)	Type of incomer		☒ DP SFU	☐ DP MCCB			
c)	Type of outgoing feeders (non- flameproof panel)		☒ DP MCB				
d)	Type of outgoing feeders (flameproof panel)						
e)	Outgoing feeders rating	A	20				
5.0	COMPONENTS OF LIGHTING SYSTEM EQUIPMENT						
5.1	Moulded Case Circuit Breaker (MCCB)						
a)	Rated voltage	V	415				
b)	Number of poles		TPN				
c)	Rated short circuit duty	kA	50				
d)	Rated breaking capacity (rms)	kA	50				
e)	Rated making current (peak)	kA	105				
f)	Release with short circuit		☒ Yes	☐ No			
g)	Release with overload		☒ Yes	☐ No			
h)	Release with under voltage		☐ Yes	☒ No			
i)	Auxiliary contacts						

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
SHEET 15 OF 20			

	Numbers	NO+NC	2NO + 2NC				
	Rating	A	As per manufacturer data				
5.2	Switch-Fuse Unit						
a)	Utilisation category for main contacts		AC23				
b)	Number of poles		TPN				
5.3	Miniature Circuit Breaker						
a)	SPN MCB rating (min)	A	Refer Sl. No. 3 & 4				
b)	DP MCB rating (min)	A	Refer Sl. No. 3 & 4				
c)	TPN MCB rating (min)	A	Refer Sl. No. 3 & 4				
d)	Short time rating	kA	9				
e)	Magnetic short circuit protection required		[√] Yes [] No				
f)	Thermal overload protection required		[√] Yes [] No				
5.4	Current Transformer						
a)	Type		Cast resin				
b)	Secondary current rating	A	[√] 1 [] 5				
c)	Burden	VA	10				
d)	Accuracy class		1.0				
e)	Instrument Safety Factor		<5				
5.5	Voltage Transformer						
a)	Type		Cast resin				
b)	Secondary terminal voltage (phase-phase)	V	110 V				
c)	Burden	VA	10				
d)	Accuracy class		1.0				

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
SHEET 16 OF 20			

e)	Winding configuration		Star/ Star				
f)	System grounding		[√] Effective [] Non-effective				
5.6	Indicating Meters						
5.6.1	Ammeter						
a)	Type		Analog				
b)	Shape		Square				
c)	Size		96mm x 96mm				
d)	Accuracy		2.0				
e)	Current coil rating	A	1				
f)	Angle of deflection	deg	90				
5.6.2	Voltmeter						
a)	Type		Analog				
b)	Shape		Square				
c)	Size		96mm x 96mm				
d)	Accuracy		2.0				
e)	AC voltage coil rating	V	0-500				
f)	DC voltage coil rating	V	0-250				
g)	Angle of deflection	deg	90				
5.6.3	Energy meter (if applicable)						
a)	Type		[√] Analog [] Digital				
b)	Accuracy		1.0				
c)	Current coil rating	A	1				
d)	Voltage coil rating	V	0-500				
5.7	Power Contactors						

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
SHEET 17 OF 20			

a)	Coil voltage (nominal)						
	AC contactors	V	240				
	DC contactors	V	220				
b)	Current rating of contacts						
	Power	A	As per manufacturer data				
	Control	A	As per manufacturer data				
5.8	Under voltage relay						
a)	Type		☒ Electromagnetic ☐ Static				
b)	Coil voltage rating	V	110				
c)	Means for in-built testing provided		As per manufacturer data				
5.9	Timer						
5.9.1	Time switch						
a)	Type		Digital synchronous				
b)	Range	hr	0-24				
c)	Coil voltage rating	V	240				
5.10	Selector switch						
a)	Type of selector switch		☒ Stay put ☐ Wing knob				
b)	Lockable		☐ Yes ☒ No				
5.11	Push Button						
a)	Voltage grade	V	500				
b)	Potential free contacts		2NO+2NC				
5.12	Indicating Lamps						

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999-558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
SHEET 18 OF 20			

a)	Lens Colour						
	ON condition		Red				
	OFF condition		Green				
b)	Circuit voltage	V	240V				
5.13	Cable Glands		By vendor for all incoming and outgoing cables [Cable sizes shall be informed during detail engineering]				
a)	Type		☒ Double compression ☐ Single compression				
b)	Material		Brass				
c)	Nickel Plating provided		☒ Yes ☐ No				
d)	Flameproof glands with flameproof equipment		☒ Yes ☐ No				
5.14	Cable Lugs		By vendor for all incoming and outgoing cables [Cable sizes shall be informed during detail engineering]				
a)	Type		Crimping type/ ring type				
b)	Material		Tinned copper				
6.0	PAINTING						
6.1	Paint shade						
a)	LDBs		Two coats of Red oxide primer followed by two coats of Powder coated, colour shade 9002				
b)	LPs		Two coats of Red oxide primer followed by two coats of Powder coated, colour shade 9002				
6.2	Paint Finish						
a)	Interior		☐ Matt ☒ Semi-glossy				
b)	Exterior		☒ Semi-glossy ☐ Full-glossy				
6.3	Paint Thickness	Microns	80				

Note :

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
		SHEET 19 OF 20	

1. *: All applicable variants are provided in Datasheet-A. Project specific requirement shall be Intimated during contract stage. Same shall be provided by vendor without any cost implication to BHEL.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999- 558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE: 05.01.2020
		SHEET 20 OF 20	

ANNEXURE-1

SUB-VENDOR LIST

(TENTATIVE)

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
ITEM CODE	ITEM/SERVICE DESCRIPTION	SL NO.	VENDOR CODE	VENDOR NAME	ADDRESS	
ES1	AC CONTACTORS	1	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA	
	AC CONTACTORS	2	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032	
	AC CONTACTORS	3	E1144	TELEMECHANIQUE/ SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	
	AC CONTACTORS	4	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI-110015	
	AC CONTACTORS	5	B04	BCH	20/4, MATHURA ROAD, FARIDABAD, HARYANA-121006	
ES2	AC LOAD BREAK SWITCH	1	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032	
	AC LOAD BREAK SWITCH	2	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI-110015	
	AC LOAD BREAK SWITCH	3	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA	
	AC LOAD BREAK SWITCH	4	E1076	KAYCEE	KAYCEE INDUSTRIES LTD., C/O-CMS COMPUTERS LTD., 35A, REAR BLDG., KILOKARI, NEW DELHI-110014	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
	PE-RC-999-558-E005					
ES3	AC LOAD BREAK SWITCH	5	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI-110020	
	AC MCCB	1	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI-110020	
	AC MCCB	2	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	
	AC MCCB	3	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA	
	AC MCCB	4	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032	
	AC MCCB	5	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI-110015	
	AC MCCB	6	C02	CROMPTON GREAVES	RAIL TRANSPORTATION SYSTEMS,VANDANA BUILDING, 11, TOLSTOY MARG, TOLSTOY MARG, NEW DELHI, DL 110001	
	ACDB/ DCDB DRAWOUT TYPE	1	EC05	ELECTRO CONTROLS & DEVICES	M/S ELECTRO CONTROLS & DEVICES, F-41, SITE-C, SURAJPUR INDUSTRIAL AREA GREATER NOIDA	
	ACDB/ DCDB DRAWOUT TYPE	2	KM1	KMG ATOZ SYSTEMS	UTTAR PRADESH :201308 C-49, SECTOR-81-NOIDA-201305	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
ES4	ACDB/ DCDB DRAWOUT TYPE	3	E1019	ASIATIC	A-58 NARAINA IND. AREA, PHASE-I , NEW DELHI 110028	
	ACDB/ DCDB DRAWOUT TYPE	4	E05	UNILEC ENGINEERS PVT. LTD.	BEHRAMPUR INDUSTRIAL AREA, BEGAMPUR KHATOLA ROAD, GURGAON-122001	
	ACDB/ DCDB DRAWOUT TYPE	5	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI-110020	
	ACDB/ DCDB DRAWOUT TYPE	6	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI-110015	
	ACDB/ DCDB DRAWOUT TYPE	7	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032	
	ACDB/ DCDB DRAWOUT TYPE	8	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA	
	ACDB/ DCDB FIXED TYPE	1	EC05	ELECTRO CONTROLS & DEVICES	M/S ELECTRO CONTROLS & DEVICES, F-41, SITE-C, SURAJPUR INDUSTRIAL AREA GREATER NOIDA UTTAR PRADESH :201309	
	ACDB/ DCDB FIXED TYPE	2	J01	JASPER ENGINEERS PVT. LTD.	A-23, SECTOR - 8, NOIDA-201301	
	ACDB/ DCDB FIXED TYPE	3	JC01	JACKSON ENGINEERS	A-43, HOSEIRY COMPLEX, OPPOSITE NSEZ, NOIDA-201305	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
	PE-RC-999-558-E005				
ES5	ACDB/ DCDB FIXED TYPE	4	S02	SPACEAGE SWITCHGEARS LTD.	68 & 13-A INDUSTRIAL DEVELOPMENT COLONY, MEHRAULI ROAD GURGAON, HARYANA-122001
	ACDB/ DCDB FIXED TYPE	5	KM1	KMG ATOZ SYSTEMS	C-49, SECTOR-81-NOIDA-201305
	ACDB/ DCDB FIXED TYPE	6	E1019	ASIATIC	A-58 NARAINA IND. AREA, PHASE-I , NEW DELHI 110028
	ACDB/ DCDB FIXED TYPE	7	E05	UNILEC ENGINEERS PVT. LTD.	BEHRAMPUR INDUSTRIAL AREA, BEGAMPUR KHATOLA ROAD, GURGAON-122001
	ACDB/ DCDB FIXED TYPE	8	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI-110020
	ACDB/ DCDB FIXED TYPE	9	E1210	ENPRO ENGG.	NO.995P, DIAMOND PLAZA, 2ND FLOOR, 12TH MAIN ROAD, ANNA NAGAR, CHENNAI-40
	ACDB/ DCDB FIXED TYPE	10	A01	ASSOCIATED SWGR & PROJ. LTD.	C-10, UPSIDC, INDUSTRIAL AREA, SITE-IV, KASNA ROAD, GREATER NOIDA-201306
	ACDB/ DCDB FIXED TYPE	11	B04	BCH	20/4, MATHURA ROAD, FARIDABAD, HARYANA-121006
	ACDB/ DCDB FIXED TYPE	12	E1043	ECS PRIVATE LTD	7/47, Site 2, Upsidc Ind Area, Loni Road, MOHAN Nagar, Ghaziabad, Uttar Pradesh 201007
	ACDB/ DCDB FIXED TYPE	13	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI-110015
	ACDB/ DCDB FIXED TYPE	14	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
	ACDB/ DCDB FIXED TYPE	15	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA	
	ACDB/ DCDB FIXED TYPE	16	E1080	KHOKHAR ELECT. PVT LTD.	C-44, SEC-63, NOIDA-201307	
	ACDB/ DCDB FIXED TYPE	17	VC01	VIDHYUT CONTROLS (INDIA) PVT. LTD.	M/S VIDHYUT CONTROL (I) PVT.LTD. D-12 & 13, SECTOR-17,KAVI NAGAR INDL.AREA,GHAZIABAD – 201002 (DELHI NCR) U.P. INDIA	
ES6	AIR CIRCUIT BREAKER	1	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI-110015	
	AIR CIRCUIT BREAKER	2	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015,	
	AIR CIRCUIT BREAKER	3	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032	
	AIR CIRCUIT BREAKER	4	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	
	AIR CIRCUIT BREAKER	5	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI-110020	
	AUXILIARY RELAYS	1	A24	ABB	14, MATHURA ROAD, FARIDABAD, HARYANA-121003	
	AUXILIARY RELAYS	2	G01	ALSTOM LTD	A-7, SEC-65, NOIDA	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
PE-RC-999-558-E005					
ES7	AUXILIARY RELAYS	3	E1075	JYOTI LTD.	JYOTI LIMITED, E&CS DIVISION,3/15, BIDC, GORWA,VADODARA - 390 016, E-MAIL ID: ECS@JYOTI.COM
	AUXILIARY RELAYS	4	E1099	OEN INDIA LTD	29/1479, VYTILLA, COCHIN - 682 019 KERALA, INDIA
	AUXILIARY RELAYS	5	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA
	BIMETAL RELAYS	1	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI-110015
ES8	BIMETAL RELAYS	2	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032
	BIMETAL RELAYS	3	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA
	BIMETAL RELAYS	4	E1144	TELEMECHANIQUE/ SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002
	BUCHHOLZ RELAY	1	G01	ALSTOM LTD	A-7, SEC-65, NOIDA
ES9	BUCHHOLZ RELAY	2	E1020	ATVUS INDUSTRIES	689, BLOCK 'O', NEW ALIPORE, CALCUTTA-700053
	BUCHHOLZ RELAY	3	E1070	INSTRUMENTS & CONTROLS	146,GIDC IND.ESTATE,MAKARPURA, VADODRA-390010

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
PE-RC-999-558-E005					
ES10	CABLE CLAMPS & CABLE TIES	1	E1045	ELECTROMAC IND.CORPN.	27/28 AF,NEW EMPIRE IND.ESTT., R.KRISHNA MANDIR RD.JB NGR ,ANDHERI(E), MUMBAI-400059
	CABLE CLAMPS & CABLE TIES	2	I01	INCAB	HARE STREET,KOLKATA,WEST BENGAL-700001
	CABLE CLAMPS & CABLE TIES	3	N05	NOVOFLEX MARKETING PVT. LTD.	RAIKVA' - 5TH FLOOR, UNIT-6 3A, RAM MOHAN MULLICK GARDEN LANE KOLKATA - 700 010
	CABLE GLANDS	1	E1201	ALLIED TRADERS & EXPORTERS	C-124 A, SECTOR-2, NOIDA -201 301, UTTAR PRADESH, INDIA
ES11	CABLE GLANDS	2	E1017	ARUP ENGG & FOUNDARY WORKS	391/119,PRINCE ANWAR SHAH ROAD, CALCUTTA-700068
	CABLE GLANDS	3	E1206	BALIGA LIGHTING EQPT.PVT.LTD.	63A,CP RAMASWAMY ROAD, ALWARPET,P.B.No 6910, CHENNAI-600018
	CABLE GLANDS	4	E1036	COMMET BRASS PRODUCTS	NUTAN CHEMICAL COMPOUND, WALBHAT ROAD, GOREGAON, MUMBAI-400063
	CABLE GLANDS	5	DW08	DOWELLS	M/S. DOWELLS ELECTRICALS 47/47A, SATGURU INDUSTRIAL ESTATE. OFF AAREY ROAD, GOREGOAN (EAST). MUMBAI 400 063.

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
	CABLE GLANDS	6	E1044	ELECTROMAC INDUSTRIES	27/28AF NEW EMPIRE IND. ESTT., R.KRISHNA MANDIR RD.JB NGR ,ANDHERI(E),MUMBAI-400059	
	CABLE GLANDS	7	I01	INCAB	HARE STREET,KOLKATA,WEST BENGAL-700001	
ES12	CABLE LUGS	1	E1040	DOWELLS	M/S. DOWELLS ELECTRICALS 47/47A, SATGURU INDUSTRIAL ESTATE. OFF AAREY ROAD, GOREGOAN (EAST).	
	CABLE LUGS	2	E1149	UNIVERSAL MACHINES LTD.	4,B.B.D.BAG (EAST) 90,STEPHEN HOUSE,5TH FLR CALCUTTA-700001	
ES13	D.C. MCCB	1	C02	CROMPTON GREAVES	RAIL TRANSPORTATION SYSTEMS,VANDANA BUILDING, 11, TOLSTOY MARG, TOLSTOY MARG, NEW DELHI, DL 110001	
	D.C. MCCB	2	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI- 110015	
	D.C. MCCB	3	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL,	
	D.C. MCCB	4	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA	
	EARTH LEAKAGE CB	1	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI- 110015	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
	PE-RC-999-558-E005					
ES14	EARTH LEAKAGE CB	2	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA	
		3	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032	
		4	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	
	EARTH LEAKAGE CB	5	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI-110020	
	EARTH LEAKAGE CB	6	A24	ABB	14, MATHURA ROAD, FARIDABAD, HARYANA-121003	
	EARTH LEAKAGE CB	7	E1068	INDO ASIAN	B-24, PHASE - II , NOIDA - 201305, U.P.	
	EARTH LEAKAGE CB	8	E1088	MDS SWITCHGEAR LTD	314-317SHAH NAHAR ESTATE	
	EARTH LEAKAGE CB	9	E1120	S&S POWER SWITCHGEAR LTD,	NEW NO. 67, OLD NO. 19, DR. RANGA ROAD, MYLAPORE, CHENNAI - 600004	
	JELLY FILLED CABLES	1	D01	DELTON SALES LTD.	DELTON HOUSE 4801,BHARAT RAM ROAD,24DARYAGANJ N.DELHI-110002	
	JELLY FILLED CABLES	2	H01	HINDUSTAN CABLES	A-40 ASIAN GAMES VILLAGE RANJIT SINGH BLOCK NEW DELHI-110049	
	JELLY FILLED CABLES	3	E1096	TELELINK-NICCO	NICCO HOUSE 2,HARE STREET,CALCUTTA-700001	
	JELLY FILLED CABLES	4	E1151	USHA BELTRON LTD.	TATISILWAI , ranchi- 835105	
ES15	DC CONTACTORS	1	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	
	DC CONTACTORS	2	E1030	BHEL (BHOPAL)	HEAVY ELECTRICAL PLANT	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
ES20	DC CONTACTORS	3	E1044	ELECTROMAC INDUSTRIES	27/28AF NEW EMPIRE IND. ESTT., R. KRISHNA MANDIR RD. JB NGR ,ANDHERI(E),MUMBAI-400059	
	DC CONTACTORS	4	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI-110015	
	DC CONTACTORS	5	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA	
	DC CONTACTORS	6	E1144	TELEMECHANIQUE/ SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	
	DC CONTACTORS	7	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032	
	CONTROL SWITCHES/ SELECTOR SWITCH	1	E1076	KAYCEE	KAYCEE INDUSTRIES LTD., C/O-CMS COMPUTERS LTD., 35A, REAR BLDG., KILOKARI, NEW DELHI-110014	
	CONTROL SWITCHES/ SELECTOR SWITCH	2	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032	
ES21	CONTROL SWITCHES/ SELECTOR SWITCH	3	G01	ALSTOM LTD	A-7, SEC-65, NOIDA	
	CONTROL SWITCHES/ SELECTOR SWITCH	4	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	
	CONTROL SWITCHES/ SELECTOR SWITCH	5	SRC01	M/s Shrenik & Co.	39A/3, PANCHRATNA INDUSTRIAL ESTATE, SARKHEJ-BAVLA ROAD, CHANGODAR,	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
	PE-RC-999-558-E005					
	CONTROL SWITCHES/ SELECTOR SWITCH	6	RE05	RECOM PVT. LTD.	M/S RECOM PVT. LTD.,16A , 2ND FLOOR A, WING RAJ INDUSTRIAL COMPLEX, MILITARY	
ES22	CONTROL TRANSFORMER/ WINDING HEATING TRANSFORMER	1	E1009	AUTOMATIC ELECTRIC LTD.	96 AB LONAVLA INDUSTRIAL ESTATE NANGARGAON, LONAVLA-410401	
	CONTROL TRANSFORMER/ WINDING HEATING TRANSFORMER	2	E1066	INDCOIL	PLOT NO. A- 150/ 151, 23RD U ROAD, WAGLE ESTATE, THANE WEST, CST RD, FRIENDS COLONY, HALLOW PUL, KURLA WEST, MUMBAI, MAHARASHTRA 400070	
	CONTROL TRANSFORMER/ WINDING HEATING TRANSFORMER	3	K18	KAPPA ELECTRICALS	KAPPA ELECTRICALS, KAPPA CONSOLIDATED PVT. LTD., 14, CART TRACK ROAD, MADUVANKARAI, CHENNAI - 600 042, INDIA.	
	CONTROL TRANSFORMER/ WINDING HEATING TRANSFORMER	4	E1082	LOGICSTAT	B-160, INDUSTRIAL AREA, C BLOCK RD, OKHLA I, OKHLA INDUSTRIAL AREA, NEW DELHI, DL 110020	
	CONTROL TRANSFORMER/ WINDING HEATING TRANSFORMER	5	E1106	PRECISE ELECTRICALS	47A-49A, CHAKALA ROAD ANDHERI(E),MUMBAI- 99 MUMBAI, MAHARASHTRA, INDIA PIN-400 099	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
	PE-RC-999-558-E005					
	CONTROL TRANSFORMER/ WINDING HEATING TRANSFORMER	6	E1128	UNILEC ENGINEERS PVT. LTD.	PLOT NO: R-247, T.T.C. INDUSTRIAL AREA, M.I.D.C , RABALE, NAVI MUMBAI- 400 701 INDIA	
ES23	LT- CURRENT TRANSFORMER	1	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA	
	LT- CURRENT TRANSFORMER	2	E1009	AUTOMATIC ELECTRIC LTD.	96 AB LONAVLA INDUSTRIAL ESTATE NANGARGAON, LONAVLA-410401	
	LT- CURRENT TRANSFORMER	3	E1066	INDCOIL	PLOT NO. A- 150/ 151, 23RD U ROAD, WAGLE ESTATE, THANE WEST, CST RD, FRIENDS COLONY, HALLOW PUL, KURLA WEST, MUMBAI, MAHARASHTRA 400070	
	LT- CURRENT TRANSFORMER	4	K18	KAPPA ELECTRICALS	KAPPA ELECTRICALS, KAPPA CONSOLIDATED PVT. LTD.,, SOUTHERN ELECTRIKS 14, CART TRACK ROAD, MADUVANKARAI, CHENNAI - 600 042, INDIA.	
	LT- CURRENT TRANSFORMER	5	E1104	PRAGATI ELECTRICALS	280/3,II POKHRAN RD	
	LT- CURRENT TRANSFORMER	6	E1106	PRECISE ELECTRICALS	47A-49A,CHAKALA ROAD ANDHERI(E),MUMBAI- 99 MUMBAI, MAHARASHTRA, INDIA PIN-400 099	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
	PE-RC-999-558-E005				
	LT- CURRENT TRANSFORMER	7	E1128	SILKAANS ELECT.MFG.CO.PVT.LTD	PLOT NO: R-247, T.T.C. INDUSTRIAL AREA, M.I.D.C , RABALE, NAVI MUMBAI- 400 701 INDIA
	LT- CURRENT TRANSFORMER	8	E1111	PRAYOG ELECTRICALS PVT. LTD.	GROUND FLOOR, THAKORE INDUSTRIAL COMPUND, STATION ROAD, VIDYA VIHAR (W), NATHANI ROAD , OPP. AMIBIKA TEMPLE,MUMBAI Mumbai - 400086, Maharashtra, India
	LT- CURRENT TRANSFORMER	9	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI- 110020
	LT- POTENTIAL TRANSFORMER	1	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA
	LT- POTENTIAL TRANSFORMER	2	E1009	AUTOMATIC ELECTRIC LTD.	96 AB LONAVLA INDUSTRIAL ESTATE NANGARGAON, LONAVLA-410401
	LT- POTENTIAL TRANSFORMER	3	E1066	INDCOIL	PLOT NO. A- 150/ 151, 23RD U ROAD, WAGLE ESTATE, THANE WEST, CST RD, FRIENDS COLONY, HALLOW PUL, KURLA WEST, MUMBAI, MAHARASHTRA 400070
	LT- POTENTIAL TRANSFORMER	4	K18	KAPPA ELECTRICALS	KAPPA ELECTRICALS, KAPPA CONSOLIDATED PVT. LTD., SOUTHERN ELECTRIKS 14, CART TRACK ROAD, MADUVANKARAI, CHENNAI - 600 042, INDIA.
ES24					

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
PE-RC-999-558-E005					
ES25	LT- POTENTIAL TRANSFORMER	5	E1104	PRAGATI ELECTRICALS	280/3,II POKHRAN RD
	LT- POTENTIAL TRANSFORMER	6	E1106	PRECISE ELECTRICALS	47A-49A,CHAKALA ROAD ANDHERI(E),MUMBAI-99 MUMBAI, MAHARASHTRA, INDIA PIN-400 099
	LT- POTENTIAL TRANSFORMER	7	E1128	SILKAANS ELECT.MFG.CO.PVT.LTD	PLOT NO: R-247, T.T.C. INDUSTRIAL AREA, M.I.D.C , RABALE, NAVI MUMBAI- 400 701 INDIA
	LT- POTENTIAL TRANSFORMER	8	E1111	PRAYOG ELECTRICALS PVT. LTD.	GROUND FLOOR, THAKORE INDUSTRIAL COMPUnd, STATION ROAD, VIDYA VIHAR (W), NATHANI ROAD , OPP. AMIBIKA TEMPLE,MUMBAI Mumbai - 400086, Maharashtra, India
	DC SWITCH	1	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032
	DC SWITCH	2	E1076	KAYCEE	KAYCEE INDUSTRIES LTD., C/O-CMS COMPUTERS LTD., 35A, REAR BLDG., KILOKARI, NEW DELHI-110014
	DC SWITCH	3	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA
	DISTRIBUTION BOX	1	SRC01	M/S SHRENIK & CO.	39A/3, PANCHRATNA INDUSTRIAL ESTATE, SARKHEJ-BAVLA ROAD, CHANGODAR, AHMEDABAD – 382 213
FUSE BASE	1	E1068	INDO ASIAN	B-24, PHASE - II , NOIDA - 201305, U.P.	

	SUBVENDOR LIST FOR DISTRIBUTION BOARDS				
	PE-RC-999-558-E005				
ES28	FUSE BASE	2	G01	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032
	FUSE BASE	3	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI- 110015
	FUSE BASE	4	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI- 110020
	FUSE BASE	5	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA
	FUSE BASE	6	A24	ABB	14, MATHURA ROAD, FARIDABAD, HARYANA- 121003
	FUSE BASE	7	S02	SPACEAGE SWITCHGEARS LTD.	68 & 13-A INDUSTRIAL DEVELOPMENT COLONY, MEHRAULI ROAD GURGAON, HARYANA-122001
	FUSE BASE	8	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002
	FUSE BASE	9	G01	ALSTOM LTD	A-7, SEC-65, NOIDA

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
	PE-RC-999-558-E005				
	FUSE BASE	10	E1050	ESSEN DEINKI	FLAT NO. 502, SKYLINE HOUSE 85, NEHRU PLACE NEW DELHI
ES29	HRC FUSES	1	E1068	INDO ASIAN	B-24, PHASE - II , NOIDA - 201305, U.P.
	HRC FUSES	2	G01	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032
	HRC FUSES	3	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI-110015
	HRC FUSES	4	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI-110020
	HRC FUSES	5	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA
	HRC FUSES	6	A24	ABB	14, MATHURA ROAD, FARIDABAD, HARYANA-121003
	HRC FUSES	7	S02	SPACEAGE SWITCHGEARS LTD.	68 & 13-A INDUSTRIAL DEVELOPMENT COLONY, MEHRAULI ROAD GURGAON, HARYANA-122001
	HRC FUSES	8	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002
	HRC FUSES	9	G01	ALSTOM LTD	A-7, SEC-65, NOIDA
	HRC FUSES	10	E1050	ESSEN DEINKI	FLAT NO. 502, SKYLINE HOUSE 85, NEHRU PLACE NEW DELHI

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
PE-RC-999-558-E005					
	GALVANISING	1		Jenco Industrial Corporation	Chincholi Bunder Khkar Road Near Link Road Devruwadi Malad (W) Mumbai 400064
	GALVANISING	2		National Galvanizing Company	66, Barrackpore Kamarhatt Trunck Road Calcutta-700058
	GALVANISING	3		Sigma Galvanising Pvt. Ltd.	Plot No.C-169, TTC, MIDC Ind Area Navin Mumbai-400705
	GALVANISING	4		B.P. Projects PVT LTD	167A, Vivekananda Road Kolkata-700006
	GALVANISING	5		Standard Galvanisers	Makardah Road, Kabar Para, Bankra, Howarah -711403
	GALVANISING	6		Steel Products	National Highway No. 6, Chamrail, Kona, Howrah-711114
	GALVANISING	7		Unitech Fabricators & Engineers Pvt. Ltd.	Village- Ajab Nagar, P.O. -Molla Simlla, P.S. - Singur, Dist - Hoogly, Pin-712223
	GALVANISING	8		Shivam Engineers & Fabricators	A0-282-284, Industrial Area, South Side of G.T. Road, Ghaziabad, U.P.
	GALVANISING	9		B.G. Shirke Construction Technology Pvt. Ltd	72-76, Mundhawa, Pune - 401 036
	GALVANISING	10		Galbro Ispat Galvanizers Pvt. Ltd.	GUT 11 AND 12, OPP. Kudus Steel,Rolling Mill, Wada, Thane , Mumbai
	GALVANISING	11		Eros Metals	G-97, MIDC, Bhutibori , Nagpur

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
PE-RC-999-558-E005					
ES30	GALVANISING	12		Industrial Perforation (India) Pvt. Ltd.	Ganganagr, Katakhal, Kolkata-700132
	GALVANISING	13		Indmark Formtech Pvt. Ltd.	Phase - 3, E - 11 / 1, M. I. D. C., Chakan, Pune - 410 501, Maharashtra, India.
	GALVANISING	14		Namdhari Industrial Traders Pvt. Ltd.	Village Latton Dana, Chandigarh Road, Ludhiana
	GALVANISING	15		Neha Galvaniser	Jalan Industrial Estate, Gate No-1, 1st Right Choise Lane, Near N.G-6, Jangalpur, PO Domjur Howrah - 700071, West Bengal, India
	GALVANISING	16		Patny Systems (P) Ltd.	Unit-IV, Sy No. -228/9, Plot No. 6, IP Kuchavaram, Toopran(M) Dist.- Medak, Telegana - 502336
	GALVANISING	17		Parmar Metal Company	Survey No.207, Veraval (Shapar) Dist. Rajkot, India.
	GALVANISING	18		Rukmani Electrical & Fabricators Pvt, Ltd.	Urla Industrial Area, Urla Sarora Road, Raipur- 493 221 (Chhattisgarh)
	GALVANISING				Shankharidaha Baniyarah, Jalan Industrial Complex, Gate no.3, Lane no. 4, Domjur, Howrah , W.B .- 71141
	GALVANISING	19		DMP Projects Pvt.Ltd.	Dulagarh Industrial Park , PS-Sankrail , Howrah -711302
	GALVANISING	20		Vinfab Engineers India Private Limited	Gut no. 224/1 &2 Bhiwandi Wada State Highway, Village khupri, Dist. Thane, Maharashtra -421303

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
	GALVANISING	21		Saral Projects & Processors	B-1, Industrial Area, Site-II, Amawan Road Rae Bareli	
	GALVANISING	22		Brahampuri Steels Limited	172 (F) Industrial Area, Jhotwara, Jaipur-302013	
	GALVANISING	23		Indiana Gratings PVT. LTD	F-5, MIDC Jejuri, Pune-412 303	
	GALVANISING	24	AT08	M/s AVAIDS TECHNOVATORS PVT. LTD	131, MATSYA INDUSTRIAL AREA, ALWAR RAJASTHAN	
ES33	IND.POWER & WLDG SOCKETS	1	C02	CROMPTON GREAVES	3RD FLOOR, EXPRESS BUILDING,9-10, BAHADUR SHAH ZAFAR MARG, NEAR ITO CROSSING,NEW DELHI-110002, INDIA	
	IND.POWER & WLDG SOCKETS	2	E1207	CYCLO ELECTRIC DEVICE & SERV.CO.	: A-3, NEAR ANTHEM BIOSCIENCE, KSSIDC INDUSTRIAL AREA, BOMMASANDRA, BOMMASANDRA INDUSTRIAL AREA, BANGALORE, KARNATAKA 560099	
	IND.POWER & WLDG SOCKETS	3	B04	BCH	20/4, MATHURA ROAD, FARIDABAD - 121006, HARYANA, INDIA	
	IND.POWER & WLDG SOCKETS	4	B02	BEST & CROMPTON	Best & Crompton Engineering Ltd	
	IND.POWER & WLDG SOCKETS	5	A03	AJMERA INDUSTRIES & ENGG. WORKS	AJMERA INDL. AND ENGG. WORKS. AJMERA HOUSE, A-61 / KHAIRANE MIDC. , TTC INDL. AREA, NAVI MUMBAI – 400705.	
	INTERPOSING RELAY	1	A24	ABB	14, MATHURA ROAD, FARIDABAD, HARYANA-121003	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
ES34	INTERPOSING RELAY	2	G01	ALSTOM LTD	A-7, SEC-65, NOIDA	
	INTERPOSING RELAY	3	E1075	JYOTI LTD.	JYOTI LIMITED, E&CS DIVISION,3/15, BIDC, GORWA,VADODARA - 390 016, E-MAIL ID: ECS@JYOTI.COM	
	INTERPOSING RELAY	4	E1099	OEN INDIA LTD	29/1479, VYTILLA, COCHIN - 682 019 KERALA, INDIA	
	INTERPOSING RELAY	5	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA	
	INDICATING LAMPS	1	B04	BCH	20/4, MATHURA ROAD, FARIDABAD, HARYANA-121006	
ES35	INDICATING LAMPS	2	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI-110020	
	INDICATING LAMPS	3	E1050	ESSEN DEINKI	FLAT NO. 502, SKYLINE HOUSE 85, NEHRU PLACE NEW DELHI	
	INDICATING LAMPS	4	E1153	VAISHNO(HOTLINE SWGR.& CONTROL)	G-19, SECTOR - 11, NOIDA - 201301, UTTAR PRADESH, INDIA	
	INDICATING LAMPS	5	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032	
	INDICATING LAMPS	6	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA	
	INDICATING LAMPS	7	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
	JUNCTION BOXES (NON FLAME PROOF)	1	J01	JASPER ENGINEERS PVT. LTD.	A-23, SECTOR - 8, NOIDA-201301	
	JUNCTION BOXES (NON FLAME PROOF)	2	EC05	Electro Controls & Devices	M/S ELECTRO CONTROLS & DEVICES, F-41, SITE-C, SURAJPUR INDUSTRIAL AREA GREATER NOIDA, UTTAR PRADESH :201308	
	JUNCTION BOXES (NON FLAME PROOF)	3	SRC01	M/s Shrenik & Co.	39A/3, PANCHRATNA INDUSTRIAL ESTATE, SARKHEJ-BAVLA ROAD, CHANGODAR, AHMEDABAD – 382 213	
	JUNCTION BOXES (NON FLAME PROOF)	4	PME-01	M/s PHOENIX MECANO LTD.,	388 BHARE, TALUKA MULSHI, POST GHOTAWADE, PIRANGOOT, INDUSTRIAL AREA, PUNE-412115	
	JUNCTION BOXES (NON FLAME PROOF)	5	ACE01	Adroit Control Engineers Pvt.Ltd.	M/S ADROIT CONTROL ENGINEERS PVT.LTD. PLOT-3, KRISHNA INDL. AREA, SECTOR-25 FARIDABAD – 121004	
	JUNCTION BOXES (NON FLAME PROOF)	6	PME-01	M/s PHOENIX MECANO LTD.,	388 BHARE, TALUKA MULSHI, POST GHOTAWADE, PIRANGOOT, INDUSTRIAL AREA, PUNE-412115	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
PE-RC-999-558-E005					
ES36	JUNCTION BOXES (NON FLAME PROOF)	7	MIK01	MIKA ENGINEERS	BRANCH OFFICE : 'D'-101, DHEERAJ HERITAGE RESIDENCY II, SHASTRI NAGAR, SANTACRUZ (W), MUMBAI 400 054.
	JUNCTION BOXES (NON FLAME PROOF)	8	PME-01	M/s PHOENIX MECANO LTD.,	388 BHARE, TALUKA MULSHI, POST GHOTAWADE, PIRANGOOT, INDUSTRIAL AREA, PUNE-412115
	JUNCTION BOXES (NON FLAME PROOF)	9	B05	BAJAJ ELECTRICALS	BAJAJ ELECTRICALS LTD. ENGINEERING & PROJECTS BU (NORTH) 3rd FLOOR, GULMOHARHOUSE, COMMUNITY CENTRE 161/B-4, GAUTAM NAGAR, YUSUF SARAI NEW DELHI – 110049

	SUBVENDOR LIST FOR DISTRIBUTION BOARDS				
	PE-RC-999-558-E005				
	JUNCTION BOXES (NON FLAME PROOF)	10	A03	AJMERA INDUSTRIES & ENGG. WORKS	AJMERA INDL. AND ENGG. WORKS. AJMERA HOUSE, A-61 / KHAIRANE MIDC. , TTC INDL. AREA, NAVI MUMBAI – 400705.
	JUNCTION BOXES (NON FLAME PROOF)	11	SB02	S.B. ELECTRICAL ENGINEERING CORPORATION	03, SARDAR GRIHA BUILDING, LOHAR CHAWAL, MUMBAI-400002

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
		12	RT13	RITTAL INDIA PVT. LTD.	Espire Building ,Level -1 A-41, Mohan Co-Operative Industrial Estate ,Mathura Road, New Delhi -110044	
	JUNCTION BOXES (NON FLAME PROOF)					
ES37	JUNCTION BOXES (FLAME PROOF)	1	SS01	SUDHIR SWITCHGEAR	305/6, APEEJAY HOUSE, 130, BOMBAY SAMACHAR MARG, MUMBAI - 400 023. INDIA	
	LIGHTING DISTRIBUTION BOARDS	1	E1007	ADVANCE ENGG. COMPANY	38,SETHI IND. ESTATE 10/E,SUREN RD,ANDHERI MUMBAI-400097	
	LIGHTING DISTRIBUTION BOARDS	2	STRG01	Sterling Generators Pvt. Ltd.	C-56/38, INSTITUTIONAL AREA, SECTOR-62, NOIDA -201307, U.P.	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS				
PE-RC-999-558-E005				
	LIGHTING DISTRIBUTION BOARDS	3	E1091	MIKA ENGINEERS BRANCH OFFICE : 'D'-101, DHEERAJ HERITAGE RESIDENCY II, SHASTRI NAGAR, SANTACRUZ (W), MUMBAI 400 054.
	LIGHTING DISTRIBUTION BOARDS	4	F04	ELEXPRO ELECTRICALS PVT/ LTD.
	LIGHTING DISTRIBUTION BOARDS	5	KM1	"ATOZ HOUSE" C-49, SECTOR-81, GAUTAM BUDDH NAGAR, NOIDA – 201 305 U. P. (INDIA)
	LIGHTING DISTRIBUTION BOARDS	6	E05	UNILEC ENGINEERS PVT. LTD.
				BEHRAMPUR INDUSTRIAL AREA, BEGAMPUR KHATOLA ROAD, GURGAON-122001

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
	PE-RC-999-558-E005				
ES38	LIGHTING DISTRIBUTION BOARDS	7	AVA01	AVAIODS TECHNOVATORS LTD.	PLOT NO.25 ,SECTOR-3,IMT-MANESAR, GURGEON-122050 (HARYANA)
	LIGHTING DISTRIBUTION BOARDS	8	ACE01	Adroit Control Engineers Pvt.Ltd.	M/S ADROIT CONTROL ENGINEERS PVT.LTD. PLOT-3, KRISHNA INDL. AREA, SECTOR-25 FARIDABAD – 121004
	LIGHTING DISTRIBUTION BOARDS	9	JC01	JACKSON ENGINEERS	A-43, HOSEIRY COMPLEX, OPPOSITE NSEZ, NOIDA-201305
	LIGHTING DISTRIBUTION BOARDS	10	ADL01	Adlec Systems Private Limited	PLOT NO-277, SWARN PARK, UDYOG NAGAR, MUNDKA, MAIN ROHTAK ROAD, UDYOG NAGAR, NEW DELHI, DELHI 110041
	LIGHTING DISTRIBUTION BOARDS	11	POP01	Popular Switchgears Pvt Ltd	712, ARUN CHAMBERS, TARDEO MAIN ROAD, TARDEO, NEAR TARDEO AIRCONDITIONER MARKET, MUMBAI - 400034
	LIGHTING DISTRIBUTION BOARDS	12	CS01	CANDS	J/202, ANSA INDUSTRIAL ESTATE, SAKI VIHAR ROAD, SAKINAKA, ANDHERI (EAST), MUMBAI-72

	SUBVENDOR LIST FOR DISTRIBUTION BOARDS			
	PE-RC-999-558-E005			
	LIGHTING DISTRIBUTION BOARDS	13	PYRE01	Pyrotech Electronics Pvt. Ltd. M/s Pyrotech Electronics Pvt. Ltd(Unit -1) Led Light, Sensor Division F-16A, Road No.3 Mewar Industrial Area, Madri Udaipur -313003, Rajasthan,

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
PE-RC-999-558-E005					
	LIGHTING DISTRIBUTION BOARDS	14	PCS01	Positronics Pvt. Ltd.	POSITRONICS HOUSE ,882/ 2, G.I.D.C. MAKARPURA,VADODARA 390010 GUJARAT
	LIGHTING DISTRIBUTION BOARDS	15	ISC01	Industrial Switchgears & Control Pvt Ltd	S-02 AMARDEEP MAHAL, NANDA PATKAR RD, VILE PARLE EAST, MUMBAI - 400057
	LIGHTING DISTRIBUTION BOARDS	16	VC01	M/s Vidhyut Control (I) Pvt.Ltd.	D-12 & 13, SECTOR-17, KAVI NAGAR INDL.AREA, GHAZIABAD – 201002 (DELHI NCR) U.P. INDIA
	LIGHTING DISTRIBUTION BOARDS	17	MIL01	MILESTONE SWITCHGEARS PVT. LTD.	MILESTONE SWITCHGEARS PVT. LTD. 97, UDYOG VIHAR, PHASE-1, GURGEON HARYANA - 122016
	LIGHTING SWITCH , SOCKET & S/F UNIT	1	F04	ELEXPRO ELECTRICALS PVT/ LTD.	C 1/27 & 37 GIDC KABILPORE NAVSARI-396424

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
ES45	LIGHTING SWITCH , SOCKET & S/F UNIT	2	E1012	ANCHOR	STEEL HOUSE, B WING, PLOT NO. 24, MAHAL INDUSTRIAL ESTATE, MAHAKALI CAVES ROAD, NEAR PAPER BOX, ANDHERI (E), MUMBAI, MAHARASHTRA.- 400093	
	LIGHTING SWITCH , SOCKET & S/F UNIT	3	E1076	KAYCEE	KAYCEE INDUSTRIES LTD., C/O-CMS COMPUTERS LTD., 35A, REAR BLDG., KILOKARI, NEW DELHI-110014	
	LIGHTING SWITCH , SOCKET & S/F UNIT	4	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI-110015	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
	LIGHTING SWITCH , SOCKET & S/F UNIT	5	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA	
	LIGHTING SWITCH , SOCKET & S/F UNIT	6	E1068	INDO ASIAN	B-24, PHASE - II , NOIDA - 201305, U.P.	
	LIGHTING TRANSFORMER	1	E1021	AUTOMATIC ELECTRIC LTD.	ADDRESS : 96 AB LONAVLA INDUSTRIAL ESTATE NANGARGAON, LONAVLA-410401	
	LIGHTING TRANSFORMER	2	E1066	INDCOIL	PLOT NO. A- 150/ 151, 23RD U ROAD, WAGLE ESTATE, THANE WEST, CST RD, FRIENDS COLONY, HALLOW PUL, KURLA WEST, MUMBAI, MAHARASHTRA 400070	
	LIGHTING TRANSFORMER	3	E1103	POWER PACK ENTERPRISES	POWER PACK ENTERPRISES MR. NEHAL SHAH / MR. SHARAD SHAH (PARTNER) NO. 3, JAYSHREE SADAN, 1ST FLOOR, OLD NAGARDAS ROAD, ANDHERI EAST MUMBAI - 400069, MAHARASHTRA, INDIA	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
PE-RC-999-558-E005					
ES46	LIGHTING TRANSFORMER	4	E1155	VIJAY ELECTRICALS LTD.	6-3-648/1&2, OFF RAJ BHAVAN ROAD, SOMAJIGUDA, HYDERABAD - 500 082. ANDHRA PRADESH, INDIA.
	LIGHTING TRANSFORMER	5	E1057	GILBERT & MAXWELL	WORKS PLOT G-28 , M.I.D.C., AMBAD NASHIK - 422010, MAHARASHTRA, INDIA
	LIGHTING TRANSFORMER	6	K18	KAPPA ELECTRICALS	KAPPA ELECTRICALS, KAPPA CONSOLIDATED PVT. LTD., SOUTHERN ELECTRIKS 14, CART TRACK ROAD, MADUVANKARAI, CHENNAI - 600 042, INDIA.
	LIGHTING TRANSFORMER	7	AIE01	Ames Impex Electricals Pvt. Ltd	C-1B/1207, PHASE IV, GIDC NARODA, AHMEDABAD, GUJARAT 382330

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
PE-RC-999-558-E005					
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	8	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	9	E1019	ASIATIC	A-58 NARAINA IND. AREA, PHASE-I , NEW DELHI 110028
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	10	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI- 110020
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	11	E1051	EVERGREEN ENGG. CO.	EVERGREEN ENGG COMPANY WORKS-5, PLOT NO. 9,10,11,12, SURVEY NO. 242, CHINCH PADA, VASAI EAST-401208
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	12	E1143	TECKNIC CONTROLS	703, MADHAVA, BANDRA, KURLA COMPLEX, BANDRA EAST, MUMBAI, MAHARASHTRA 400051
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	13	E1053	EX-PROTECTA LIGHTING EQUIPMENT	305-306, GIDC ESTATE, VITHAL UDYOGNAGAR - 388121 DIST. ANAND, GUJARAT 388121 INDIA
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	14	E1206	BALIGA ELECTRICALS	63A, CP RAMASWAMY ROAD, PB NO 6910, CHENNAI-600018
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	15	E1210	ENPRO ENGG.	NO.995P, DIAMOND PLAZA, 2ND FLOOR, 12TH MAIN ROAD, ANNA NAGAR, CHENNAI-40

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
PE-RC-999-558-E005					
ES47	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	16	E1132	STERLING SWGR CONTROL PVT.LTD.	P.O. BOX NO. 17023, SORAB HOUSE, 2ND FLOOR, 555, S.B. MARG, DADAR, MUMBAI - 400028, MAHARASHTRA, INDIA
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	17	F04	ELEXPRO ELECTRICALS PVT/ LTD.	C 1/27 & 37 GIDC KABILPORE NAVSARI-396424
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	18	E1153	VAISHNO(HOTLINE SWGR & CONTROL)	G-19, SECTOR - 11, NOIDA - 201301, UTTAR PRADESH, INDIA
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	19	J01	JASPER ENGINEERES PVT. LTD.	A-23, SECTOR - 8, NOIDA-201301
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	20	KM1	KMG ATOZ SYSTEMS	C-49, SECTOR-81-NOIDA-201305
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	21	E05	UNILEC ENGINEERS PVT. LTD.	BEHRAMPUR INDUSTRIAL AREA, BEGAMPUR KHATOLA ROAD, GURGAON-122001
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	22	B04	BCH	20/4, MATHURA ROAD, FARIDABAD, HARYANA- 121006
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	23	E1035	CANDS	J/202, ANSA INDUSTRIAL ESTATE, SAKI VIHAR ROAD, SAKINAKA, ANDHERI (EAST), MUMBAI-72
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	24	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	25	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	26	E1143	TECKNIC CONTROLS	703, MADHAVA, BANDRA, KURLA COMPLEX, BANDRA EAST, MUMBAI, MAHARASHTRA 400051	
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	27	E1148	UNITED ELECTRIC	97 UDYOG VIHAR PHASE-I, GURGAON 122015, HARYANA	
	LOCAL PUSH BUTTON STATION (NON FLAME PROOF)	28	SRC01	M/s Shrenik & Co.	39A/3, PANCHRATNA INDUSTRIAL ESTATE, SARKHEJ-BAVLA ROAD, CHANGODAR, AHMEDABAD – 382 213	
	LOCAL PUSH BUTTON STATION (FLAME PROOF)					
ES48						
ES49	LIGHTING PANEL (FLAME PROOF)	1	E1206	BALIGA ELECTRICALS	63A,CP RAMASWAMY ROAD, PB NO 6910, CHENNAI-600018	
	LIGHTING PANEL (FLAME PROOF)	2	SS01	SUDHIR SWITCHGEAR	305/6, APEEJAY HOUSE, 130, BOMBAY SAMACHAR MARG, MUMBAI - 400 023. INDIA	
	LIGHTING PANEL (NON FLAME PROOF)	1	E1091	MIKA ENGINEERS	D'-101, DHEERAJ HERITAGE RESIDENCY II, SHASTRI NAGAR, SANTACRUZ (W), MUMBAI 400 054.	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
	PE-RC-999-558-E005				
ES50	LIGHTING PANEL (NON FLAME PROOF)	2	F04	ELEXPRO ELECTRICALS PVT/ LTD.	C 1/27 & 37 GIDC KABILPORE NAVSARI-396424
	LIGHTING PANEL (NON FLAME PROOF)	3	VC01	Vidhyut Controls (India) Pvt. Ltd.	M/S VIDHYUT CONTROL (I) PVT.LTD. D-12 & 13, SECTOR-17,KAVI NAGAR INDL.AREA,GHAZIABAD – 201002 (DELHI NCR) U.P. INDIA
	LIGHTING PANEL (NON FLAME PROOF)	4	KM1	KMG ATOZ SYSTEMS	"ATOZ HOUSE" C-49, SECTOR-81, GAUTAM BUDDH NAGAR, NOIDA – 201 305 U. P. (INDIA)
	LIGHTING PANEL (NON FLAME PROOF)	5	E05	UNILEC ENGINEERS PVT. LTD.	BEHRAMPUR INDUSTRIAL AREA, BEGAMPUR KHATOLA ROAD, GURGAON-122001
	LIGHTING PANEL (NON FLAME PROOF)	6	AVA01	AVAIODS TECHNOVATORS LTD.	PLOT NO.25 ,SECTOR-3,IMT-MANESAR, GURGEON-122050 (HARYANA)
	LIGHTING PANEL (NON FLAME PROOF)	7	ACE01	Adroit Control Engineers Pvt.Ltd.	M/S ADROIT CONTROL ENGINEERS PVT.LTD. PLOT-3, KRISHNA INDL. AREA, SECTOR-25 FARIDABAD – 121004
	LIGHTING PANEL (NON FLAME PROOF)	8	JC01	JACKSON ENGINEERS	A-43, HOSEIRY COMPLEX, OPPOSITE NSEZ, NOIDA-201305

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
	LIGHTING PANEL (NON FLAME PROOF)	9	MIL01	MILESTONE SWITCHGEARS PVT. LTD.	MILESTONE SWITCHGEARS PVT. LTD. 97, UDYOG VIHAR, PHASE-1, GURGEEON HARYANA - 122016	
	LIGHTING PANEL (NON FLAME PROOF)	10	PCS01	Positronics Pvt. Ltd.	POSITRONICS HOUSE ,882/ 2, G.I.D.C. MAKARPURA,VADODARA 390010 GUJARAT	
	LIGHTING PANEL (NON FLAME PROOF)	11	PYRE01	Pyrotech Electronics Pvt. Ltd.	M/s Pyrotech Electronics Pvt. Ltd(Unit -1) Led Light, Sensor Division F-16A, Road No.3 Mewar Industrial Area, Madri Udaipur -313003, Rajasthan,	
	MCB	1	E1088	MDS SWITCHGEAR LTD	314-317SHAH NAHAR ESTATE	
	MCB	2	E1068	INDO ASIAN	B-24, PHASE - II , NOIDA - 201305, U.P.	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005;						
ES51	MCB	3	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	
	MCB	4	E1120	S&S POWER SWITCHGEAR LTD,	NEW NO. 67, OLD NO. 19, DR. RANGA ROAD, MYLAPORE, CHENNAI - 600004	
	MCC (FIXED TYPE)	1	S02	SPACEAGE SWITCHGEARS LTD.	68 & 13-A INDUSTRIAL DEVELOPMENT COLONY, MEHRAULI ROAD GURGAON, HARYANA-122001	
ES52	MCC (FIXED TYPE)	2	A01	ASSOCIATED SWGR & PROJ.LTD.	C-10, UPSIDC, INDUSTRIAL AREA, SITE-IV, KASNA ROAD, GREATER NOIDA-201306	
	MCC (FIXED TYPE)	3	B04	BCH	20/4, MATHURA ROAD, FARIDABAD, HARYANA-121006	
	MODULAR SWITCH BOARD	1	E1012	ANCHOR	STEEL HOUSE, B WING, PLOT NO. 24, MAHAL INDUSTRIAL ESTATE, MAHAKALI CAVES ROAD, NEAR PAPER BOX, ANDHERI (E), MUMBAI, MAHARASHTRA.- 400093	
ES55	MODULAR SWITCH BOARD	2	F04	ELEXPRO ELECTRICALS PVT/LTD.	C 1/27 & 37 GIDC KABILPORE NAVSARI-396424	
	MODULAR SWITCH BOARD	3	H101	HAVELLS INDIA LIMITED	QRG TOWERS , 2D SECTOR-126, NOIDA- 201301	
	OIL TEMP INDICATOR	1	E1101	PERFECT CONTROLS	BLOCK NO. 7, NORTH ROAD,WEST C.I.T. NAGAR,CHENNAI - 600035, INDIA.	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
PE-RC-999-558-E005					
ES56	OIL TEMP INDICATOR	2	E1105	PRECIMEASURE	M/S. PRECIMEASURE CONTROLS PVT. LTD. 168/C, INDUSTRIAL SUBURB, PEENYA 3RD PHASE, BANGALORE - 560058. KARNATAKA, INDIA
ES57	PROTECTION - RELAYS (PNUEMATIC)	1	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA
	PROTECTION - RELAYS (PNUEMATIC)	2	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002
	PROTECTION - RELAYS (PNUEMATIC)	3	A35	GE-MULTILINE, GE INDIA INDUSTRIAL PVT. LTD.	NO. 90- B, ELECTRONICS CITY, HOSUR ROAD, BENGALURU - 560016, KARNATAKA
	PROTECTION - RELAYS (PNUEMATIC)	4	SC01	SCHWEITZER ENGG. LAB (SEL)	406, BHIKAJI CAMA BHAVAN, BHIKAJI CAMA PLACE, BHIKAJI CAMA PLACE, MOHAMMADPUR, RK PURAM, NEW DELHI, DL 110066
	PROTECTION - RELAYS (PNUEMATIC)	5	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI- 110020
	PROTECTION - RELAYS (PNUEMATIC)	6	G01	ALSTOM LTD	A-7, SEC-65, NOIDA
	PROTECTION - RELAYS (PNUEMATIC)	7	A24	ABB	14, MATHURA ROAD, FARIDABAD, HARYANA- 121003
	PROTECTION - RELAYS (PNUEMATIC)	8	C01	AVK-SEG & CONTROLS(I) LTD	C-60,NOIDA PHASE-II
	PROTECTION - RELAYS (NUMERICAL)	1	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
ES58	PROTECTION - RELAYS (NUMERICAL)	2	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	
	PROTECTION - RELAYS (NUMERICAL)	3	A35	GE-MULTILINE, GE INDIA INDUSTRIAL PVT. LTD.	NO. 90- B, ELECTRONICS CITY, HOSUR ROAD, BENGALURU - 560016, KARNATAKA	
	PROTECTION - RELAYS (NUMERICAL)	4	SC01	SCHWEITZER ENGG. LAB (SEL)	406, BHIKAJI CAMA BHAVAN, BHIKAJI CAMA PLACE, BHIKAJI CAMA PLACE, MOHAMMADPUR, RK PURAM, NEW DELHI, DL 110066	
	RESISTOR FOR DC STARTERS	1	B04	BCH	20/4, MATHURA ROAD, FARIDABAD, HARYANA- 121006	
ES60	RESISTOR FOR DC STARTERS	2	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI- 110020	
	RESISTOR FOR DC STARTERS	3	E1119	RSI	60,IND.DEV.COLONY, MEHRAULI ROAD, GURGAON-122001	
	RESISTOR FOR DC STARTERS	4	S04	SPEED-O-CONTROL	C-16, NAND JYOT INDUSTRIAL ESTATE, SAFED POOL, ANDHERI-KURLA ROAD, SAFED POOL, MAGAN NATHURAM RD, SHIVAJI NAGAR, SAKINAKA, MUMBAI, MAHARASHTRA 400072	
	RESISTOR FOR DC STARTERS	5	E1137	SUSHIL ENGG CORP.	D-7, GHATKOPAR INDUSTRIAL ESTATE, OFF LBS MARG, GHATKOPAR (WEST), AMRUT NAGAR RD, AMRUT NAGAR, GHATKOPAR WEST, MUMBAI, MAHARASHTRA 400086	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
ES61	SWITCH BOX	1	E1012	ANCHOR		STEEL HOUSE, B WING, PLOT NO. 24, MAHAL INDUSTRIAL ESTATE, MAHAKALI CAVES ROAD, NEAR PAPER BOX, ANDHERI (E), MUMBAI, MAHARASHTRA.- 400093
	SWITCH BOX	2	F04	ELEXPRO ELECTRICALS PVT/ LTD.		C 1/27 & 37 GIDC KABILPORE NAVSARI-396424
	SWITCH BOX	3	B05	BAJAJ ELECTRICALS		BAJAJ ELECTRICALS LTD. ENGINEERING & PROJECTS BU (NORTH) 3rd FLOOR, GULMOHARHOUSE, COMMUNITY CENTRE 161/B-4, GAUTAM NAGAR, YUSUF SARAI NEW DELHI – 110049
	SWITCH BOX	4	A03	AJMERIA INDUSTRIES & ENGG. WORKS		AJMERIA INDL. AND ENGG. WORKS. AJMERIA HOUSE, A-61 / KHAIRANE MIDC. , TTC INDL. AREA, NAVI MUMBAI – 400705.
	SWITCH BOX	5	SB02	S.B. ELECTRICAL ENGINEERING CORPORATION		03, SARDAR GRIHA BUILDING, LOHAR CHAWAL, MUMBAI-400002
	TERMINAL BLOCKS	1	C01	WAGO-CONTROLS		C 27, GREATER NOIDA, SECTOR 58, C BLOCK, SECTOR 58, NOIDA, UTTAR PRADESH 201307

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
	PE-RC-999-558-E005				
ES62	TERMINAL BLOCKS	2	E1038	CONNECT WELL	309A/4, 3RD FLOOR, KALKAJI, OKHLA IND AREA PH-2, GOVINDPURI, NEW DELHI, DL 110019
	TERMINAL BLOCKS	3	E1047	ELMEX CONTROLS PVT. LTD.	12,G.I.D.C.ESTATE,MUKARPURA ROAD,VADODARA-390010
	TERMINAL BLOCKS	4	E1050	ESSEN DEINKI	FLAT NO. 502, SKYLINE HOUSE 85, NEHRU PLACE NEW DELHI
	TERMINAL BLOCKS	5	E1142	TECHNOPLAST	OPP.I.M.INTER COLLEGE, BEGUM SARAI KHURD ROAD, AMROHA - 244221, U.P.
	TERMINAL BLOCKS	6	PME-01	M/s PHOENIX MECANO LTD.,	388 BHARE, TALUKA MULSHI, POST GHOTAWADE, PIRANGOOT, INDUSTRIAL AREA, PUNE-412115
	TERMINAL BLOCKS	7	E1050	ESSEN DEINKI	FLAT NO. 502, SKYLINE HOUSE 85, NEHRU PLACE NEW DELHI
	TIMERS - PNEUMATIC	1	B04	BCH	20/4, MATHURA ROAD, FARIDABAD, HARYANA-121006
	TIMERS - PNEUMATIC	2	G01	ALSTOM LTD	A-7, SEC-65, NOIDA
	TIMERS - PNEUMATIC	3	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI-110015

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
ES63	TIMERS - PNEUMATIC	4	E1144	TELEMECHANIQUE/ SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	
	TIMERS - PNEUMATIC	5	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	
	TIMERS - PNEUMATIC	6	E01	ELECTRONIC AUTOMATION PVT. LTD.	20, KHB INDUSTRIAL AREA YELAHANKA BANGLORE-560064	
ES64	TIMERS - ELECTRONIC	1	E1050	ESSEN DEINKI	FLAT NO. 502, SKYLINE HOUSE 85, NEHRU PLACE NEW DELHI	
ES65	TRANSDUCERS	1	E1021	AUTOMATIC ELECTRIC LTD.	ADDRESS : 96 AB LONAVLA INDUSTRIAL ESTATE NANGARGAON, LONAVLA-410401	
	TRANSDUCERS	2	E1202	SOUTHERN TRANSDUCERS	INTERTECH B-83, FLATTED FACTORY COMPLEX, NEAR MODI MILLS, OKHLA, NEW DELHI-110020	
ES66	WINDING TEMP INDICATOR	1	E1101	PERFECT CONTROLS	OFFICE ADDRESS: 7, NORTH ROAD, WEST C.I.T. NAGAR,CHENNAI - 600035, INDIA.	
	WINDING TEMP INDICATOR	2	E1105	PRECIMEASURE	M/S. PRECIMEASURE CONTROLS PVT. LTD. 168/C, INDUSTRIAL SUBURB, PEENYA 3RD PHASE, BANGALORE - 560058. KARNATAKA, INDIA	
	ENERGY METER (ANALOG)	1	B07	BHEL (EDN)	MYSORE ROAD, BANGALORE-560026	
	ENERGY METER (ANALOG)	2	E1129	SIMCO ENGG. LTD	NO. 126, K ROAD, TIRUCHIRAPPALLI -620001, TAMIL NADU	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
ES72	ENERGY METER (ANALOG)	3	R01	RISHABH INST.PVT LTD	RISHABH INSTRUMENTS PVT. LTD. F-31, MIDC, SATPUR NASHIK - 422007 MAHARASHTRA INDIA	
	ENERGY METER (ANALOG)	4	E1009	AUTOMATIC ELECTRIC LTD.	96 AB LONAVLA INDUSTRIAL ESTATE NANGARGAON, LONAVLA-410401	
	ENERGY METER (ANALOG)	5	CON1	CONZERVE SYSTEMS PVT. LTD.(SCHNEIDER)	87, 1ST FLOOR INDUSTRIAL DEVELOPMENT COLONY (IDC) MEHRAULI ROAD, UGURGAON 122001 HARYANA, INDIA.	
	ENERGY METER (DIGITAL)	1	CON1	CONZERVE SYSTEMS PVT. LTD.(SCHNEIDER)	87, 1ST FLOOR INDUSTRIAL DEVELOPMENT COLONY (IDC) MEHRAULI ROAD, UGURGAON 122001 HARYANA, INDIA.	
ES73	AMMETER	1	E1009	AUTOMATIC ELECTRIC LTD.	96 AB LONAVLA INDUSTRIAL ESTATE NANGARGAON, LONAVLA-410401	
	AMMETER	2	R01	RISHABH INST.PVT LTD	RISHABH INSTRUMENTS PVT. LTD. F-31, MIDC, SATPUR NASHIK - 422007 MAHARASHTRA INDIA	
	VOLTMETER	1	E1009	AUTOMATIC ELECTRIC LTD.	96 AB LONAVLA INDUSTRIAL ESTATE NANGARGAON, LONAVLA-410401	
ES74	VOLTMETER	2	R01	RISHABH INST.PVT LTD	RISHABH INSTRUMENTS PVT. LTD. F-31, MIDC, SATPUR NASHIK - 422007 MAHARASHTRA INDIA	
	MPCB	1	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	
ES75	MPCB	2	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI- 110015	

SUBVENDOR LIST FOR DISTRIBUTION BOARDS						
PE-RC-999-558-E005						
ES76	MPCB	3	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA	
	MPCB	4	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032	
	MPCB	5	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	
	MPCB	6	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI-110020	
ES77	MAGNETIC OIL GAUGE	1	E1134	SUKRUT UDYOG	9/1/A, ERANDAWANE, OPPOSITE MEHENDALE GARAGE, ERANDAWANE, GULAWANI MAHARAJ RD, SWAROOP SOCIETY, VAKIL NAGAR, ERANDWANE, PUNE, MAHARASHTRA 411004	
ES78	MULTIFUNCTION METER	1	CON1	CONZERVE SYSTEMS PVT. LTD./ SCHNEIDER ELECTRIC INDIA PVT. LTD.	87, 1ST FLOOR INDUSTRIAL DEVELOPMENT COLONY (IDC) MEHRAULI ROAD, GURGAON 122001 HARYANA, INDIA.	
	RCCB	1	C01	C&S ELECTRIC LTD.	222, OKHLA IND. ESTATE, PH-III, NEW DELHI-110020	
	RCCB	2	S03	SCHNEIDER ELECTRIC INDIA PVT. LTD.	9TH FLOOR, BLDG. NO. 10, TOWER-C, DLF CYBER CITY, PH-II, GURGAON-122002	
	RCCB	3	S01	SIEMENS	RC-IN I S NR DEL AREA, JIL BUILDING, TOWER-B, PLOT NO. 78, SECTOR 18, GURGAON-122015, INDIA	

	SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
	PE-RC-999-558-E005					
ES79	RCCB	4	A35	GE-POWER	KAMAK TOWER, 3RD FLOOR, PLOT NO. 12-A, TVK INDUSTRIAL ESTATE, EKKADUTHANGAL, GUINDY, CHENNAI-600032	
	RCCB	5	L01	L&T	32, SHIVAJI MARG, P.O. BOX- 6223, NEW DELHI- 110015	
	RCCB	6	C02	CROMPTON GREAVES	RAIL TRANSPORTATION SYSTEMS,VANDANA BUILDING, 11, TOLSTOY MARG, TOLSTOY MARG, NEW DELHI, DL 110001	
ES85	HUME PIPE					REPUTED MAKE
ES86	PHOTOELECTRIC SWITCH					REPUTED MAKE

SUBVENDOR LIST FOR DISTRIBUTION BOARDS					
PE-RC-999-558-E005					
GI WIRE & FLAT	1	I039	INDUSTRIAL PERFORATION (I) PVT.LTD.	MR. A. K. SAHA 327, R.N.GUHA ROAD, DUM DUM KOLKATA-West Bengal-India Phone- 9830241788 Pincode : 700028 Email : ipipl@cal2.vsnl.net.in	
GI WIRE & FLAT	2	I070	INDIA ELECTRICALS SYNDICATE	Mr. Suresh Kumar Agarwal 55, Ezra Street, Kolkata-West Bengal-India Phone- 033- 22354047 Pincode : 700001 Email : cabletray@vsnl.com	
GI WIRE & FLAT	3	I072	INDMARK FORMTECH PVT. LTD.	Mr. Narendra R. Meher J Block, Plot No.-375, MIDC BHOSARI PUNE-MAHARASHTRA-INDIA Phone- 020-27130546 Pincode : 411026 Email : indmarkformtech@vsnl.net	
GI WIRE & FLAT	4	P039	PREMIER POWER PRODUCTS (CAL) PVT. LTD.	Chatterjee International Centre, 33A, Jawaharlal Nehru Road, 6th Floor, Suit No. - 11A, Kolkata,- West Bengal-India Phone- 9331008739 Pincode : 700071 Email : hemantdaga@dagaventures.com	
GI WIRE & FLAT	5	P050	PATNY SYSTEMS (P) LTD	PATNY PLAZA 160 , SARDAR PATEL ROAD SEUNDRABAD SECUNDRABAD-TELANGANA- INDIA Phone- 040-27902451 Pincode : 500003 Email : mr.mkt@patnysystems.com	

PE-RC-999-558-E005					
ES31	GI WIRE & FLAT	6	P079	PASSIVE INFRA PROJECTS PVT. LTD.	MR. VARUN AGRAWAL 182, VAISHALI, PITAMPURA Delhi-DELHI-INDIA Phone- 9871183059 Pincode : 110088 Email : ATANU.SAHA@PASSIVEINFRA.COM
	GI WIRE & FLAT	7	R036	RUKMANI ELECTRICAL & COMPONENTS PVT LTD	11A, MAHARISHI DEBENDRA ROAD 1ST FL., ROOM NO.4 KOLKATA-WEST BENGAL-INDIA Phone- Pincode : 700007 Email : maruthikabra@gmail.com
	GI WIRE & FLAT	8	R037	RATAN PROJECTS & ENGINEERING CO. PVT.LTD.	MR. G.D. SINGHEE/MR. MAHESH SINGHEE 26, P.K. TAGORE STREET, MAIN BUILDING KOLKATA-WEST BENGAL-INDIA Phone- 9830177331 Pincode : 700006 Email : mahesh@ratans.com
	GI WIRE & FLAT	9	R041	RABI ENGINEERING WORKS PVT. LTD.	MR. TAPAN KUMAR SEN/MR. SIDDHARTHA 327, R.N. GUHA ROAD, DUM DUM, KOLKATA-WEST BENGAL-INDIA Phone- 9748753002 Pincode : 700028 Email : rabiengineering@gmail.com
	GI WIRE & FLAT	10	R200	RAJASTHAN METAL SMELTING CO.	Mr. R. K. Tibrewala D-80, Road No. 7, V.K.I.A., Jaipur-Rajasthan-India Phone- 0141-2332269 Pincode : 302013 Email : info@rmscoindia.com
	GI WIRE & FLAT	11	S210	SARAL INDUSTRIES	Mr. Y.K. Gupta L-1, L-2, Industrial Area-1 Sultanpur Road Rae Bareilly-Uttar Pradesh-India Phone- 0535-2702474 Pincode : 229010 Email : saralindustries@gmail.com

	PE-RC-999-558-E005				
	GI WIRE & FLAT	12		PARCO Engineers Pvt. Ltd.	401, skyline Epitom Building ,Near to Jolly Gym Khana, Kirol Road , Vidhyavihar, MH 400086 India
	GI WIRE & FLAT	13	U019	UNITECH FABRICATORS and ENGINEERS PVT LTD	INDRAPRASHTHA APARTMENT 24 , M.B.RAOD , BIRATI KALABAGAN KOLKATA KOLKATA-WEST BENGAL-INDIA Phone- Pincode : 700051 Email : ufep1@vsnl.net; ufep1@rediffmail.com
ES80	PVC WIRES	BIS APPROVED MAKE			

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999-558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE:

SHEET 1 OF 9

DATA SHEET –C

S. No.	Description	Unit	Value
1.0	SYSTEM DESIGN DATA		
1.1	Design ambient	⁰ C	
1.2	AC Supply		
a)	Rated voltage	V	
b)	Rated frequency	Hz	
c)	Voltage variation (permissible)	%	
d)	Frequency variation (permissible)	%	
e)	Combined voltage & frequency variation (sum of absolutes permissible)	%	
f)	System fault level & duration	kA, sec.	
2.0	APPLICABLE STANDARDS IS 60947 Low voltage switchgear and controlgear IS 11171 Dry type transformers IS 13703 Low voltage fuses for voltages not exceeding 1000V AC or 1500 V IS 10118 Code of practice for selection, installation and maintenance of switchgear and controlgear IS 60898 Electrical Accessories - circuit breakers for over protection for household and similar installations IS 1901 Visual indicator lamps IS 60079 Explosive atmospheres IS 5572 Classification of hazardous areas (other than mines) having flammable gases and vapours for electrical installation IS:2551 Danger notice plates		
3.0	LIGHTING/ WELDING DISTRIBUTION BOARDS		
3.1	Operational Front		

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999-558-E005	
		VOLUME II	
		SECTION - I	
		REV. 0	DATE:
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	SHEET 2 OF 9	

3.2	Type of execution of modules (functional unit)		
3.3	Type of sheet steel		
3.4	Sheet metal thickness (minimum)		
a)	Non-load bearing covers	mm	
b)	Non-load bearing partitions	mm	
c)	Load bearing members	mm	
d)	Frames	mm	
e)	Door	mm	
f)	Withdrawable unit (if applicable)	mm	
3.5	Cable alley width (minimum)	mm	
3.6	Bus bar material		
3.7	Earth bus bar material		
3.8	Degree of Protection		
a)	Main Panel		
b)	Transformer cubicle		
3.9	Gland plate thickness	mm	
3.10	AC LDB/ WDB		
a)	No. of Incomers		
b)	Bus coupler required		
c)	Incomer and Bus coupler rating	A	
d)	Type of Incomer and Bus coupler		
e)	Type of Outgoing Feeders		
f)	Outgoing feeders rating	A	

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999-558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE:
		SHEET 3 OF 9	

g)	Cable entry		
3.11	Lighting Transformer		
a)	Rating	kVA	
b)	Type of cooling		
c)	Voltage ratio	V	
d)	Rated frequency	Hz	
e)	No. of phases		
f)	Vector group		
g)	Off circuit taps		
	Tap range, steps	%	
	Voltage of each tap	V	
h)	Impedance at rated current, frequency at 75 °C	%	
i)	Rated current		
	Primary	A	
	Secondary	A	
j)	Transformer type		
k)	Transformer winding insulation		
l)	Transformer winding insulation temperature rise limit		
n)	Type of ventilation arrangement provided for transformer enclosure		
o)	Winding conductor material		
p)	Iron loss at 50 Hz and 100% rated voltage	kW	

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999-558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE:
		SHEET 4 OF 9	

q)	Copper loss at rated load at 75 °C	kW	
r)	Regulation at full load at 75 °C and 0.8 p.f. lagging		
s)	Weight	kg	
4.0	LIGHTING PANELS		
4.1	Application		
4.2	Type of sheet steel		
4.3	Sheet metal thickness (minimum)		
3.4	Degree of Protection		
a)	Indoor panel		
b)	Outdoor panel		
c)	Canopy in outdoor panel		
4.5	Bus bar material		
4.6	Earth bus bar required		
4.7	Earth bus bar material (if applicable)		
4.8	Gland Plate	mm	
4.9	Earthing studs required		
4.10	Hinged door with locking facility		
4.11	AC Lighting Panel		
a)	Incomer rating	A	
b)	Type of Incomer		
c)	Earth Leakage Circuit Breaker (ELCB) in incomer required		

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999-558-E005	
		VOLUME II	
		SECTION - I	
		REV. 0	DATE:
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	SHEET 5 OF 9	

d)	Type of Outgoing Feeders (non-flameproof panel)		
e)	Timer required for indoor panel		
f)	Timer required for outdoor panel		
g)	Timer required Street Light panel/ High mast feeder pillar		
h)	Photocell required for Street Light panel/ High mast feeder pillar		
i)	Outgoing feeders rating	A	
5.0	COMPONENTS OF LIGHTING SYSTEM EQUIPMENT		
5.1	Moulded Case Circuit Breaker (MCCB)		
a)	Rated voltage	V	
b)	Number of poles		
c)	Rated short circuit duty	kA	
d)	Rated breaking capacity (rms)	kA	
e)	Rated making current (peak)	kA	
f)	Release with short circuit		
g)	Release with overload		
h)	Release with under voltage		
i)	Auxiliary contacts		
	Numbers	NO+NC	
	Rating	A	
5.2	Switch-Fuse Unit		
a)	Utilisation category for main contacts		

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999-558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE:
		SHEET 6 OF 9	

b)	Number of poles		
5.3	Miniature Circuit Breaker		
a)	SPN MCB rating (min)	A	
b)	DP MCB rating (min)	A	
c)	TPN MCB rating (min)	A	
d)	Short time rating	kA	
e)	Magnetic short circuit protection required		
f)	Thermal overload protection required		
5.4	Current Transformer		
a)	Type		
b)	Secondary current rating	A	
c)	Burden	VA	
d)	Accuracy class		
e)	Instrument Safety Factor		
5.5	Voltage Transformer		
a)	Type		
b)	Secondary terminal voltage (phase-phase)	V	
c)	Burden	VA	
d)	Accuracy class		
e)	Winding configuration		
f)	System grounding		
5.6	Indicating Meters		
5.6.1	Ammeter		

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999-558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE:
		SHEET 7 OF 9	

a)	Type		
b)	Shape		
c)	Size		
d)	Accuracy		
e)	Current coil rating	A	
f)	Angle of deflection	deg	
5.6.2	Voltmeter		
a)	Type		
b)	Shape		
c)	Size		
d)	Accuracy		
e)	AC voltage coil rating	V	
f)	DC voltage coil rating	V	
g)	Angle of deflection	deg	
5.6.3	Energy meter (if applicable)		
a)	Type		
b)	Accuracy		
c)	Current coil rating	A	
d)	Voltage coil rating	V	
5.7	Power Contactors		
a)	Coil voltage (nominal)		
	AC contactors	V	
	DC contactors	V	
b)	Current rating of contacts		

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999-558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE:
		SHEET 8 OF 9	

	Power	A	
	Control	A	
5.8	Under voltage relay		
a)	Type		
b)	Coil voltage rating	V	
c)	Means for in-built testing provided		
5.9	Timer		
5.9.1	Time switch		
a)	Type		
b)	Range	hr	
c)	Coil voltage rating	V	
5.10	Selector switch		
a)	Type of selector switch		
b)	Lockable		
5.11	Push Button		
a)	Voltage grade	V	
b)	Potential free contacts		
5.12	Indicating Lamps		
a)	Lens Colour		
	ON condition		
	OFF condition		
b)	Circuit voltage	V	

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-RC-999-558-E005	
		VOLUME II	
		SECTION - I	
	2 X 500 MW NTPC MOUDA ST-I FGD 3 X 660 MW NORTH KARANPURA FGD 3 X 660 MW NTPC BARH ST-I FGD 3 X 660 MW NPGCPL NABINAGAR STPP FGD 2 X 660 MW NTPC BARH ST-II FGD 2X250MW NSPCL BHILAI TPP FGD 3X200+3X500 MW NTPC RAMAGUNDAM TPP FGD 3X200+3X500+1X500 MW NTPC KORBA TPP FGD 4X250 MW BRBCL NABINAGAR STPP FGD	REV. 0	DATE:
		SHEET 9 OF 9	

5.13	Cable Glands		
a)	Type		
b)	Material		
c)	Nickel Plating provided		
d)	Flameproof glands with flameproof equipment		
5.14	Cable Lugs		
a)	Type		
b)	Material		
6.0	PAINTING		
6.1	Paint shade		
a)	LDBs		
b)	LPs		
6.2	Paint Finish		
a)	Interior		
b)	Exterior		
6.3	Paint Thickness	Microns	

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 1 OF 22	

SECTION – II

STANDARD TECHNICAL REQUIREMENTS

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 2 OF 22	

1.0

INTENT OF SPECIFICATION

1.1

The requirements given in specification shall be fully complied with.

1.2

The “design” shall broadly cover the selection of components, materials, sizes etc. for the equipment of supply in vendor’s scope. Complete responsibility of establishing the correctness of equipment design rests with the vendor.

1.3

It is not the intent to specify herein all the details of design and manufacture. However, the equipment shall conform in all respects to high standards of design, engineering and workmanship, and shall be capable of performing required function in a manner acceptable to Purchaser, who will interpret the meaning of drawings and specifications and shall be entitled to reject any work or material, which in his judgement is not in full accordance herewith.

1.4

Make of all equipment and components shall be to the approval of Purchaser.

2.0

CODES & STANDARDS

2.1

The material shall comply with all currently applicable safety codes and statutory regulations of India as well as of the locality where the material is to be installed.

2.2

The material, construction, manufacture, inspection and testing shall conform to the latest revisions of standards as specified in Data Sheet A.

2.3

In case of conflict between the applicable reference standard and this specification, stringent requirement shall govern.

3.0

DESIGN REQUIREMENTS

3.1

LIGHTING DISTRIBUTION BOARD (LDB) / WELDING DISTRIBUTION BOARD (WDB)

3.1.1

General Requirements of LDBs/ WDBs

a)

LDB/WDB shall be totally enclosed, modular in construction, indoor type and suitable for electrical system data as specified in Data Sheet-A. The LDB/ WDB shall be free standing type suitable for installation on cable trenches / floor.

b)

LDB/ WDB shall consist of dust and vermin proof cubicles without the use of louvers (except the transformer compartment, where applicable).

c)

Good quality synthetic rubber / neoprene gaskets shall be put around the door, cover edges and cut-out edges for push button, lamps etc. for protection against dust. The door when closed, shall compress the gasket uniformly.

d)

Cut-out edges for instruments, relays etc. shall have sufficient overlap surface to minimize the dust entry. The arrangement for the front mounting of switch

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 3 OF 22	

handles shall render the LDB/ WDB reasonably dust free such that the normal operations are not affected.

e) The LDB/ WDB shall be designed to prevent contact with live parts both within the modules and in the cable alley.

f) The bidder shall be responsible to check and coordinate the MCB characteristic with back up fuses etc. provided.

g) All equipment shall be constructed of non-hygroscopic and non-inflammable materials.

h) All components mounted in the LDB/ WDB shall be accessible and shall not impede access to wiring or terminals. All faults except busbar fault which may occur within any individual unit shall be confined within that unit only and shall not cause shutdown of any section of the board other than the affected unit itself. Maintenance and inspection shall be possible in any individual unit without affecting other units.

i) Incoming unit shall comprise of either switch-fuse/ composite switch-fuse unit or MCCB as per Data Sheet A. Outgoing units shall be either switch-fuse/ composite switch-fuse unit or MCCB as per data Sheet A.

j) Interlock between compartment door and modules shall be provided such that the door cannot be opened without switching off the power supply to the module.

k) Defeat interlock shall be provided for the units comprising of switch or moulded case circuit breaker as a means of isolation device, such that it is possible to open the door with device ON. It shall not be possible to close the door till the interlock has been reinstated.

l) Each LDB/ WDB shall be fitted with base frame made of angle or channel.

m) All fixing nuts and bolts together with grounding bolts shall be provided.

n) Lifting lugs shall be provided for each shipping section of LDB/ WDB. Removal of such lugs or hooks shall leave no opening in the LDB/ WDB.

3.1.2 LDB/ WDB with transformers (Additional Features)

a) The LDB/ WDB shall be arranged in two adjacent but separate compartments, one compartment for the lighting transformer and the other for the incoming & outgoing feeders etc.

b) The transformer shall be mounted on the base channel and it shall be possible to easily remove the transformer from the cubicle after opening the door. Necessary portable ramp made of mild steel shall be supplied along with each LDB/ WDB.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 4 OF 22	

c) Independent gasket hinged door with operating handle shall be provided for access to transformer & its taps. Operating handle shall have built-in key locking arrangement.

d) Suitable ventilation arrangement for the transformer compartment to dissipate the heat of the transformer shall be provided. The arrangement shall be in the form of louvers and the same shall be provided with galvanised wire mesh with dust catchers on the inside.

e) Connections between transformer secondary terminals and the busbars shall be made by using PVC insulated flexible copper cables or busbars.

f) Warning plate shall be provided on transformer enclosure. The inscription of warning plate shall be as given below:

- DO NOT OPEN DOORS WHEN ENERGISED

- KEEP TAPS AT SAME POSITION FOR ALL PHASES

g) Transformer enclosure shall be provided with a danger plate.

3.1.3 Lighting Transformer/ Welding Transformer

a) Transformer, where specified, shall form an integral part of LDB/ WDB.

b) Lighting transformer shall be dry type, natural air cooled and suitable for mounting inside the lighting distribution board. Transformer particulars shall be as specified in Data Sheet A.

c) Rating of transformer shall be as per BOQ.

d) Winding shall be of copper material and maximum winding temperature at full load and under site conditions shall not exceed 120 °C.

e) Transformer shall be suitable for cable connections on the primary side and flexible cable or busbar connection on the secondary side.

f) The secondary neutral of the transformer shall be brought out for getting a grounded 4 wire supply system.

g) The transformer neutral shall be brought outside the LDB/ WDB for earthing. The neutral bus bar shall be insulated from the LDB/ WDB enclosure.

h) Transformers shall be provided with the rollers, pulling holes, lifting lugs, jacking positions etc.

3.1.4 Busbars, Connections and Joints

a) Busbars shall be supported on non-hygroscopic and non-inflammable insulators of material such as glass reinforced moulded plastic material, epoxy cast resin

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 5 OF 22	

etc. Separate supports shall be provided for each phase of the busbars. Insulation level of neutral busbar shall be same as that of phase busbars.

b) Busbars shall be contained in a separate vermin-proof compartment within the LDB/ WDB and shall have bolted sheet steel covers for providing suitable access.

c) Busbar clearances in the air shall be as per applicable standard for 415V, 3 phase system.

d) Temperature for busbars, droppers and connections shall not exceed 90 deg.C for an ambient of 50 deg.C while carrying maximum continuous current.

e) The busbar, busbar connections and supports shall have sufficient strength to withstand thermal and electromechanical stresses produced by the specified short circuit level of the system.

f) Busbars (including neutral busbar) shall be capable of carrying the short-time current specified in Data Sheet A. The duration of short-time current shall be 1 sec unless mentioned otherwise in Data Sheet A. For the specified current and duration, there shall be no damage to the equipment.

g) The neutral bus shall be rated same as phase bus.

h) Main busbars and connections shall be prominently marked and displaced for standard sequence counting from rear to front, top to bottom, or left to right as viewed from the switching device operating mechanism side.

i) Busbars and connections shall be provided with colour coded PVC sleeves. All live parts shall be properly shrouded with insulating material.

j) Earth busbar shall be provided separately.

k) Busbar Joints

- Busbar and tap off joints shall be bolted type.
- Busbars shall be thoroughly cleaned before jointing. Suitable contact grease shall be applied to remove oxide film just before jointing.
- For copper busbars, the connecting portion shall be tinned or silver plated.

3.1.5 Wiring and Terminals

a) All internal wiring for connections to remote equipment shall be brought to terminal boards. Spare contacts of devices shall also be wired upto terminal board as per schemes. Wires shall not be jointed or teed-off except at terminal points.

b) Wiring shall be made by 1100 volt grade three / seven strand PVC insulated copper wire having a cross-sectional area of not less than 1.5 sq.mm. All

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 6 OF 22	

connections from CT leads upto instruments, terminals shall be made by copper wires of minimum 2.5 sq.mm size.

c) All wiring shall be made with the Colour Codes specified below :

i) 3 phase AC Connections

Phase 1 (R)	Red
Phase 2 (Y)	Yellow
Phase 3 (B)	Blue
Neutral	Black

ii) 1 phase AC Connections

Phase	Red / Yellow / Blue (as per associated circuit)
Neutral	Black

iii) DC Connections

Positive	White
Negative	Grey

iv) Earth Connection Green

d) Where wiring passes from one compartment to another, the aperture shall be 'Bushed' to prevent damage to wires against sheet metal edges. Bushes may comprise of good quality rubber / PVC grommets.

e) Every wire end shall be fitted with numbered ferrules of white or yellow colour having glossy finish with identification number engraved in black. Ferrules shall be made of moisture and oil resisting insulating material. Ferrules shall be of interlocked type or tight fitting type. Ferrules shall be so fitted that they will not get detached, when the wire is removed from the terminal.

f) System of marking of wiring shall be as per applicable standard.

g) All wires used internally shall have crimped on tinned copper lugs for terminations.

h) Terminal boards shall be stud type with insulating barriers of adequate height.

i) Terminal boards shall have separate terminals for incoming and outgoing wires with not more than two wires connected to any one terminal.

j) Terminal boards shall be mounted vertically or in the horizontal rows and properly spaced to have clean wiring arrangement, adequate access for putting ferrules, making terminations etc. It shall be possible to read the ferrule numbers when the wiring is complete. Where terminals may be live when the equipment is isolated from the main supply, these shall be clearly marked near the terminal boards.

3.1.6 Cable Terminations

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 7 OF 22	

a) All cables, either incoming or outgoing to the LDB/ WDB, shall be terminated in a cable chamber. For each panel, there shall be a cable chamber on the side. The door of cable chamber should open or be locked with the help of a tool. Unless stated otherwise in Data Sheet A, all cables shall enter from the bottom.

b) Removable undrilled gland plates of sheet steel shall be provided in the cable chamber for entry of cables. Minimum thickness of gland plate shall be as per Data Sheet-A. The gland plate shall be of adequate size for connecting requisite number of cable glands for power and control cables.

c) Heavy duty bolt-on termination tinned copper lugs of compression type shall be used for power cable termination. The tinned copper cable lugs for all incoming and outgoing power cables shall be supplied by the vendor.

d) For supporting and clamping of cable cores at regular interval in cable alleys, suitable slotted angle upto the respective terminal blocks shall be provided.

3.1.7 Earthing

a) An earth busbar of adequate size of shall be provided at the bottom for the entire length of the LDB/ WDB. Material of earth busbar shall be GI unless mentioned otherwise in Data Sheet A.

b) Every metal part other than those forming parts of an electrical circuit shall be connected to the earth bus by means of high conductivity copper wire of size not less than 2.5 sq. mm. cross-sectional area.

c) Doors shall have a flexible copper wire for earth connection to fixed unit.

d) Each LDB/ WDB shall be fitted with two earthing studs located in accessible position on sides for connection of internal earth busbar to the external earthing connection.

e) Earth busbar shall be brought outside LDB/ WDB for making external connections.

3.1.8 Types of LDB/ WDB

a) The LDB/ WDB shall be of following type:

- LDB/ WDB-H (n) - AC LDB/ WDB with 100 kVA transformer
- LDB/ WDB-F (n) - AC LDB/ WDB with 50 kVA transformer
- LDB/ WDB-N (n) - AC LDB/ WDB with no transformer
- LDB-D (n) - DC LDB

NOTE: (n) indicates number of outgoing feeders.

b) AC LDB/ WDB (LDB/ WDB-H, LDB/ WDB-F, LDB/ WDB-N)

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 8 OF 22	

Each LDB/ WDB shall comprise of the following and comply with Data Sheet A:

- i. One lighting/welding transformer (LDB/WDB-H & LDB/WDB-F).
- ii. Incomer(s) of TP / TPN switch-fuse unit or MCCB / MCCB with neutral link as per Data Sheet A. It shall be provided on the primary side of transformer for LDB/WDB type LDB/WDB-H & LDB/WDB-F.
- iii. Set of busbars with 3 phase and neutral.
- iv. TPN switchfuse units or MCBs for each outgoing circuit.
- v. Three indicating lamps with fuses for indicating bus supply ON.
- vi. CT operated ammeter with selector switch.
- vii. VT operated voltmeter with selector switch.
- viii. Power & control terminals, earth-stud, earth busbar, designation labels, internal wiring, power cable lugs, glands etc. shall be provided to complete the LDB/ WDB in all respects.

c) DC LDB (LDB-D)

Each LDB shall comprise of following and comply with enclosed Data Sheet A:

- i. Incomer & Outgoing feeders shall be as per Datasheet-A.
- ii. Two pole DC contactor on the incoming circuit for changeover to DC in case of AC normal supply failure.
- iii. One under voltage relay of suitable range, if required.
- iv. One ON delay timer.
- v. One test push button.
- vi. Set of bus bars for positive and negative.
- vii. Two indicating lamps with fuses for indicating bus supply ON.
- viii. Power & control terminals, earth-stud, earth busbar, designation labels, internal wiring, power cable lugs, glands etc. shall be provided to complete the LDB in all respects.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 9 OF 22	

3.2 LIGHTING PANELS (LPs)

3.2.1 General Requirements of Lighting Panels

- a) LPs shall be totally enclosed, suitable for electrical system data as specified in Data Sheet A. The LP shall be suitable for mounting on wall / column / structure.
- b) Panels shall be suitable for indoor / outdoor application as per Data Sheet A.
- c) All components of the LP shall be fully mounted inside the panel. LPs shall have only one operational front. Door shall be provided to give full access to all the components. Door shall have padlocking arrangement.
- d) LPs shall consist of dust and vermin proof cubicles without the use of louvers.
- e) Good quality synthetic rubber / neoprene gaskets shall be put around the door. The door when closed, shall compress the gasket uniformly.
- f) The LPs shall be designed to prevent contact with live parts when the front door is open.
- g) All busbars (phase, neutral, positive, negative as applicable) within a panel shall be of the same size.
- h) All control wiring inside the panels shall be carried out with 1100 V grade, PVC insulated flexible copper wire of 2.5 sq. mm size.
- i) The rated continuous current of the equipment and components shall be as given in Datasheet-A. These ratings shall be obtained with the components mounted in their housing as in service without exceeding the permissible temperature rise.
- j) Each LP shall be fitted with M.S. mounting brackets.
- k) Panel shall be suitable for top / bottom cable / conduit entries. However, outdoor LPs shall have bottom cable / conduit entry. Removable undrilled gland plate of sheet steel shall be provided for entry of cables. Minimum thickness of gland plate shall be as per Data Sheet-A. The gland plate shall be of adequate size having knock-outs for requisite number cable connections. Gland plate shall be provided with gasket.
- l) The lighting panel shall be complete with copper busbars, and shall incorporate incomer and outgoing circuits as per Data Sheet-A. Number of outgoing circuits shall be as per BOQ.
- m) Each lighting panel shall be fitted with two GI earth studs located in accessible position on the outside of the panel on opposite sides.
- n) All metal parts of the panel except current carrying parts shall be bonded together electrically to the earthing stud.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 10 OF 22	

o) Each panel shall be fitted with phase barriers of fireproof insulating material in such a manner that it is not readily possible for personnel to touch the phase busbars. Insulating sheet shall be fitted around the MCBs such that only the surface and toggle of the MCBs are available on the front.

p) The supply of cable lugs for power and control cable connections forms part of the supply of equipment.

q) Each panel shall be provided with a circuit directory plate with inscriptions neatly typed and laminated, fitted on the inside of door.

3.2.2 Type of Lighting Panels

a) LP-A (n) - AC Lighting Panel

b) LP-D (n) - DC Lighting Panel

c) LP-F (n) - Fancy Lighting Panel (Decorative)

d) LP-S (n) - Street Lighting Panel

NOTE: (n) indicates number of outgoing circuits.

3.2.3 AC Lighting Panel (LP-A)

a) LPs shall be provided with incomer and requisite number of outgoing circuits as per Data Sheet-A. Number of outgoing circuits shall be as per BOQ.

b) Separate neutral shall be available at terminal block for each outgoing circuit.

c) Construction of AC Normal and AC Emergency panels shall be same.

3.2.4 DC Lighting Panels (LP-D)

a) LPs shall be provided with incomer and requisite number of outgoing circuits as per Data Sheet-A. Number of outgoing circuits shall be as per BOQ.

3.2.5 Decorative Type Lighting Panels (LP-A)

a) Decorative lighting panels shall be designed for use in areas like administrative building, service building, canteen, residential premises etc.

b) Thickness of sheet steel shall be as per manufacturer’s practice.

c) LPs shall be of tone colour with elegant finish.

d) LPs shall be provided with incomer and requisite number of outgoing circuits as per Data Sheet-A. Number of outgoing circuits shall be as per BOQ.

e) LPs shall be suitable for either surface or flush mounting. Flush mounted panels shall have the collared door suitable for matching with the wall.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 11 OF 22	

f) Lighting Panels may be provided with transparent acrylic cover for operation of MCBs.

g) LPs shall be provided with knockouts on the top, bottom and sides.

3.2.6 Street Lighting Panel (LP-S)

a) Street Lighting Panels shall be provided for feeding power supply to luminaires of street light poles, flood lighting poles, lighting masts, watch towers etc.

b) Each Street Lighting Panel shall comprise of the following :

- i. One TPN door interlocked switch-fuse unit incomer. Interlock defeat feature shall also be provided.
- ii. Three pole AC Contactor
- iii. 0 - 24 hrs timer and/or photo-electric switch for automatic switching of contactor
- iv. Three phase & neutral busbars
- v. Single pole or three pole MCBs for each outgoing circuit as per Data Sheet A
- vi. Two lamps for bus supply ON & OFF indications
- vii. Complete wiring arrangement as per control scheme.
- viii. Auto-Manual selector switch
- ix. ON push button
- x. OFF push button

c) Switching ON and switching OFF shall be through both 0 - 24 hrs timer and light sensor in automatic mode.

d) One number light sensor in weather proof enclosure having IP:55 degree of protection shall be supplied loose along with each SLP.

e) Internal power wiring shall be done with PVC insulated Cu wire of suitable size. All control wiring inside the panel shall be carried out with 1100 V grade, PVC insulated flexible copper wires.

f) Two nos. outgoing circuit in each panel shall be tapped before contactor for watch tower supply.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET	12 OF 22

4.0

COMPONENTS OF LDB/WDB AND LIGHTING PANEL

4.1

MOULDED CASE CIRCUIT BREAKERS

a)

Moulded case circuit breakers (MCCBs) shall be provided when called for in Data Sheet A for use in lieu of switch fuse. MCCB shall meet the requirements stipulated in Data Sheet A.

b)

MCCBs in AC circuits shall be of single throw, air break, heavy duty type triple pole construction arranged for simultaneous three pole manual closing and opening and for automatic tripping at short circuit and overload. Neutral link shall be provided for LDB/ WDB without transformers.

c)

Operating mechanism shall be quick make, quick break and trip free type.

d)

The ON, OFF & TRIP positions of the MCCB shall be clearly indicated so as to be visible to the operator when mounted as in service. Operating handle shall be provided on front of the LDB/ WDB.

e)

MCCBs shall be capable of withstanding the thermal stresses caused by overloads and short circuits. The maximum tripping time under short circuit shall not exceed 20 milli-seconds.

f)

MCCB terminals shall be shrouded and designed to receive cable lugs for cable sizes relevant to circuit ratings.

g)

Under voltage releases and other releases shall be provided as specified in data Sheet-A.

4.2

SWITCH-FUSE UNITS

a)

These units shall preferably comprise of switches having integral fuses, called composite units. Alternatively, combination units of separate switch and fuse may also be acceptable.

b)

These units shall be provided for general purpose i.e. incoming or outgoing units.

c)

The units shall be of the air break air insulated type and designed to ensure safety to operating personnel.

d)

Composite units shall have integral fuses i.e. fuse carrier with fuse link (fuse link forming the moving contact). The design shall ensure that the moving contact is not live when switch is open i.e. in OFF position, so as to facilitate removal of fuse.

e)

The switch shall be capable making and carrying the system prospective fault current, but limited in magnitude and duration by the cut off characteristics of the largest HRC fuse link that may be fitted to that unit.

f)

The fixed contact shall be so shrouded that maintenance of the unit can be carried out in safety with the busbars live.

TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
	VOLUME II	
	SECTION II	
	REVISION: 0	DATE: 22.08.2016
	SHEET 13 OF 22	

g) Where one isolating switch is used as the incoming device, the incoming side fixed contacts shall be shrouded to ensure that maintenance can be carried out with the remote fuse and switch closed.

h) Composite switch-fuse or the combination of switch and fuse shall meet the requirements of its components as follows:

Isolating Switch

i. Switches shall be air-break, quick make, and quick break heavy duty type conforming to applicable standard.

ii. All switches shall have visible ON / OFF position indication and shall be padlockable in any (ON / OFF) position.

iii. Switches shall be door interlocked such that it shall not be possible to gain access to inside the unit unless the isolating switch is in OFF position.

iv. The switches shall be suitable for independent manual operation.

v. The switch contacts shall be of silver alloy or silver plated copper and springs of non-corrosive material.

vi. Inter-phase barriers shall be provided to prevent possibilities of phase to phase fault in the switch. The switch shall also be shrouded from all sides to prevent access to live parts on the switch after opening the unit door. The barriers and shrouding shall extend upto the height of switch to fully enclose both side terminals of the device. The arrangement shall permit easy maintenance.

High Rupturing Capacity (HRC) Fuses

i. The fuse serving as the short-circuit protective device in isolating fuse-switch units shall be of HRC cartridge, current limiting and plug-in non-deteriorating type.

ii. The fuse carriers shall be easily withdrawable for replacement of fuse. Insulated fuse pullers shall be provided where fuses are not mounted in insulating carriers to remove and replace fuses in live conditions.

iii. Fuses shall preferably be fitted with a device to indicate operation (i.e. when the fuse has blown).

iv. Live terminals of fuse bases shall be shrouded to prevent contact with personnel where fuse links are not mounted in carriers and are directly plugged into the fuse base. Inter-phase barriers extending throughout the length of the fuse base shall be provided to prevent inter-phase short circuit. They shall be shrouded from all sides to prevent accidental contact.

v. Fuse carriers and bases shall be of good quality moulded insulating material. Porcelain fuse bases and carriers will not be accepted.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET	14 OF 22

vi. The rating and characteristics of fuse links shall be chosen appropriately for short circuit protection of circuits downstream.

4.3 MINIATURE CIRCUIT BREAKERS

a) The use of miniature circuit breakers (MCBs) combining thermal overload and magnetic short circuit protection shall be application for the outgoing circuits of Lighting Panels.

b) MCBs shall have suitable rating as specified in Data Sheet A.

c) MCBs shall be suitable for housing in the lighting panel and for connection of copper link bus bar at the incoming and copper lugs at the outgoing ends.

d) The terminals of MCB and ON/OFF positions shall be clearly and indelibly marked.

4.4 CURRENT TRANSFORMERS

a) CTs shall be air insulated having insulation class E or better, cast resin type and shall be capable to withstand the thermal and mechanical stresses resulting from maximum short circuit.

b) The short time current duration for CTs shall be one second.

c) CT primary current shall not be less than the full load thermal rating of the associated circuit. CT secondary current shall be as specified in Data Sheet A. Polarity shall be marked in a suitable manner. The ratings shall be adequate to cater for the burden of connected instruments.

d) CTs shall be of bar primary / wound primary / ring type capable of carrying the rated primary current.

4.5 VOLTAGE TRANSFORMER

a) Voltage transformers (VT) shall be dry, cast resin type comprising of single phase or three phase units. They shall have their primary windings protected by current limiting fuses with interrupting capacity corresponding to that of the lighting board / panel.

b) VT secondary windings shall be earthed in LDB/ WDB / LP through link, which can be removed for insulation testing.

c) Three phase voltage transformers shall be as per Data Sheet A.

Single phase VTs shall have voltage rating of (Nominal System Voltage / $\sqrt{3}$) V / (110 / $\sqrt{3}$) V so that secondary voltage shall be 110 volts phase to phase when the secondary winding is star connected.

d) VTs shall have an output rating adequate to cater to the burden connected to them.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET	15 OF 22

4.6 INDICATING METERS

- a) Meters shall be panel mounted, flush type and suitable for rear terminal connection.
- b) Meters and instruments shall be enclosed in dust proof, moisture resistant black finished cases and shall be suitable for tropical use. Instruments shall be suitable for operation from the secondary windings of CTs and VTs.
- c) All instruments shall be calibrated to enable direct reading of primary quantities. Instruments shall be adjusted and calibrated at manufacturer's works and shall have means of calibration, checking and zero adjustment at site.
- d) All the divisions and the quantity to be measured shall be clearly marked. Instruments shall conform to applicable standard having black numerals and lettering on white anti-parallax dial with knife edge pointer. Indicating instruments shall be of moving iron type for AC and moving coil type for DC circuits.
- e) Instruments having metallic cases shall be fitted with earthing terminals.

4.7 CONTACTORS

- a) Contactors shall be of the air break type, electromagnetic type fitted with arc shields.
- b) The operating coil shall be suitable for satisfactory operation in the range of 85% - 110% of nominal voltage specified under the Data Sheet A. The coil shall be tropicalized having insulation not less than class 'E'.
- c) Electrically independent auxiliary contacts not less than 2NO + 2NC for interlocking and indication shall be fitted to individual power contactor.
- d) All springs shall be made out of a corrosion proof material.

4.8 RELAYS

- a) Relays shall be provided on the various circuits as per schemes. Relays shall be flush mounted on front of the board. Relay case shall be painted with dull black or egg shell black enamel and with back connected terminals. Metal cases and frames of relay shall be earthed.
- b) All relays shall be of withdrawable type with built-in testing facilities, with provision for inspection, maintenance and replacement. Where built-in test facility is not provided for a particular relay, separate suitable test block shall be provided on the board for this purpose.
- c) Relay performance shall not alter due to mechanical shock or vibration or external magnetic field which may be present at the place of mounting.
- d) Each relay shall not have less than two independent pairs of contacts.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 16 OF 22	

4.9 TIMERS

4.9.1 Time Switch

- a) Time switch shall be suitable for automatic switching ON and OFF of street lighting / flood lighting circuits.
- b) Time switch have 00 - 24 hrs clock base.
- c) Time switch shall indicate actual time and shall permit accurate time setting.
- d) Time switch shall be rugged, independent of normal fluctuations of voltage / frequency and free from maintenance.
- e) Contact rating, clock accuracy, rated voltage rating and frequency rating of timer shall be suitable to its application.
- f) Time switch shall be provided with Ni-Cd battery.
- g) Time switch shall be suitable for mounting inside the panel.

4.9.2 On/Off Delay Timer

- a) On delay timer shall be required for continuation of DC supply for a limited duration when the AC Emergency supply has been restored and DG set is under stabilisation.
- b) Timer shall be fully static and suitable for operation on normal frequency and system voltage.
- c) Timer shall have high setting accuracy, high repeat accuracy, low reset time and low power consumption.
- d) Timer shall have the time setting range as mentioned in Data Sheet A.
- e) Timer shall be suitable for mounting inside the panel.

4.10 SELECTOR SWITCHES

- a) The rating and other features of the switches shall be suitable for the application. The number of positions and the number of contacts required for each switch shall be as indicated in the schemes
- b) Selector switches shall be stay put type, provided with properly designated escutcheon plates clearly marked to show operating position.
- c) Terminals carrying potential above 120 Volts shall be shrouded to prevent accidental contact with personnel.
- d) Ammeter selector switches shall have make before break contacts.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 17 OF 22	

e) The switches shall be suitable for semi-flush mounting with the front plate and operating handle projecting out. All connection to the switches shall be from the back.

f) The arrangement for front mounting of these devices shall be such as to make them reasonably dust free so as not to interfere with normal operation.

4.11 PUSH BUTTONS

a) Push button shall be heavy duty, flush mounted suitable for the application.

b) Push button shall be provided with integral escutcheon plates marked with its function identified as per schemes.

c) Colour shall be appropriate to the function.

d) Minimum number of contacts shall be 2 NO + 2 NC or as per the requirements of control scheme.

4.12 INDICATION LAMPS

a) Indication lamps shall be complete with lens covers and holders.

b) Each lamp shall be fitted with a durable resistance integrally wired in series with the lamp. Alternatively, lamps with built in transformers are acceptable.

c) The lamp cover (lens) shall be translucent of appropriate colour.

d) Bulbs and covers shall be interchangeable, easily replaceable from the front without the need for any special means.

e) Terminals having potential above 120V shall be shrouded to prevent contact with personnel.

f) Terminals shall be suitable for ring type copper cable lugs of size depending upon the circuit rating.

4.13 CABLE GLANDS

a) Whether specifically mentioned or not, cable glands of suitable sizes shall be supplied along with each equipment for power and control cables.

b) Rubber components used in the gland shall be of neoprene.

c) Name / trade name of manufacturer, type no. and applicable range of outer diameter of cable shall be engraved / indelibly printed on the cable gland.

4.14 CABLE LUGS

a) All equipment shall be supplied with the power and control cable lugs of suitable size, whether specifically mentioned or not.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 18 OF 22	

b) Name / trade name and size of lug shall be engraved/ indelibly printed on each cable lug.

4.15 TERMINALS

a) Terminals shall be stud type of copper material.

b) Terminals shall be provided with transparent cover(s).

c) Separate terminals shall be available for each termination of loop-in and loop-out power connections.

5.0 LABELING

5.1 Labels to identify all the Main assemblies, Sub-assemblies and components of the LDB/ WDB and LPs shall be provided.

5.2 Name and rating plate / marking shall be provided as required by relevant standard applicable to each component / assembly to be identified.

5.3 Labels shall be of two colour, three layer plastic material with matt or semi matt finish or of the anodised aluminium sheet.

5.4 All labels other than “Danger” or “Warning” labels shall have black lettering on a white background. Danger labels shall be as per applicable standard and shall not be affixed on to removable parts.

5.5 All labels shall be securely fixed on to the equipment by means of self tapping screws or other approved means.

5.6 Stick-on type labels of good quality and permanent mounting shall be acceptable for internally mounted components only.

5.7 A list of all such items to be labeled and text and type of labels to be provided is given below:

a) BOARD DESIGNATION (MAIN EQUIPMENT LABEL)

i. **Inscription :**
Designation & LDB/ WDB number for LDB/ WDB.
Designation and LP number for LPs.

ii. **Location :**
Top centre in the front of the LDB/ WDB.
Top centre in the front of the LP.

iii. **Material :**
3 Layer plastic material, fixation by self tapping, non-rusting screws, black inscription on white back ground.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET	19 OF 22

b) **OUTGOING - FEEDER DESIGNATION**

i. **Inscription** : Module number, LP number / purpose.

ii. **Material** :
Black engraving on white anodised aluminium plate of thickness 1.6 mm or more. Plate to be secured with screws.

c) **COMPONENT DESIGNATION**

i. **Inscription** : Letter symbol / Legend as assigned in schemes.

ii. **Location** : Near or on the component

iii. **Material** : Stick-on type

5.8 CIRCUIT DIAGRAM / DIRECTORY PLATE

a) A diagram is to be prepared for fixing to the inside cover of every lighting panel giving details of the points controlled by each circuit.

b) The circuit list shall be typed or printed stating the location of the equipment served, rating of the protective unit and the circuit loadings.

c) The list shall be mounted on the inside of the cover door and shall be protected by an acrylic sheet cover to be easily removable to permit circuit modifications.

6.0 SURFACE TREATMENT

6.1 All metal parts and the surfaces (exterior & interior) of equipment, unless stated otherwise in case of reflectors, shall be degreased by dipping in hot alkaline solution and rubbed with wire brush to remove oil & scale from them & then rinsed in water. Alternatively, they may be shot / sand blasted.

6.2 Parts shall be pickled by dipping in hydrochloric acid tank to remove the rust from the surfaces formed during storage of sheets & then rinsed to remove traces of the acid. The cleaning and pretreatment of all metal parts shall be as per applicable standard.

6.3 The surfaces to be painted shall then be prepared by phosphatizing to protect them from further rusting & to create a good bond with the paint. The pretreatment shall conform to the applicable standard.

6.4 All parts shall then be subjected to a coat of red oxide primer paint.

6.5 All inside and outside surfaces of panel shall be spray painted with synthetic enamel of the shade and minimum thickness as per Data Sheet A.

6.6 Electrostatic or powder painting shall be acceptable subject to purchaser's approval.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET	20 OF 22

6.7 Wherever possible, finished parts shall be coated with peelable compound by spraying method to protect the finished product from scratches, grease, dirty and oily spots during handling and transportation.

7.0 PACKING

7.1 Packing procedure shall conform to the following :

a) The equipment shall be properly packed before dispatch. The packing shall prevent damage to the contents while handling and lengthy period of outdoor storage.

b) The equipment shall be wrapped in weather proof packing using polythene sheets/ air bubble sheets/ thermocol sheets and then secured in wooden packing cases. Wood for wooden packing cases/ crates shall be chemically treated to prevent deterioration due to fungi and attack by termites, borers, and any other kind of infection.

c) The equipment shall be secured by fixing base plate/ frame with the help of bolt and nuts etc. to bottom frame of the wooden packing cases/ crates. Suitable cushioning material like rubberised coir (min. 50 mm thick & 100 mm wide) shall be provided on the bottom support. Gap between the panel and casing shall be filled with rubberised coir with distance between consecutive supports less than 500mm.

7.2 Specification for the sea worthy packing, if enclosed, for the export jobs shall form part of the specification.

8.0 INSPECTION & TESTING

8.1 Bidder shall confirm compliance with the BHEL Standard Quality Plan (PE-QP-999-558-E005) without any deviations. At contract stage, the successful bidder shall submit the same QP for BHEL/ ultimate customer's approval. In case bidder has reference QP agreed with ultimate customer, same can be submitted for specific project after award of contract for BHEL/ ultimate customer's approval. There shall be no commercial implication to BHEL on account of any changes in QP during contract stage.

8.2 All the components and completely assembled equipment shall be tested as per the latest edition of standards. Charges for these tests shall be deemed to be included in equipment price.

8.3 All the specified type and routine tests shall be carried out to verify the rating and performance of the equipment. Where valid type test certificates in evidence of equipment performance claimed are available & approved by purchaser, the requirements for conducting type tests may be waived. The general arrangement of object under test shall be to purchaser's approval.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 21 OF 22	

8.4 Functional testing shall be carried out for Lighting/Welding Distribution Boards/ Lighting Panels.

8.5 All manufacturing processes viz. machining, sheet forming, electroplating, wire routing, cleating & crimping, assembly, surface preparation shall conform to good manufacturing practices.

8.6 Inspection for dimensional & visual checks especially of the following, with respect to contract drawings, documents & standards shall be conducted:

a) General sturdiness & rigidity of equipment.

b) Surface finishing.

c) Gasketting.

d) Inter-changeability.

e) Constructional features viz. location, accessibility & marking of components, segregation, accessibility to live parts (shrouding) etc.

f) Completeness of scope.

8.7 Safety interlocking verification shall be done.

8.8 Each lighting transformer shall be routine tested and one transformer of each rating shall be type tested in accordance with relevant standard in case type test certificates of similar transformers are not available / not acceptable to the purchaser.

8.9 Equipment shall be liable for rejection if tolerances on the values of dimensions, power consumption, impedances, temperature rise etc. exceed the specified values by purchaser and / or standards.

9.0 TOOLS AND TACKLE

9.1 Tools & tackle which are essential to facilitate assembly, adjustments, erection, maintenance & dismantling of equipment shall be provided as part of equipment supplied.

9.2 The above tools shall be supplied along with the initial consignment of equipment so as to be available prior to erection but may not be used for erection purposes.

9.3 Vendor shall also submit a list of recommended tools and tackle. Acceptance of these tools and tackle shall not be a binding on the purchaser.

9.4 Schedule of tools & tackle shall be filled up by bidder.

10.0 SPARES

10.1 Mandatory spares (if applicable) are indicated in BOQ-cum-price schedule.

	TECHNICAL SPECIFICATION FOR DISTRIBUTION BOARDS	SPECIFICATION NO. PE-SS-999-558-E005	
		VOLUME II	
		SECTION II	
		REVISION: 0	DATE: 22.08.2016
		SHEET 22 OF 22	
10.2 Erection & commissioning spares are included in the bidder's scope of supply. Bidder to furnish list of E&C spares in the relevant schedules of the Bid Form and Price Schedules.			

ITEM : (MATERIAL, CLASS, GRADE, RATING, SIZE ETC.): LIGHTING PANEL & LIGHTING DISTRIBUTION BOARDS		STANDARD QUALITY PLAN				Q.P. No. : 0000-995-QOE-S-034 REV. : 01 DTD: 15/03/04 PAGE 1 OF 3 VALID UPTO : 14.03.07				REVIEWED BY S.D. SINGH O.P. NIRANJAN I. J. SINGH	APPROVED BY ANIL GUPTA		
SL. NO.	COMPONENT & OPERATIONS	CHARACTERISTICS	CLASS	TYPE OF CHECK	QUANTUM OF CHECK		REFERENCE DOCUMENT	ACCEPTANCE NORMS	FORMAT OF RECORD	AGENCY			REMARKS
					M	C/N				M	C	N	
1	2	3	4	5	6	7	8	9	10	11			
1	Lighting Panels & Lighting Distribution Boards Final Inspection and Testing	a) Overall Dimensions	MA	Meas.	100%	One Panel/Type/lot	NTPC/Main supplier Appd. Drg / data sheet	NTPC/Main supplier Appd. Drg / data sheet	Inspt. Report	P	W	W	
		b) Thickness of sheet	MA	Meas.	100%	--DO--	--DO--	--DO--	--DO--	P	W	W	
		c) Paint shade	MA	Visual	100%	--DO--	--DO--	--DO--	--DO--	P	W	W	
		d) Thickness of paint	MA	Meas	100% of items	Min. 5 points/Panel	--DO--	--DO--	--DO--	P	W	W	
		e) Surface finish	MA	Visual	100%	--DO--	Smooth, without lump	Smooth, without lump	--DO--	P	W	W	
		f) Adhesion Test	MA	Mech.	One sample/lot/size	One sample lot	Should not peel off	Should not peel off	--DO--	P	W	W	
		g) Name Plate	MA	Visual	100%	10% of each type	NTPC/Main supplier Appd drg/ data sheet	NTPC/Main supplier Appd drg/ data sheet	--DO--	P	W	W	
		h) Tightness of bus bar bolts	MA	Mech	100%	One Panel/Type/lot	Manufacturer Std.	Manufacturer Std.	--DO--	P	W	W	
		i) Bus Bar Clearance	MA	Meas.	100%	--DO--	NTPC/Main supplier Appd drg /data sheet	NTPC/Main supplier Appd drg /data sheet	--DO--	P	W	W	

LEGEND: RECORDS IDENTIFIED WITH "TICK" SHALL BE ESSENTIALLY INCLUDED BY THE CONTRACTOR IN QA DOCUMENTATION

** M: MANUFACTURER/SUB-SUPPLIER, C: CONTRACTOR/NOMINATED INSPECTION AGENCY (SUBJECT TO PRIOR APPROVAL OF NTPC), N: NTPC, INDICATE "P" PERFORM "W" WITNESS AND "V" VERIFICATION AS APPROPRIATE

"CHP" BY NTPC SHALL BE IDENTIFIED IN COLUMN "N" AS "W".

FORMAT -QS-01-QAI-P-10F2-R0

ENGINEERING DIV./QA&I

ITEM : (MATERIAL, CLASS, GRADE, RATING, SIZE ETC.): LIGHTING PANEL & LIGHTING DISTRIBUTION BOARDS		STANDARD QUALITY PLAN				Q.P. No. : 0000-999-QOE-S-034 REV. : 01 DTD: 15/03/04 PAGE 2 OF 3 VALID UPTO :14.03.07				REVIEWED BY S.D. SINGH O.P. NIRANJAN I. J. SINGH	APPROVED BY S.D. SINGH O.P. NIRANJAN I. J. SINGH	
SL. NO.	COMPONENT & OPERATIONS	CHARACTERISTICS	CLASS	TYPE OF CHECK	QUANTUM OF CHECK		REFERENCE DOCUMENT	ACCEPTANCE NORMS	FORMAT OF RECORD	AGENCY		
					M	C/N				M	C	N
1	2	3	4	5	6	7	8	9	10	11		
	j) GA& Bill of material	CR	Phy.	100%	10% of each type	--DO--	--DO--	--DO--	P	W		
	k) Identification of Component lay out	MA	Visual	100%	One Panel/ type/lot	--DO--	--DO--	--DO--	P	W		
	l) Completeness of											
	i) Wiring	MA	Elect.	100%	--DO--	--DO--	--DO--	--DO--	P	W		
	ii) Ferruling	MA	Visual	100%	--DO--	--DO--	--DO--	--DO--	P	W		
	m) Size of wires	MA	Meas.	100%	--DO--	--DO--	--DO--	--DO--	P	W		
	n) Colour coding of bus bar	MA	Visual	100%	--DO--	--DO--	--DO--	--DO--	P	W		
	o) Spare terminals	MA	Meas.	100%	--DO--	--DO--	--DO--	--DO--	P	W		
	p) Shrouding of live parts	MA	Visual	100%	--DO--	--DO--	--DO--	--DO--	P	W		
	q) Door earthing	MA	Megger	100%	--DO--	--DO--	--DO--	--DO--	P	W		
	r) Functional Tests including HV, IR & continuity	CR	Elec.	100%	10%	--DO--	--DO--	--DO--	P	W		
	s) Degree of protection (Paper insertion method)	CR	Phy.	100%	One Panel/ type/lot	NTPC/Main supplier Appd drg./data sheet	NTPC/Main supplier Appd drg./data sheet	--DO--	P	W		

LEGEND: RECORDS IDENTIFIED WITH "TICK" SHALL BE ESSENTIALLY INCLUDED BY THE CONTRACTOR IN QA DOCUMENTATION

*** M: MANUFACTURER/SUB-SUPPLIER, C: CONTRACTOR/NOMINATED INSPECTION AGENCY((SUBJECT TO PRIOR APPROVAL OF NTPC) N: NTPC. INDICATE "P" PERFORM "W" WITNESS AND "V" VERIFICATION AS APPROPRIATE

"CHP" BY NTPC SHALL BE IDENTIFIED IN COLUMN "N" AS "W".

FORMAT -QS-01-QAL-P-10/F2-R0

		ITEM : (MATERIAL, CLASS, GRADE, RATING, SIZE ETC.): LIGHTING PANEL & LIGHTING DISTRIBUTION BOARDS	STANDARD QUALITY PLAN	Q.P. No. : 0000-999-QOE-S-034 REV. : 01 DID: 15/03/04 PAGE 3 OF 3 VALID UPTO : 14.03.07	REVIEWED BY  S.D. SINGH  O.P. NIRANJANA  I.J. SINGH	APPROVED BY  ANIL GUPTA  A. J. SINGH
ANNEXURE 1 TO SQP NO. 0000 - 999 - QOE - S - 034 REV 01						
Sl. No		Item	Make			
1 Indicating Meters 2 Indicating lamp 3 Current Transformer 4 Potential Transformer 5 Dry Type Transformer 6 Timer 7 MCB 8 On-Off Switch 9 Fuse 10 Push Button 11 Contactor 12 Terminal Block 13 Wires		NOTE : Makes of major BOIs will be subject to NTPC approval / acceptance				
LEGEND: RECORDS IDENTIFIED WITH "TICK" SHALL BE ESSENTIALLY INCLUDED BY THE CONTRACTOR IN QA DOCUMENTATION ** M: MANUFACTURER/SUB-SUPPLIER, C: CONTRACTOR/NOMINATED INSPECTION AGENCY (SUBJECT TO PRIOR APPROVAL OF NTPC) N: NTPC. INDICATE "P" PERFORM "W" WITNESS AND "V" "CHP" BY NTPC SHALL BE IDENTIFIED IN COLUMN "N" AS "W".						