

RFQ/NIT HEADER DETAIL

ORGANIZATION NAME	TRICHY, BHEL	RFQ FLOATED UNDER THE	PURCHASE POLICY
RFQ/NIT REFERENCE	2661700569	POLICY	
CODE/ENQUIRY NO		RFQ OWNER/NIT	MR ARUNACHALAM T(AE1/PUR)
RFQ/NIT TYPE	OPEN TENDER	OFFICER/ENQUIRY OWNER	
NUMBER OF ITEMS ALREADY	17		
ATTACHED			
CURRENCY	INR - INDIAN RUPEE		
DESCRIPTION	Solid Tyres		
DETAILED DESCRIPTION	Solid tyres for material handling equipment		
NUMBER OF BID PART(S)	2	PUBLISHED DATE	20 Sep , 2017 1:13:55 PM

ATTRIBUTE(S)

ATTRIBUTE NAME	ATTRIBUTE VALUE
Delivery at	BHEL Trichy
Inspection By	BHEL engineers
Validity of the Offer	PRICE SHOULD BE FIXED AND VALID FOR 90 DAYS FROM THE DATE OF TENDER OPENING
Inspection	BHEL WORKS

DATE-TIME DETAIL(S)

BID START DATE	20 Sep , 2017 10:15:00 AM	BID DUE DATE	4 Oct , 2017 10:00:00 AM
BID OPEN DATE	4 Oct , 2017 10:30:00 AM		
(SCHEDULED)			

PRE-BID DISCUSSION DETAILS

PRE-BID DISCUSSION TYPE NOT REQUIRED

ALTERNATE BID DECRYPTOR(S)

USER DETAILS
MR Admin SANJEEVI B(SDGM/PUR)
MR CHANDRAMOHAN D(DGM/PUR)
MR CHELLIAH V(SM/PUR)
MR ARUNACHALAM T(AE1/PUR)

SELLER DETAIL(S)

CODE	ORGANIZATION NAME
023505	TEST (Mr test ot test)

TERM AND CONDITION DETAIL(S) - SPECIAL TERM(S)

SL. NO.	CATEGORY	DESCRIPTION
1	SPECIAL TERM(S)	SPECIAL TERM(S) GENERAL NOTE:PLEASE SUBMIT YOUR OFFER IN "TWO PART BID SYSTEM" AS PERTHE ANNEXURES ENCLOSED THROUGH E-TENDER ONLY. ENCLOSURES:ANNEXURE III,IV,V,VI,VII.OPENING OF TENDERS:The Part I - Technical & commercial bid alone would be opened on theTender opening date.The Part II - Price bid of technically suitable Bidders alone would beopened. The TechnicallySuitable Bidders would be informed about the tender opening date through e-mail.Clarifications if any required by BHEL for Technical evaluation would besought from Bidders before opening of Part II - price bid.For anyclarification the bidders may contact us through chells@bheltry.co.in , arunachal@bheltry.co.inSubmit your offer in E-Procurement website only www.bheleps.buyjunction.in. The bidder along with its associate/ collaborators/ sub-contractors/ sub-vendors/ consultants/ serviceproviders shall strictly adhere to BHEL fraud prevention policy displayed on BHEL website http://www.bhel.comand shall immediately bring to the notice of BHEL management about any fraud or suspected fraud as soon as itcomes to their notice.

RFQ/NIT ITEM DETAILS

SL. NO.	CODE	DESCRIPTION	QUANTITY	RFQ/NIT U.O.M	OFFER U.O.M
---------	------	-------------	----------	---------------	-------------



10	TPFD50042700	SOLID TYRE WITHOUT RIM- 26"X7"X12"(7.00 X 12 - 5)TYRE NOMINAL OD- 26",NOMINAL SECTION(MAX) WIDTH-7" , NOMINAL ID- 12",RIM WIDTH - 5"Conventional Solid tyre - 3 layer construction.Shore Hardness 68+/- 3(SUITABLE FOR VOLTAS DIESEL FORKLIFT FRONT TYRE DVX-30, 3 Ton CAPACITY)NOTE- The following general conditions are applicable for item nos. from10 to 160 of this indent.01.The tyres should be manufactured by rich natural rubber tread andsoft centre compound.02.The tyre should be used for superior ride comfort.03.The tyres should be HEAVY DUTY and have long operating life, lowrolling resistance and WIDE FOOT PRINT.04.APPLICATION : HARD APPLICATION.VENDOR QUALIFYING CRITERIA:Only those vendors who satisfy the following conditions will getqualified to participate in the tender:1. Vendor should have minimum 2 years of experience in this field.2. The vendor shall enclose company address and profile details alongwith the offer.3. Previous PO details for supplying Heavy Duty Solid or Cushion tyres,Press on Band tyres and Polyurethane tyres for materialhandling equipments to BHEL / any other organisation should be submittedalong with the offer,otherwise the offer shall be rejected.4. BHEL reserves the right to visit the vendor's works for verifying themanufacturing facilities and any other credential furnished by thevendor. In case the information furnished with the offers found to befalse /incorrect, the offer shall be rejected.SOLID TYRE WITHOUT RIM- 26"X7"X12"	08.00	NUMBER	NUMBER
	ATTRIBUTE DETAILS	ATTRIBUTE NAME	ATTRIBUTE VALUE		
		MATERIAL CODE:	TPFD50042700		
		MATERIAL GROUP:	75MECHSPR		
		KILOGRAM PER UNIT:	0.0		
		Cenvatable (Yes / No)	Yes		
		Delivery Location	TAMIL NADU		
		Vatable (Yes / No)	Yes		
		Delivery Date (i) :	08-DEC-2017		
		Delivery Qty (i) :	8		
20	TPFD50042600	SOLID TYRE WITHOUT RIM- 23"X6 1/2"X10" - 5"TYRE NOMINAL OD- 23" ,NOMINAL SECTION(MAX) WIDTH- 6.50" ,NOMINAL ID.- 10"RIM WIDTH - 5"Conventional Solid tyre - 3 layer construction.Shore Hardness 68+/-3(SUITABLE FOR VOLTAS DIESEL FORKLIFT REAR TYRE DVX-30, 3 Ton CAPACITY)SOLID TYRE WITHOUT RIM- 23"X6 1/2"X10"	07.00	NUMBER	NUMBER



	ATTRIBUTE DETAILS	ATTRIBUTE NAME		ATTRIBUTE VALUE	
		MATERIAL CODE:		TPFD50042600	
		MATERIAL GROUP:		75MECHSPR	
		KILOGRAM PER UNIT:		0.0	
		Cenvatable (Yes / No)		Yes	
		Delivery Location		TAMIL NADU	
		Vatable (Yes / No)		Yes	
		Delivery Date (i) :		08-DEC-2017	
		Delivery Qty (i) :		7	
30	TPFD50054000	SOLID PRESS ON TYRE WITH RIM 18"X9"X12 1/8"TYRE NOMINAL OD- 18"TYRE NOMINAL SECTION(MAX) WIDTH- 9"INTEGRATED RIM BORE ID - 12 1/8"RIM THICKNESS- 10 MMConventional Solid tyre - 3 layer construction.Shore Hardness 68+/- 3(SUITABLE FOR VOLTAS ELECTRIC EVX-30 FORKLIFT FRONT TYRE - 3 TONCAPACITY)SOLID PRESS ON TYRE WITH RIM 18"X9"X12 1	08.00	NUMBER	NUMBER
	ATTRIBUTE DETAILS	ATTRIBUTE NAME		ATTRIBUTE VALUE	
		MATERIAL CODE:		TPFD50054000	
		MATERIAL GROUP:		75MECHSPR	
		KILOGRAM PER UNIT:		0.0	
		Cenvatable (Yes / No)		Yes	
		Delivery Location		TAMIL NADU	
		Vatable (Yes / No)		Yes	
		Delivery Date (i) :		08-DEC-2017	
		Delivery Qty (i) :		8	
40	TPFD50054100	SOLID PRESS ON TYRE WITH RIM- 16 1/4"X6"X11 1/4"TYRE NOMINAL OD- 16 1/4"TYRE NOMINAL SECTION(MAX)WIDTH- 6"INTEGRATED RIM BORE ID- 11 1/4"RIM THICKNESS- 10 MMConventional Solid tyre - 3 layer construction.Shore Hardness 68+/-3(SUITABLE FOR VOLTAS ELECTRIC FORKLIFT EVX-30 REAR TYRE - 3 TONCAPACITY)SOLID TYRE-16 1/4" X 6 "X 11 1/4"	08.00	NUMBER	NUMBER
	ATTRIBUTE DETAILS	ATTRIBUTE NAME		ATTRIBUTE VALUE	
		MATERIAL CODE:		TPFD50054100	
		MATERIAL GROUP:		75MECHSPR	
		KILOGRAM PER UNIT:		0.0	
		Cenvatable (Yes / No)		Yes	
		Delivery Location		TAMIL NADU	
		Vatable (Yes / No)		Yes	
		Delivery Date (i) :		08-DEC-2017	
		Delivery Qty (i) :		8	
50	TPFD50061300	SOLID TYRE WITHOUT RIM- 28"X9"X15"TYRE NOMINAL OD- 28" , NOMINAL SECTION(MAX)WIDTH- 9" , NOMINAL ID- 15"RIM SIZE- 7.00WFB-15RIM TYPE- SINGLE DISC WITH LOCK (Similar to Bus and Lorry)ALL MEASUREMENTS - IN INCHESConventional Solid tyre - 3 layer construction.Shore Hardness 68+/- 3SUITABLE FOR ACE DIESEL FORKLIFT TRUCK FRONT TYRE - 3 TON CAPACITY.SOLID TYRE WITHOUT RIM- 28"X9"X15"	02.00	NUMBER	NUMBER
	ATTRIBUTE DETAILS	ATTRIBUTE NAME		ATTRIBUTE VALUE	
		MATERIAL CODE:		TPFD50061300	
		MATERIAL GROUP:		75MECHSPR	
		KILOGRAM PER UNIT:		0.0	
		Cenvatable (Yes / No)		Yes	
		Delivery Location		TAMIL NADU	
		Vatable (Yes / No)		Yes	
		Delivery Date (i) :		08-DEC-2017	
		Delivery Qty (i) :		2	



60	TPFD50061400	SOLID TYRE WITHOUT RIM- 21 1/8"x6.5"x10"TYRE NOMINAL OD-21 1/8",NOMINAL SECTION(MAX)WIDTH-6.5" ,NOMINAL ID-10"RIM SIZE 5.00ALL MEASUREMENTS - IN INCHESRIM TYPE-TWO PART SPLIT RIMConventional Solid tyre - 3 layer construction.Shore Hardness 68+/-3SUITABLE FOR ACE DIESEL FORKLIFT TRUCK REAR TYRE - 3 TON CAPACITY.SOLID TYRE WITHOUT RIM- 21 1/8"x6.5"x10"	02.00	NUMBER	NUMBER
ATTRIBUTE DETAILS		ATTRIBUTE NAME	ATTRIBUTE VALUE		
		MATERIAL CODE:	TPFD50061400		
		MATERIAL GROUP:	75MECHSPR		
		KILOGRAM PER UNIT:	0.0		
		Cenvatable (Yes / No)	Yes		
		Delivery Location	TAMIL NADU		
		Vatable (Yes / No)	Yes		
		Delivery Date (i) :	08-DEC-2017		
		Delivery Qty (i) :	2		
70	TPFL30065200	SOLID TYRE WITHOUT RIM 23"x7"x12"TYRE NOMINAL OD- 23" , NOMINAL SECTION(MAX)WIDTH- 7" , NOMINAL ID- 12"RIM SIZE- 5.00-12ALL MEASUREMENTS - IN INCHESRIM TYPE - TWO PART SPLIT RIMConventional Solid tyre - 3 layer construction.Shore Hardness 68+/-3(SUITABLE FOR ACE ELECTRIC FORKLIFT TRUCK FRONT TYRE - 3 TON CAPACITY)SOLID TYRE WITHOUT RIM 23"x7"x12"	02.00	NUMBER	NUMBER
ATTRIBUTE DETAILS		ATTRIBUTE NAME	ATTRIBUTE VALUE		
		MATERIAL CODE:	TPFL30065200		
		MATERIAL GROUP:	75MECHSPR		
		KILOGRAM PER UNIT:	0.0		
		Cenvatable (Yes / No)	Yes		
		Delivery Location	TAMIL NADU		
		Vatable (Yes / No)	Yes		
		Delivery Date (i) :	08-DEC-2017		
		Delivery Qty (i) :	2		
80	TPFL30065300	SOLID TYRE WITHOUT RIM 18"x7"x8"TYRE NOMINAL OD- 18" , NOMINAL SECTION(MAX)WIDTH- 7" ,NOMINAL ID- 8"RIM SIZE - 4.33R-8ALL MEASUREMENTS - IN INCHESRIM TYPE- TWO PART SPLIT RIMConventional Solid tyre - 3 layer construction.Shore Hardness 68+/-3(SUITABLE FOR ACE ELECTRIC FORKLIFT TRUCK REAR TYRE - 3 TON CAPACITY)SOLID TYRE WITHOUT RIM 18"x7"x8"	02.00	NUMBER	NUMBER
ATTRIBUTE DETAILS		ATTRIBUTE NAME	ATTRIBUTE VALUE		
		MATERIAL CODE:	TPFL30065300		
		MATERIAL GROUP:	75MECHSPR		
		KILOGRAM PER UNIT:	0.0		
		Cenvatable (Yes / No)	Yes		
		Delivery Location	TAMIL NADU		
		Vatable (Yes / No)	Yes		
		Delivery Date (i) :	08-DEC-2017		
		Delivery Qty (i) :	2		
90	TPFL30035600	SOLID PRESS ON TYRE WITH RIM - 22"x6"x16"TYRE NOMINAL OD- 22"NOMINAL SRCTION(MAX) WIDTH- 6"INTEGRATED RIM BORE ID- 16"RIM THICKNESS- 10 MMConventional Solid tyre - 3 layer construction.Shore Hardness 68+/-3(SUITABLE FOR MACNEILL ELECTRICAL FORKLIFT TRUCK FRONT TYRE)SOLID TYRE WITH RIM- 22"x6"x16"	08.00	NUMBER	NUMBER



	ATTRIBUTE DETAILS	ATTRIBUTE NAME		ATTRIBUTE VALUE	
		MATERIAL CODE:		TPFL30035600	
		MATERIAL GROUP:		75MECHSPR	
		KILOGRAM PER UNIT:		0.0	
		Cenvatable (Yes / No)		Yes	
		Delivery Location		TAMIL NADU	
		Vatable (Yes / No)		Yes	
		Delivery Date (i) :		08-DEC-2017	
Delivery Qty (i) :		8			
100	TPJS10026300	SOLID TYRE WITH 5 HOLES DISC-17 1/4"X5"X11 1/2"TYRE NOMINAL OD - 17 1/4"NOMINAL SECTION(MAX) WIDTH- 5"INTEGRATED DISC ID- 11 1/2"DISC THICKNESS - 10 MM , DISC BORE DIA. - 105 MM5 NOS. HOLES AND DIA. 15 MM,PCD- 140 MM.Conventional Solid tyre - 3 layer construction.Shore Hardness 68+/- 3(SUITABLE FOR JOST PLATFORM TRUCK -2 Ton)SOLID TYRE-5 HOLES DISC17 1/4"X5"X11 1/2"	08.00	NUMBER	NUMBER
	ATTRIBUTE DETAILS	ATTRIBUTE NAME		ATTRIBUTE VALUE	
		MATERIAL CODE:		TPJS10026300	
		MATERIAL GROUP:		75MECHSPR	
		KILOGRAM PER UNIT:		0.0	
		Cenvatable (Yes / No)		Yes	
		Delivery Location		TAMIL NADU	
		Vatable (Yes / No)		Yes	
		Delivery Date (i) :		08-DEC-2017	
Delivery Qty (i) :		8			
110	TPJS10018800	SOLID TYRE WITH DISC - 17 1/4"X5"X 11 1/4"TYRE NOMINAL OD- 17 1/4"NOMINAL SECTION(MAX) WIDTH- 5"INTEGRATED DISC ID - 11 1/4"DISC THICKNESS - 8 MMDISC BORE -95 MM , 6 HOLES- DIA. 22 MM AND PCD. - 140 MMConventional Solid tyre - 3 layer construction.Shore Hardness 68+/-3(SUITABLE FOR JOST PLATFORM TRUCK)SOLID TYRE WITH DISC - 17 1/4"X5"X 11 1/4"	08.00	NUMBER	NUMBER
	ATTRIBUTE DETAILS	ATTRIBUTE NAME		ATTRIBUTE VALUE	
		MATERIAL CODE:		TPJS10018800	
		MATERIAL GROUP:		75MECHSPR	
		KILOGRAM PER UNIT:		0.0	
		Cenvatable (Yes / No)		Yes	
		Delivery Location		TAMIL NADU	
		Vatable (Yes / No)		Yes	
		Delivery Date (i) :		08-DEC-2017	
Delivery Qty (i) :		8			
120	TPJL10016700	SOLID TYRE WITH DISC- 18"X6"X12 1/8"TYRE NOMINAL OD - 18"NOMINAL SECTION(MAX) WIDTH- 6"TYRE ID - 12 1/8"INTEGRATED DISC OD- 12 1/8"INTEGRATED DISC ID- 11 1/4"DISC THICKNESS - 11 MM ,DISC BORE - 4" , 6 NOS. HOLES- DIA. 22 MMAND PCD.- 140 MM.Conventional Solid tyre - 3 layer construction.Shore Hardness 68+/- 3(SUITABLE FOR JALDOOT PLATFORM TRUCK REAR TYRE)SOLID TYRE WITH DISC- 18"X6"X12 1/8"	08.00	NUMBER	NUMBER



	ATTRIBUTE DETAILS	ATTRIBUTE NAME		ATTRIBUTE VALUE	
		MATERIAL CODE:		TPJL10016700	
		MATERIAL GROUP:		75MECHSPR	
		KILOGRAM PER UNIT:		0.0	
		Cenvatable (Yes / No)		Yes	
		Delivery Location		TAMIL NADU	
		Vatable (Yes / No)		Yes	
		Delivery Date (i) :		08-DEC-2017	
		Delivery Qty (i) :		8	
130	TPTL10000900	SOLID TYRE WITH DISC - 535x380x150 (in mm)TYRE NOMINAL OD- 535 mmTYRE NOMINAL SECTION(MAX) WIDTH- 150 mmINTEGRATED DISC ID - 380 mmDISC THICKNESS - 10 MMDISC BORE - 110 MM , 6 Nos. HOLES- DIA. 20 MM AND PCD. - 150 MMConventional Solid tyre - 3 layer construction.Shore Hardness 68+/- 3(SUITABLE FOR MACNEILL TRANSLOADER 2120LX FRONT TYRE)SOLID TYRE WITH DISC - 535x380x150 (mm)		08.00	NUMBER
					NUMBER
	ATTRIBUTE DETAILS	ATTRIBUTE NAME		ATTRIBUTE VALUE	
		MATERIAL CODE:		TPTL10000900	
		MATERIAL GROUP:		75MECHSPR	
		KILOGRAM PER UNIT:		0.0	
		Cenvatable (Yes / No)		Yes	
		Delivery Location		TAMIL NADU	
		Vatable (Yes / No)		Yes	
		Delivery Date (i) :		08-DEC-2017	
		Delivery Qty (i) :		8	
140	TPTL10001000	SOLID TYRE WITH DISC - 535x350x150 (in mm)TYRE NOMINAL OD- 535 mmTYRE NOMINAL SECTION(MAX) WIDTH- 150 mmINTEGRATED DISC ID - 350 mmDISC THICKNESS - 10 MMDISC BORE - 130 MM , 8 Nos. HOLES- DIA. 20.5 MM AND PCD. - 163.5 MMConventional Solid tyre - 3 layer construction.Shore Hardness 68+/- 3(SUITABLE FOR MACNEILL TRANSLOADER 2120LX REAR TYRE)SOLID TYRE WITH DISC - 535x350x150 (mm)		08.00	NUMBER
					NUMBER
	ATTRIBUTE DETAILS	ATTRIBUTE NAME		ATTRIBUTE VALUE	
		MATERIAL CODE:		TPTL10001000	
		MATERIAL GROUP:		75MECHSPR	
		KILOGRAM PER UNIT:		0.0	
		Cenvatable (Yes / No)		Yes	
		Delivery Location		TAMIL NADU	
		Vatable (Yes / No)		Yes	
		Delivery Date (i) :		08-DEC-2017	
		Delivery Qty (i) :		8	
150	TPTL10001100	SOLID TYRE WITH DISC - 381x286x127 (in mm)TYRE NOMINAL OD- 381 mmTYRE NOMINAL SECTION(MAX) WIDTH- 127 mmINTEGRATED DISC ID - 286 mmDISC THICKNESS - 10 MMDISC BORE - 110 MM , 6 Nos. HOLES- DIA. 21 MM AND PCD. - 151 MMConventional Solid tyre - 3 layer construction.Shore Hardness 68+/- 3(SUITABLE FOR MACNEILL TRANSLOADER 2520EN FRONT TYRE)SOLID TYRE WITH DISC - 381X286X127 (MM)		08.00	NUMBER
					NUMBER



	ATTRIBUTE DETAILS	ATTRIBUTE NAME		ATTRIBUTE VALUE	
		MATERIAL CODE:		TPTL10001100	
		MATERIAL GROUP:		75MECHSPR	
		KILOGRAM PER UNIT:		0.0	
		Cenvatable (Yes / No)		Yes	
		Delivery Location		TAMIL NADU	
		Vatable (Yes / No)		Yes	
		Delivery Date (i) :		08-DEC-2017	
		Delivery Qty (i) :		8	
160	TPTL10001200	SOLID TYRE WITH DISC - 457x310x152 (in mm)TYRE NOMINAL OD- 457 mmTYRE NOMINAL SECTION(MAX) WIDTH- 152 mmINTEGRATED DISC ID - 310 mmDISC THICKNESS - 10 MMDISC BORE - 130 MM , 8 Nos. HOLES- DIA. 21 MM AND PCD. - 165 MMConventional Solid tyre - 3 layer construction.Shore Hardness 68+/- 3(SUITABLE FOR MACNEILL TRANSLOADER 2520EN REAR TYRE)SOLID TYRE WITH DISC - 457x310x152 (mm)		08.00	NUMBER
					NUMBER
	ATTRIBUTE DETAILS	ATTRIBUTE NAME		ATTRIBUTE VALUE	
		MATERIAL CODE:		TPTL10001200	
		MATERIAL GROUP:		75MECHSPR	
		KILOGRAM PER UNIT:		0.0	
		Cenvatable (Yes / No)		Yes	
		Delivery Location		TAMIL NADU	
		Vatable (Yes / No)		Yes	
		Delivery Date (i) :		08-DEC-2017	
		Delivery Qty (i) :		8	
170	TPFL20013900	POLYURETHENE TYRE WITH RIM- 22"X8"X16"RIM THICKNESS- 9.5 MM.(REAR TYRE FOR ELWELL PARKER-20Ton FORKLIFT TRUCK)Note:01. Tread pattern : Tyre should be smooth and designed with crownprofile.Tyre should NOT have any kind of buttons.02. Optimum PU Hardness: 90-95 Degree shore A.POLYURETHENE TYRE WITH RIM - 22"X8"X16"		03.00	NUMBER
					NUMBER
	ATTRIBUTE DETAILS	ATTRIBUTE NAME		ATTRIBUTE VALUE	
		MATERIAL CODE:		TPFL20013900	
		MATERIAL GROUP:		75MECHSPR	
		KILOGRAM PER UNIT:		0.0	
		Cenvatable (Yes / No)		Yes	
		Delivery Location		TAMIL NADU	
		Vatable (Yes / No)		Yes	
		Delivery Date (i) :		08-DEC-2017	
		Delivery Qty (i) :		3	

IMPORTANT NOTICE

PLEASE READ THE FOLLOWING ATTACHMENT(S)[SEPARATELY DOWNLOADABLE] ALONG WITH THIS RFQ/NIT/ENQUIRY .

RFQ/NIT/ENQUIRY - ATTACHMENTS

LABEL	FILE NAME
ANNEXURES EPS trichy stores	ANNEXURES EPS trichy stores.docx

