

TECHNICAL SPECIFICATIONS FOR BUTTERFLY VALVE ASSEMBLY SET – 30 TON FURNACE

S.No.	MATERIAL CODE	DESCRIPTION	QUANTITY	UNIT	BIDDERS SPECIFICATION AND REMARKS
01	IM8227450328	<p>BUTTERFLY VALVE ASSEMBLY SET-30T FURNACE ASSEMBLED SOLENOID OPERATED BUTTERFLY VALVE WITH LIMIT SWITCH CONSISTS OF U FLOW MAKE OR WITH EQUIVALENT SPECIFICATION IN ASSEMBLED CONDITION WITH READY TO USE CONDITION IN 30 TON CAPACITY FURNACE. (1) MICRO LIMIT SWITCH WEATHER PROOF (M20X1.5-3 Nos)(5AMP HONEYWELL)(1NO & 1NC), MODEL:GW11A. (2). 2-1/2" PNEUMATIC OPERATED WAFER TYPE BUTTERFLY VALVE WITH SINGLE ACTING ACTUATOR SIZE 80 WITH SPRING SET NO 222 AND COUPLER KIT DN50 BALL VALVE WITH AS80 (1755), MODEL : RIE98M1WI-AS80222 (C-1755). (3). 3X 2 NAMUR SINGLE SOLENOID PILOT OPERATED VALVE WITH SPRING RETURN WITH EPOXY SQUARE COIL 230V AC WITH PLUG (10 MM) 6W, MODEL : STA1R – MAG06S.</p>	4	NOS	

NOTE : BIDDER SHOULD SUBMIT THE DULY SIGNED AND SEALED COPY OF TECHNICAL SPECIFICATION AND PQR ALONG WITH OFFER FOR CONFIRMATION. BIDDER HAS TO SPECIFY THE OFFERED PRODUCT WITH MAKE AND MODEL.