

**3X1.5 SQ.MM FLEX.COPPER MULT.STRD CABLE**

SIZE : 3 x 1.5 SQ.MM

ISI marked, PVC insulated, Multistrand, flexible copper cable with electrolytic grade annealed copper. Suitable for Voltage upto and including 1100 Volts

Supplier shall duly fill the specification sheet attached for technical evaluation.

**3X2.5 SQ.MM FLEX.COPPER.MULTI.STRD CABLE**

SIZE : 3 x 2.5 SQ.MM

ISI marked, PVC insulated, Multistrand, flexible copper cable with electrolytic grade annealed copper. Suitable for Voltage upto and including 1100 Volts

Supplier shall duly fill the specification sheet attached for technical evaluation.

4 x 1.0 SQ.MM FLX.CU. MULTI STRAND CABLE

SIZE : 4 x 1.0 SQ.MM

ISI marked, PVC insulated, Multistrand, flexible copper cable with electrolytic grade annealed copper. Suitable for Voltage upto and including 1100 Volts

Supplier shall duly fill the specification sheet attached for technical evaluation.

**4x2.5 SQ.MM FLX.COPPR.MULT.STRAND CABLE**

SIZE : 4 x 2.5 SQ.MM

ISI marked, PVC insulated, Multistrand, flexible copper cable with electrolytic grade annealed copper. Suitable for Voltage upto and including 1100 Volts

Supplier shall duly fill the specification sheet attached for technical evaluation.

**4 X 6 SQ MM FLEX.COPPER MULT.STRD CABLE**

SIZE : 4 x 6.0 SQ.MM

ISI marked, PVC insulated, Multistrand, flexible copper cable with electrolytic grade annealed copper. Suitable for Voltage upto and including 1100 Volts

Supplier shall duly fill the specification sheet attached for technical evaluation.

4X10 SQ.MM FLEX.COPPER MULT.STRD CABLE

SIZE : 4 x 10.0 SQ.MM

ISI marked, PVC insulated, Multistrand, flexible copper cable with electrolytic grade annealed copper. Suitable for Voltage upto and including 1100 Volts

Supplier shall duly fill the specification sheet attached for technical evaluation.

**4X16SQ.MM FLEX.COPPER MULT.STRD CABLE**

SIZE : 4 x 16.0 SQ.MM

ISI marked, PVC insulated, Multistrand, flexible copper cable with electrolytic grade annealed copper. Suitable for Voltage upto and including 1100 Volts

Supplier shall duly fill the specification sheet attached for technical evaluation.

**4 X 25 SQ.MM FLEX.COPPER MULT.STRD CABLE**

SIZE : 4 x 25.0 SQ.MM

ISI marked, PVC insulated, Multistrand, flexible copper cable with electrolytic grade annealed copper. Suitable for Voltage upto and including 1100 Volts

Supplier shall duly fill the specification sheet attached for technical evaluation.