













MATERIAL CODE EL819010019	 EPD	1800-01 Rev. 00	PURCHASE SPECIFICATION FOR BATTERY OPERATED ELECTRIC PALLET TRUCK				ISSUE NO : 06																																																										
							DOC.NO: SPV-UT-008																																																										
			REV : 00		JUN 2019		Page 1 of 5																																																										
PURPOSE: Battery Operated Electrical Pallet Truck 3 T capacity will be used for handling of raw materials and finished products related to SPV 300 MW Module manufacturing plant. SCOPE: Scope involves supply and commissioning of Battery Operated Electric Pallet Truck of required parameters as detailed below : <table border="1"> <thead> <tr> <th>S/no</th> <th>Parameters</th> <th>Requirement of BHEL</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Battery operated Electric Pallet truck with capacity</td> <td>3 Ton at 500 mm load centre.</td> </tr> <tr> <td>2</td> <td>Model No</td> <td>Bidder to specify</td> </tr> <tr> <td>3</td> <td>Qty</td> <td>3 nos ✓</td> </tr> <tr> <td>4</td> <td>Drive Motor/Pump Rating in KW</td> <td>Bidder to indicate</td> </tr> <tr> <td>5</td> <td>Drive Type</td> <td>AC/DC</td> </tr> <tr> <td>6</td> <td>Total Length mm</td> <td>Bidder to specify.</td> </tr> <tr> <td>7</td> <td>Total Width mm</td> <td>850-900 mm</td> </tr> <tr> <td>8</td> <td>Turning radius mm</td> <td>Bidder to Indicate</td> </tr> <tr> <td>9</td> <td>Drive motor KW</td> <td>Bidder to indicate</td> </tr> <tr> <td>10</td> <td>Lifting motor kW</td> <td>Bidder to indicate</td> </tr> <tr> <td>11</td> <td>Travel speed km/h</td> <td>0-6</td> </tr> <tr> <td>12</td> <td>Lifting arrangement</td> <td>Shall be with lever /joystick operated attached to the Handle.</td> </tr> <tr> <td>13</td> <td>Lowering arrangement</td> <td>Shall be with lever /joystick operated attached to the Handle.</td> </tr> <tr> <td>14</td> <td>Battery</td> <td>24V</td> </tr> <tr> <td>15</td> <td>Battery Ampere Hour Rating</td> <td>250 to 350 AH</td> </tr> <tr> <td>16</td> <td>Fork Length</td> <td>NOT LESS THAN 2000mm</td> </tr> <tr> <td>17</td> <td>Range of lifting height of the fork with wheels</td> <td>100-250mm</td> </tr> <tr> <td>18</td> <td>Min height of the fork from ground level with wheels</td> <td>90 to 120mm</td> </tr> </tbody> </table>									S/no	Parameters	Requirement of BHEL	1	Battery operated Electric Pallet truck with capacity	3 Ton at 500 mm load centre.	2	Model No	Bidder to specify	3	Qty	3 nos ✓	4	Drive Motor/Pump Rating in KW	Bidder to indicate	5	Drive Type	AC/DC	6	Total Length mm	Bidder to specify.	7	Total Width mm	850-900 mm	8	Turning radius mm	Bidder to Indicate	9	Drive motor KW	Bidder to indicate	10	Lifting motor kW	Bidder to indicate	11	Travel speed km/h	0-6	12	Lifting arrangement	Shall be with lever /joystick operated attached to the Handle.	13	Lowering arrangement	Shall be with lever /joystick operated attached to the Handle.	14	Battery	24V	15	Battery Ampere Hour Rating	250 to 350 AH	16	Fork Length	NOT LESS THAN 2000mm	17	Range of lifting height of the fork with wheels	100-250mm	18	Min height of the fork from ground level with wheels	90 to 120mm
S/no	Parameters	Requirement of BHEL																																																															
1	Battery operated Electric Pallet truck with capacity	3 Ton at 500 mm load centre.																																																															
2	Model No	Bidder to specify																																																															
3	Qty	3 nos ✓																																																															
4	Drive Motor/Pump Rating in KW	Bidder to indicate																																																															
5	Drive Type	AC/DC																																																															
6	Total Length mm	Bidder to specify.																																																															
7	Total Width mm	850-900 mm																																																															
8	Turning radius mm	Bidder to Indicate																																																															
9	Drive motor KW	Bidder to indicate																																																															
10	Lifting motor kW	Bidder to indicate																																																															
11	Travel speed km/h	0-6																																																															
12	Lifting arrangement	Shall be with lever /joystick operated attached to the Handle.																																																															
13	Lowering arrangement	Shall be with lever /joystick operated attached to the Handle.																																																															
14	Battery	24V																																																															
15	Battery Ampere Hour Rating	250 to 350 AH																																																															
16	Fork Length	NOT LESS THAN 2000mm																																																															
17	Range of lifting height of the fork with wheels	100-250mm																																																															
18	Min height of the fork from ground level with wheels	90 to 120mm																																																															
COPY RIGHT AND CONFIDENTIAL The information on this document is the property of Bharat Heavy Electricals Limited. It must not be used directly or indirectly in anyway detrimental to the interest of the company.																																																																	
Rev.00:		Issued By	Prepared By	Checked By	Approved By	Date																																																											
1 st Issue		SPV PROD GROUP				28/06/19																																																											

MATERIAL CODE EL8619010019	 EPD	1800-01 Rev. 00	PURCHASE SPECIFICATION FOR BATTERY OPERATED ELECTRIC PALLET TRUCK				ISSUE NO : 06																																					
							DOC.NO: SPV-UT-008																																					
			REV : 00		JUN 2019		Page 2 of 5																																					
COPY RIGHT AND CONFIDENTIAL The information on this document is the property of Bharat Heavy Electricals Limited. It must not be used directly or indirectly in anyway detrimental to the interest of the company.		<table border="1"> <tr> <td>19</td> <td>Gap between two forks</td> <td>250 to 360mm</td> </tr> <tr> <td>20</td> <td>Maximum distance between two forks including fork width</td> <td>650-850 mm</td> </tr> <tr> <td>21</td> <td>Maximum width of the fork</td> <td>200 to 250 mm</td> </tr> <tr> <td>22</td> <td>Minimum sheet thickness of the fork</td> <td>NOT LESS THAN 8.0 mm</td> </tr> <tr> <td>23</td> <td>Minimum sheet thickness of the body</td> <td>NOT LESS THAN 4.0 mm</td> </tr> <tr> <td>24</td> <td>Net Weight</td> <td>Bidder to specify</td> </tr> <tr> <td>25</td> <td>Battery Charger kit I/P Voltage</td> <td>230V AC, 50 Hz</td> </tr> <tr> <td>26</td> <td>Minimum Continuous duty in fully charged condition</td> <td>4 hrs.</td> </tr> <tr> <td>27</td> <td>Safety</td> <td> a) Automatic lift cut off at 80% battery discharge condition. b) Emergency power cut-off switch on chassis panel. c) Anti-collision switch on tiller head. d) Hydraulic safety features like pressure relief valve and non-return valves. e) Toe guard at the rear. f) Pressure compensated for control. </td> </tr> <tr> <td>28</td> <td>Steering</td> <td> a) Easy steering without much effort. b) Steering lock at 90 deg on either side to operate in limited range handle inclinations comfortable to operator. </td> </tr> <tr> <td>29</td> <td>Handle</td> <td>Low hinged for greater maneuverability.</td> </tr> <tr> <td>30</td> <td>Tiller Head</td> <td>Multifunction tiller head with ergonomically arranged operating elements for travel, lift, lowering and horn at fingertips for higher operator comfort and safety</td> </tr> </table>							19	Gap between two forks	250 to 360mm	20	Maximum distance between two forks including fork width	650-850 mm	21	Maximum width of the fork	200 to 250 mm	22	Minimum sheet thickness of the fork	NOT LESS THAN 8.0 mm	23	Minimum sheet thickness of the body	NOT LESS THAN 4.0 mm	24	Net Weight	Bidder to specify	25	Battery Charger kit I/P Voltage	230V AC, 50 Hz	26	Minimum Continuous duty in fully charged condition	4 hrs.	27	Safety	a) Automatic lift cut off at 80% battery discharge condition. b) Emergency power cut-off switch on chassis panel. c) Anti-collision switch on tiller head. d) Hydraulic safety features like pressure relief valve and non-return valves. e) Toe guard at the rear. f) Pressure compensated for control.	28	Steering	a) Easy steering without much effort. b) Steering lock at 90 deg on either side to operate in limited range handle inclinations comfortable to operator.	29	Handle	Low hinged for greater maneuverability.	30	Tiller Head	Multifunction tiller head with ergonomically arranged operating elements for travel, lift, lowering and horn at fingertips for higher operator comfort and safety
		19	Gap between two forks	250 to 360mm																																								
		20	Maximum distance between two forks including fork width	650-850 mm																																								
		21	Maximum width of the fork	200 to 250 mm																																								
		22	Minimum sheet thickness of the fork	NOT LESS THAN 8.0 mm																																								
		23	Minimum sheet thickness of the body	NOT LESS THAN 4.0 mm																																								
		24	Net Weight	Bidder to specify																																								
		25	Battery Charger kit I/P Voltage	230V AC, 50 Hz																																								
		26	Minimum Continuous duty in fully charged condition	4 hrs.																																								
		27	Safety	a) Automatic lift cut off at 80% battery discharge condition. b) Emergency power cut-off switch on chassis panel. c) Anti-collision switch on tiller head. d) Hydraulic safety features like pressure relief valve and non-return valves. e) Toe guard at the rear. f) Pressure compensated for control.																																								
		28	Steering	a) Easy steering without much effort. b) Steering lock at 90 deg on either side to operate in limited range handle inclinations comfortable to operator.																																								
		29	Handle	Low hinged for greater maneuverability.																																								
		30	Tiller Head	Multifunction tiller head with ergonomically arranged operating elements for travel, lift, lowering and horn at fingertips for higher operator comfort and safety																																								
		Rev.00:	Issued By	Prepared By	Checked By	Approved By	Date																																					
1 st Issue	SPV PROD GROUP				28/06/19																																							

MATERIAL CODE EL8119010019	 EPD	1800-01 Rev. 00	PURCHASE SPECIFICATION FOR BATTERY OPERATED ELECTRIC PALLET TRUCK				ISSUE NO : 06																																																												
							DOC.NO: SPV-UT-008																																																												
			REV : 00		JUN 2019		Page 3 of 5																																																												
COPY RIGHT AND CONFIDENTIAL The information on this document is the property of Bharat Heavy Electricals Limited. It must not be used directly or indirectly in anyway detrimental to the interest of the company.		<table border="1"> <tr> <td>31</td> <td>Hydraulic system</td> <td colspan="5"> a) Compact power pack unit with high pressure pump driven by sturdy motor. b) Lifting mechanism comprising of low lift hydraulic cylinder and load wheel linkages. </td> </tr> <tr> <td>32</td> <td>Brake</td> <td colspan="5"> a) Electromagnetic disc brake with hard wearing asbestos free liner. b) When the handle is close to vertical or horizontal position, the brake should become operational with simultaneous power cutoff. </td> </tr> <tr> <td>33</td> <td>Forks</td> <td colspan="5"> a) Robust steel fabricated forks to ensure long lasting and durable service. b) The fork end shall be suitably tapered to provide better maneuverability. </td> </tr> <tr> <td>34</td> <td>Chassis</td> <td colspan="5"> a) Robust construction with suitable design for stability during turning b) Swivel side support wheels to provide stability during travel and for safe maneuverability. c) Shall have suitable roller bed for easy removal of batteries. </td> </tr> <tr> <td>35</td> <td>Drive wheels</td> <td colspan="5"> Drive wheel materials shall be Polyurethane. </td> </tr> <tr> <td rowspan="3">36</td> <td rowspan="3">Load test</td> <td colspan="5"> Bidders to provide the facility of full load test at their works </td> </tr> <tr> <td colspan="5"> Transit Insurance shall be in the scope of Supplier. </td> </tr> <tr> <td colspan="5"> Unloading of equipment shall be in the scope of BHEL. </td> </tr> <tr> <td colspan="5"></td> <td colspan="2"> Training for Operation & maintenance should be provided to BHEL personnel during commissioning. </td> </tr> </table>							31	Hydraulic system	a) Compact power pack unit with high pressure pump driven by sturdy motor. b) Lifting mechanism comprising of low lift hydraulic cylinder and load wheel linkages.					32	Brake	a) Electromagnetic disc brake with hard wearing asbestos free liner. b) When the handle is close to vertical or horizontal position, the brake should become operational with simultaneous power cutoff.					33	Forks	a) Robust steel fabricated forks to ensure long lasting and durable service. b) The fork end shall be suitably tapered to provide better maneuverability.					34	Chassis	a) Robust construction with suitable design for stability during turning b) Swivel side support wheels to provide stability during travel and for safe maneuverability. c) Shall have suitable roller bed for easy removal of batteries.					35	Drive wheels	Drive wheel materials shall be Polyurethane.					36	Load test	Bidders to provide the facility of full load test at their works					Transit Insurance shall be in the scope of Supplier.					Unloading of equipment shall be in the scope of BHEL.										Training for Operation & maintenance should be provided to BHEL personnel during commissioning.	
		31	Hydraulic system	a) Compact power pack unit with high pressure pump driven by sturdy motor. b) Lifting mechanism comprising of low lift hydraulic cylinder and load wheel linkages.																																																															
		32	Brake	a) Electromagnetic disc brake with hard wearing asbestos free liner. b) When the handle is close to vertical or horizontal position, the brake should become operational with simultaneous power cutoff.																																																															
		33	Forks	a) Robust steel fabricated forks to ensure long lasting and durable service. b) The fork end shall be suitably tapered to provide better maneuverability.																																																															
		34	Chassis	a) Robust construction with suitable design for stability during turning b) Swivel side support wheels to provide stability during travel and for safe maneuverability. c) Shall have suitable roller bed for easy removal of batteries.																																																															
		35	Drive wheels	Drive wheel materials shall be Polyurethane.																																																															
		36	Load test	Bidders to provide the facility of full load test at their works																																																															
				Transit Insurance shall be in the scope of Supplier.																																																															
Unloading of equipment shall be in the scope of BHEL.																																																																			
					Training for Operation & maintenance should be provided to BHEL personnel during commissioning.																																																														
Rev.00:	Issued By	Prepared By	Checked By	Approved By	Date																																																														
1 st Issue	SPV PROD GROUP				28/06/19																																																														

MATERIAL CODE EL819010019	 EPD 1800-01 Rev. 00	PURCHASE SPECIFICATION FOR BATTERY OPERATED ELECTRIC PALLET TRUCK				ISSUE NO : 06							
						DOC.NO: SPV-UT-008							
		REV : 00		JUN 2019		Page 4 of 5							
COPY RIGHT AND CONFIDENTIAL The information on this document is the property of Bharat Heavy Electricals Limited. It must not be used directly or indirectly in anyway detrimental to the interest of the company.								37	Pre dispatch Inspection	Pre dispatch inspection shall be carried out at Supplier's works by BHEL engineer. Supplier has to inform well in advance (7 days) about the readiness of material for inspection. Supplier has to make all arrangement for inspection within the quoted rate.			
								38	Documents required along with dispatch:	(a) Load test certificates, (b) 2 sets of O&M manual, Integrated list of Spare parts & their catalogue and all hydraulic & electrical schematic drawings (c) Guarantee Certificate – Minimum 12 month from the date of commissioning or 18 months From date of dispatch of at site whichever is early.			
								39	AFTER SALES SERVICE	Reliable after sales service should be available. Vendor to provide necessary details			
								Sl no	BHEL Standard Terms & Conditions	Documents to be submitted by vendor / Remarks			
								01	Bidder should be original equipment manufacturer (OEM) of the quoted item. Bidder to submit company credentials to prove as OEM. Authorized dealer can also submit offer.	Registration certificate as a manufacturer or any other document to establish bidder as manufacturer. Incase of dealer, current valid authorization certificate from OEM is to be submitted.			
								02	Bidder should have manufactured, supplied and successfully commissioned minimum of 10 numbers of BOEP truck or more in the last 3 years.	Bidder to submit copy of purchase orders and performance certificates from the users.			
								03	BHEL preserves the right for independent verification of the reference provided.	Accepted / Not accepted			
								04	Offer shall be for new equipment and not For any refurbished or used equipment	YES / NO			
								05	Bid shall be kept valid for a period of 60 days starting from the date of opening of Techno-commercial bid.	YES / NO			
								Rev.00:	Issued By	Prepared By	Checked By	Approved By	Date
								1 st Issue	SPV PROD GROUP	 	 	 	28/06/19

MATERIAL CODE EL8119010019	 EPD		1800-01 Rev. 00		PURCHASE SPECIFICATION FOR BATTERY OPERATED ELECTRIC PALLET TRUCK		ISSUE NO : 06 DOC.NO: SPV-UT-008 REV : 00 JUN 2019 Page 5 of 5	
	<u>SPECIFICATION REVIEWED AND APPROVED</u>							
COPY RIGHT AND CONFIDENTIAL The information on this document is the property of Bharat Heavy Electricals Limited. It must not be used directly or indirectly in anyway detrimental to the interest of the company.	NAME		SIGNATURE					
	AMAR JYOTI SARKIA							
	RAVI-Y							
	S. ARUNACHALAM							
	MOHAN J							
	P. K. SINGH							
	C. N. PURUSHOTHAM							
Rev 00:	Issued By	Prepared By	Checked By	Approved By	Date			
1 st Issue	SPV PROD GROUP				28/6/19			

Ref: PR No. 5000323
Date: 02.07.201

Sl No.	Item / Description	Unit	Quantity	Rate	Amount	Remarks
1	Battery operated Pallet Truck - 3000kg	Each	3			The BOPT as per Purchase Specification No. SPV-JT-008 Complete inclusive of the following units / components and not limited to: a. Main machine unit b. Additional / Associated equipment : Other accessories as required.
2	Installation and Commissioning of the Line at BHEL - EPD	Set	3			
3	Training of BHEL Staff on Operation and Maintenance					
4	Technical Documentation and other associated information					