

ANNEXURE-1 to Specification PY51390 R01

Sl. No.	Description of Nozzle with K factor and discharge angle
1	HVW Spray nozzle
1.1	SPRAY NOZZLE- K-18 * 80 Deg
1.1	SPRAY NOZZLE- K-23 * 120 Deg
1.1	SPRAY NOZZLE- K-26 * 100 Deg
1.2	SPRAY NOZZLE- K-42* 115 Deg
2	MVW Spray nozzle
2.1	SPRAY NOZZLE- K-18 * 120 Deg
2.2	SPRAY NOZZLE- K-18 * 140 Deg
2.3	SPRAY NOZZLE- K 22 * 120 Deg
2.4	SPRAY NOZZLE- K 22 * 140 Deg
2.5	SPRAY NOZZLE- K41 * 120 Deg
2.6	SPRAY NOZZLE- K41 * 140 Deg
2.7	SPRAY NOZZLE- K51 * 120 Deg
2.8	SPRAY NOZZLE- K51 * 140 Deg
2.9	SPRAY NOZZLE- K-64 * 120 Deg
2.10	SPRAY NOZZLE- K-64 * 140 Deg
2.11	SPRAY NOZZLE- K-79 * 120 Deg
2.12	SPRAY NOZZLE- K-79 * 140 Deg
2.13	SPRAY NOZZLE- K-91 * 120 Deg
2.14	SPRAY NOZZLE- K-91 * 140 Deg

Note: Actual K factor and discharge angle shall be confirmed during post order & bidder to comply the same.