



TYP. CROSS SECTION OF MAIN APPROACH ROAD (DOUBLE LANE ROADS)

(SCALE NTS)

FOR TENDER PURPOSE ONLY

REFERENCE DRAWING:

- PY-DZ-0-M088-1260-01 : LAYOUT OF ROADS
- PY-DZ-0-M088-1260-02 : LAYOUT OF DRAINS
- ARRAY LAYOUTS FOR 40MW & 25 MW BLOCKS

GENERAL NOTES

- ALL DIMENSIONS ARE IN MM AND ELEVATIONS IN METER UNO.
- EL(+)0.00 CORRESPONDS TO FGL & T.O. ROAD SHALL BE (+)0.10 AS SHOWN.
- LATRITE SOLING SHALL BE IN TWO LAYERS, EACH OF 150MM PRE-CONSOLIDATED THICK-ROLLED TO 115 MM THK. EACH LAYER SHALL BE BLINDED WITH GRAVEL WITH 1/3 QUANTITY OF LATRITE.
- WBM SHALL BE USING 40MM BG METAL IN TWO LAYERS, EACH OF 135 THK PRE-CONSOLIDATED- ROLLED TO 100THK. THIS INCLUDES DRY & WET ROLLING OF EACH LAYER, SPREADING GRAVEL FOR BLINDAGE & CONSOLIDATION WITH WATER.

PROJECT : 65MW SOLAR POWER PLANT

CUSTOMER:  NEYVELI LIGNITE CORPORATION LTD.
NEYVELI-TAMILNADU

		BHARAT HEAVY ELECTRICALS LTD.		UNIT : HYDERABAD		NAME		SIGN.	DATE	NO.OF VAR.
						DRN.	PVG	—sd—	22.09.16	
						CHD.	SRK	—sd—	23.09.16	
						APPD.	EC	—sd—	24.09.16	
DEPT. PE&SD	UNTOL. DIMS. GR. Q/M/F		SCALE	WEIGHT (KG)	REF. TO ASSY. DRG.	ITEM NO.	NO.OF ITEMS			
CODE 450				N.A.	N.A.	N.A.				
TITLE TYP. C/S OF ROADS & DRAINS FOR MAIN APPROACH ROAD				CARD CODE NA	BHEL DRG NO. PY-DZ-3-M088-1260-01			REV. 00		
					SHT. No	02	NO. OF SHT.	02		