

**TECHNICAL SPECIFICATIONS FOR PORTABLE WATER MIST FIRE EXTINGUISHER AS PER
IS15683 (COMPLIES WITH NFPA 750)**

REF PR NO: 50003251

Sl. No.	PRODUCT DESCRIPTION
01.	✓ 2 LITERS CAPACITY FIRE EXTINGUISHER ✓ Water / Foam Mist Technology. (Non-Toxic, Bio-Degradable, DM Water) ✓ Portable, Hand Held Fighting Extinguisher ✓ Working Pressure : 15Bar ✓ Special Alloy Steel ✓ Internal PU Coated and External Powder coated, corrosion protection. ✓ Jet nozzle : <u>12 – Feet Lancing Distance</u> ✓ Squeeze Trigger operated ✓ Squeeze Trigger – Insulated ✓ Wall Mounded Clamps ✓ Fire Class : A, B, LPG Gas Fires ✓ Live Electrical Fire 1000Volts (test certificate must) ✓ Warranty : One year (Manufacturing Defects)
02.	✓ 4 LITERS CAPACITY FIRE EXTINGUISHER ✓ Water / Foam Mist Technology. (Non-Toxic, Bio-Degradable, DM Water) ✓ Portable, Hand Held Fighting Extinguisher ✓ Working Pressure : 15Bar ✓ Special Alloy Steel ✓ Internal PU Coated and External Powder coated, corrosion protection. ✓ Jet nozzle : <u>18 – Feet Lancing Distance</u> ✓ Squeeze Trigger operated ✓ Squeeze Trigger – Insulated ✓ Wall Mounted Clamps ✓ Fire Class : A, B, LPG Gas Fires ✓ Live Electrical Fire 1000Volts (test certificate must) ✓ Warranty : One year (Manufacturing Defects)
03.	✓ 6 LITERS CAPACITY FIRE EXTINGUISHER ✓ Water / Foam Mist Technology (Non-Toxic, Bio-Degradable, DM Water) ✓ Portable, Hand Held Fighting Extinguisher ✓ Working Pressure : 15Bar ✓ Special Alloy Steel ✓ Internal PU Coated and External Powder coated, corrosion protection. ✓ Jet nozzle : <u>18 – Feet Lancing Distance</u> ✓ Squeeze Trigger operated ✓ Squeeze Trigger – Insulated ✓ Wall Mounted Clamps ✓ Fire Class : A, B, LPG Gas Fires ✓ Live Electrical Fire 1000Volts (test certificate must) ✓ Warranty : One year (Manufacturing Defects)



K S SRINIVASA
DY SECURITY OFFICER / FIRE

ಕೆ.ಎಸ್. ಶ್ರೀನಿವಾಸ, ಉಪ ಭದ್ರತಾ ಅಧಿಕಾರಿ/ಮಾಹಿತಿ
ಕೆ.ಎಸ್. ಶ್ರೀನಿವಾಸ, ಉಪ ಭದ್ರತಾ ಅಧಿಕಾರಿ/ಮಾಹಿತಿ
K.S. SRINIVASA, Deputy Security Officer/HRM
BHEL - EPD, BENGALURU-560 012

TECHNICAL SPECIFICATION FOR HYDRANT

WALL MOUNTED HOSE REEL

Ref PR No: 50003251

- Hose reel drum shall be fabricated from 16 SWG CRCA sheets.
- Powder Coated / Painted with red color enameled paint.
- The Hose Reel shall be swinging type (180 degrees) and the entire Drum, Reel etc. Hose: Nominal bore high pressure, 30 meter long rubber hose with 36 kg/sq.cm bursting pressure 20mm dia., and the rubber tubing shall be of approved quality.
- The nozzle shall be 6 mm diameter shut off type.
- Hose reel shall conform to IS: 884.



K S SRINIVASA

DY. SECURITY OFFICER/ FIRE

ಕೆ.ಎಸ್. ಶ್ರೀನಿವಾಸ, ಉಪ ಭದ್ರತಾ ಅಧಿಕಾರಿ/ಮಾಸಂ
के एस श्रीनिवास, उप सुरक्षा अधिकारी/मासंम
K.S. SRINIVASA, Deputy Security Officer/HRM
BHEL - EPD, BENGALURU-560 012

TECHNICAL SPECIFICATION FOR PORTABLE MEGAPHONE

Ref PR NO: 50003251

Specifications of Portable Megaphone:-

- ♦ 20 WATTS.
- ♦ Shoulder Sling type.
- ♦ Dry Cell & 12V Car Battery operation.
- ♦ All ABS Body, Sturdy Yet Lightweight.
- ♦ Built-in Siren.
- ♦ Clear Sound, Long Range & Efficient Design.
- ♦ Microphone with Volume Control & Press-to-Talk Switch.
- ♦ Warranty 1 year.



K S SRINIVASA

DY. SECURITY OFFICER/FIRE
ಕೆ.ಎಸ್. ಶ್ರೀನಿವಾಸ, ಉಪ ನಿರ್ದೇಶಕ ಅಧಿಕಾರಿ/ಮಾಸಂ
के एस श्रीनिवास, उप निरक्षी अधिकारी/मासंम
K.S. SRINIVASA, Deputy Security Officer/HRM
BHEL - EPD, BENGALURU-560 012