




Zurrpunkt ZA-3
LASHING POINT ZA-3
max.Load 150kN



MAX. ALLOWED TRANSPORTATION ACCELERATION



POSITION OF SUPPORTS
CONSIDER SUFFICIENT SIZE
OF CONTACT AREA
Position Abstellböcke
ausreichend Auflagefläche
berücksichtigen

ALWAYS USE ANTI SKID PADS BELOW FRAME
FRICTION FACTOR $\mu \geq 0,6$
Antirutschmatten unter Auflagefläche
benutzen $\mu \geq 0,6$

*
DIMENSIONS CAN VARIATE UP TO 50mm BECAUSE OF
INACCURACY WHILE LOADING AND PACKING
Maße können bis zu 50mm variieren aufgrund von
Ungenauigkeiten beim Verladen und Verpacken

PACKING AND DISPATCH GUIDELINES ACC. TO TLV 0130
Versand- und Verpackungsrichtlinie nach TLV 0130

NETWEIGHT : 175 Mg
GROSSWEIGHT: 180 MG

TECHNOLOGY NOT SPECIFIED IN THE CCL, AL OR BCL			
TECHNICAL CLASSIFICATION: ECCN:EAR99 ALIN ECLIN US-Content:			
THIS DOCUMENT IS SUBJECT TO US AND/OR NATIONAL EXPORT REGULATIONS. UNAUTHORIZED DIVERSION IS PROHIBITED. IN CASES OF DOUBT CONTACT YOUR EXPORT COMPLIANCE DEPARTMENT.			
REVISION: SEE SEPARATE CID DOCUMENT			
Siemens AG Energy Sector			
WEIGHT:	SCALE: 1:1	SPEC: KUN 35100 DCC:	
ORIGINATED: 2013-04-04 Hoppe	TITLE: Transportzeichnung Turbine shipping dwg turbine		
CHECKED: 2013-04-04 Asbeck			
RELEASED: 2013-04-04 Hoppe			
COPYRIGHT (C) Siemens AG 2010 ALL RIGHTS RESERVED	LANG.-DRAWING NO. / VALUE DPPPG-70029363 12680-MA10100010		REV: S A 1
21	AutoCAD		