
REQUEST FOR QUOTATION



BHARAT HEAVY ELECTRICALS LIMITED
Electronics Division
PB No. 2606, Mysore Road Bangalore - 560026
INDIA

RFQ NUMBER: AKSPROP052

RFQ DATE: 04.09.2023



MMI:PU:RF:003

(address for communication):

(for all correspondence)

Purchase Executive : ABHISHEK

Phone : 26998102 Fax : 00918026989215 E-mail: singh.abhishek@bhel.in

1)This RFQ is for entering into Rate contract (RC) with BHEL for the tendered item. Validity of the RC will be 1 year from the award of rate contract. Firm orders will be placed during the tenure of rate contract. Prices will remain firm till the validity of RC or till the completion of supplies against the Purchase Orders placed against this rate contract whichever is later. Please note that these quantities are projections based on the current business scenario and expected orders from customers. In the eventuality of business not coming through, BHEL is not obligated to exhaust the ordering of RC quantities.

2)Reverse Auction Clause: BHEL shall be resorting to Reverse Auction (RA) (Guidelines as available on www.bhel.com) for this tender. RA shall be conducted among all the techno-commercially qualified bidders. Price bids of all techno-commercially qualified bidders shall be opened and same shall be considered as initial bids of bidders in RA. In case any bidder(s) do(es) not participate in online Reverse Auction, their sealed envelope price bid along with applicable loading, if any, shall be considered for ranking.

Sl No.	Description	Qty	Unit	Delivery qty	Delivery Date
1	TI0668103531 HIGH VOLTAGE INDICATOR 48-4300VAC/DC * HSN/SAC : 3921	750	NO	750	
	HIGH VOLTAGE INDICATOR 48-4300VAC/DC, CABLE 2.35 MT as per Specification No: PS4452541 rev 00,				

Total Number of Items -	1		

1. 2.

2.

NOTES:

- 1. This RFQ is governed by:
- a) INSTRUCTIONS TO BIDDERS/SELLERS and GENERAL CONDITIONS OF CONTRACT FOR PURCHASE available at http://edn.bhel.com (RFQ-PO Terms & Conditions)
- b) Any other specific Terms and Conditions mentioned.

* The HSN/SAC no mentioned against the line items in the RFQ are indicative only.

For and On behalf of BHEL.

ABHISHEK Control Equipment

1 OF 1



The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in anyway detrimental to the interest of the company.

COPYRIGHT AND CONFIDENTIAL

PREQUALIFICATION CRITERIA (PQC) FOR HIGH VOLTAGE INDICATOR

GROUP: TRACTION ENGINEERING

Ref: 445/PQC_HVI/22

Rev. No.: 01

Page 1 of 1

1.0 PRE QUALIFICATION CRITERIA (PQC)

- 1. The Bidder should be Supplier of High Voltage indicators for rolling stock applications.
- 2. BHEL shall approach and submit credentials/details furnished by vendor with their offers to customer and await customer's decision for a maximum of one month from the date of tender opening. If approval is not received within the above period, BHEL shall treat the offer as "Not meeting" Pre-qualification criteria and offer shall be rejected.
- 3. It is preferred that the bidder is the manufacturer of this item. If the bidder is importing some portion of the components, then minimum value addition shall be 20%. Bidder to confirm this in the offer. Value addition less than 20% is not acceptable.

2.0 DOCUMENTS SUBMISSION

- 1. Bidder to submit clause by clause compliance to complete technical specification (Technical specification no. PS4452541 Rev. No.00, dated 21.12.2015) along with copy of type test report.
- 2. Should possess a valid type test report, not older than five years, conducted at a NABL accredited laboratory or equivalent as per relevant standards mentioned in the specification with respect to time during the bid submission.
- 3. Proof of supply of High voltage indicators or higher rating indicators used in traction applications directly or through any agency to Indian Railways during the last 5 years to be submitted.
- 4. For the vendors already qualified and added in the source list, the above points (point no. 2 & 3) are not applicable.

3.0 REFERENCE DOCUMENTS

a) Purchase Specification No PS4452541, Rev. No. 00 for High Voltage Indicator.

	REVISION 01	APPROVED AGOSH CHANDRAN R S
	See a constitution of the	PREPARED ISSUED DATE L SUNITHA HOTO TRACTION ENGG 01.09.2022

	ची ए !	पडणा क्रिक	PURCHASE SP	ECIFICATION		P.S NO.		452541	
	A4 – 12		GROUP: TRACTIO	P: TRACTION ENGINEERING —			REV. NO: 00 		
		SPEC	IFICATION FOR HIG	H VOLTAGE	INDI				
					Code I	No. TI	0668103	3531	
MITED. pany.			REVISION HIST	TORY SHEET					
TRICALS LI t of the com	REV. NO.	DATE	NATURE OF CHANGE	REASONS	PRE	PARED BY	API	PROVED	BY
It must not be used directly or indirectly in anyway detrimental to the interest of the company.	00	21.12.201	5 FIRST ISSUE		B. Ha	aribhushan		Shekar	R.

REVISIONS

00

APPROVED BY

PREPARED BY

ISSUED BY

TRACTION ENGG.

DATE

21.12.2015

	भारत हे एन BHEL		PURCHASE	SPECIFICATION	N	P.S NO. REV. NO:	: PS4452541
	A4 – 10	G	ROUP: TRAC	TION ENGINEER	RING	PAGE	02 OF 06
CALS LIMITED. the company.	1.0 Functional This docum converter. T	requirement covers so the indicato ounting. The	nts:	igh voltage indicator, to a cabinet/enclosure are shown below.	be used at the desired will be used Loac	ne DC link o	
COPYRIGHT AND CONFIDENTIAL on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. e used directly or indirectly in anyway detrimental to the interest of the company.	2.0 APPLICAT 3.0 TYPE			DC link Object of this secification connect across DC link ge presence in traction exposing	ets		
The information on this docum It must not be used directly	IEC 60571 IEC 62498-1		Railway applicati Railway applicati	ons – Electronic equipn ons – Environmental co t on board rolling stock	onditions for		
Th							

ISSUED BY

TRACTION ENGG.

DATE

21.12.2015

PREPARED BY



A4 - 11

PURCHASE SPECIFICATION

GROUP: TRACTION ENGINEERING

P.S NO. : PS4452541

REV. NO: 00

PAGE 03 OF 06

SPECIFICATION FOR HIGH VOLTAGE INDICATOR 5.0 ENVIRONMENTAL CONDITIONS:

5.1 Ambient Temperature

: 55°C

5.2 Maximum Temperature

: 70°C (when locomotive standing dead under sun)

55°C (when locomotive working)

47°CNominal

5.3 Relative Humidity

: Up to 95% relative humidity, any moisture condensation during operation

shall not lead any damage or failure

Yearly average < 75% Relative Humidity

5.4 Altitude

The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in anyway detrimental to the interest of the company.

COPYRIGHT AND CONFIDENTIAL

: Up to 1200 m above mean sea level

5.5 Atmosphere during hot weather: Extremely dusty and desert terrain in certain areas. The dust concentration

in air may reach a high value of 1.6mg/cub meter.

5.6 Air Pollution

: The equipment shall be designed to work in coastal area in humidity and

salt laden corrosive atmosphere. The maximum values will be as

follows

(a) Maximum pH Value: 8.5 (b)

Sulphate: 7mg/litre

(c) Maximum concentrate of chlorine:6mg/liter (d) Maximum conductivity:230µSiemens/m

5.7 Climate : Tropical, Hot and humid Climate

6.0 ELECTRICAL REQUIREMENTS

6.1 Input voltage range

: 40 V to 4000 V DC or 40 V_{rms} to 4000 V_{rms}

6.2 Flashing frequency at 1 – 4 kV 6.3 Input current

: 2Hz +/- 10% : < 5mA

6.4 Operating temperature

: -50° C to $+70^{\circ}$ C

REVISIONS

00

APPROVED BY

PREPARED BY

Hoist tust

ISSUED BY

DATE

TRACTION ENGG.

21.12.2015



A4 - 11

The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in anyway detrimental to the interest of the company.

COPYRIGHT AND CONFIDENTIAL

PURCHASE SPECIFICATION

GROUP: TRACTION ENGINEERING

P.S NO. : PS4452541

REV. NO: 00

PAGE 04 OF 06

SPECIFICATION FOR HIGH VOLTAGE INDICATOR

7.0 CONSTRUCTION

7.1 Housing:


The PCB should be encapsulated in an housing made of Polyamide 6 with Glass reinforced material confirming to flame class V-0, as per the mechanical dimensions specified


7.2 Termination:


Termination should be done with electron beam irradiated cable of 3.6 kV class with 2.35 meter cable length (ex. Huber+Suhner AG Radox 9 GKW-AX)

8.0 MECHANICAL DIMENSION LIMITATION

The High voltage indicator dimensions (overall & mounting) shall not exceed the dimensions indicated in the below sketch. This sketch is given for guidance only for limiting dimensions







Supplier to prepare detailed drawing & submit to BHEL for approval before commencing manufacturing process

PREPARED BY ISSUED BY DATE
TRACTION ENGG. 21.12.2015



A4 – 11

PURCHASE SPECIFICATION

GROUP: TRACTION ENGINEERING

P.S NO. : PS4452541

REV. NO: 00

PAGE 05 OF 06

SPECIFICATION FOR HIGH VOLTAGE INDICATOR

9.0 TESTS TO BE CONDUCTED AT SUPPLIER'S WORKSPACE

High Voltage Indicator				
Name of the test	Type test	Routine test		
Visual Inspection	Yes	Yes		
Performance test	Yes	Yes		
Hot operation test	Yes	No		
Dielectric test	Yes	Yes		
Electrical endurance test	Yes	No		

9.1 Visual Inspection

Check of dimensions as per drawing.

9.2 Performance test

The Visual LED Indicator shall be checked at the minimum and maximum rated voltages (AC & DC) and the frequency of flashes noted to be within the specified limits.

9.3 Hot operation test

The test 9.2 shall be repeated at the maximum ambient temperature.

9.4 Dielectric test

The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in anyway detrimental to the interest of the company.

COPYRIGHT AND CONFIDENTIAL

A test voltage of 2 kV rms at power frequency for 1 minute shall be applied between the input terminals shorted and earth.

9.5 Electrical endurance test

The Visual LED Indicator shall be subject to the maximum rated voltage and kept on for 168 hours and test 9.2 shall be repeated at the end

10.0 TEST PROTOCOL

Supplier shall submit test protocol for Routine & Type tests along with techno-commercial offer. List of tests are as per clause 5.0 of this specification.

REVISIONS	00	APPROVED BY					
		PREPARED BY	ISSUED BY TRACTION ENGG.	DATE 21.12.2015			



A4 – 11

PURCHASE SPECIFICATION

GROUP: TRACTION ENGINEERING

P.S NO. : PS4452541 REV. NO: 00

PAGE 06 OF 06

SPECIFICATION FOR HIGH VOLTAGE INDICATOR 11.0 DOCUMENTATION

- 11.1 Information required along with techno commercial offer without which offer is liable for rejection.
- 11.2 Supplier shall furnish clause wise confirmation/comments to the technical specification in the typical format given below. Deviation, if any, shall be clearly brought out indicating the clause number, original specification, deviation sought with proper technical backup (catalogue, technical brochure, international standards, calculations etc. If no deviations required, then supplier shall furnish certificate indicating "NO DEVIATION REQUESTED" and we comply fully with all the technical requirements of this specification no.
- 11.3 Supplier shall take a copy of this specification and sign on each page and submit the signed copy along with offer.
- 11.4 Supplier shall furnish winding material, winding resistance, winding cross section.
- 11.5 Supplier shall furnish the type of core used along with technical details of core.
- 11.6 Information required after the placement of order
- 11.7 Detailed dimensional drawing for BHEL approval
- 11.8 Test protocol for BHEL approval.
- 11.9 Information required along with material supply.
- 11.10 Two sets of Test certificates.
- 11.11 BHEL engineer witnessed Pre inspection report.

12.0 ACCEPTANCE

The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in anyway detrimental to the interest of the company.

COPYRIGHT AND CONFIDENTIAL

- 12.1 Dimensions as per approved drawing
- 12.2 Routine test certificate
- 12.3 Type test certificate

13.0 PRE-SHIPMENT INSPECTION

Pre-shipment inspection will be carried out by BHEL engineer as per the approved test protocol. BHEL engineers will witness Routine & Type tests before dispatch.

14.0 RATING PLATE DETAILS

- 14.1 BHEL Specification No.
- 14.2 Input voltage range
- 14.3 Serial number
- 14.4 Month & Year of Manufacture
- 14.5 Manufacturer Name

REVISIONS	00	APPROVED BY	_
		P. Gran	
		PREPARED BY ISSUED BY DATE TRACTION ENGG 21.12.2015	
		Hairhurle TRACTION ENGG 21.12.2015	