

TD-201 Rev No. 00	Form No.		PRODUCT STANDARD PROJECT ENGINEERING & SYSTEMS DIVISION, HYDERABAD		PY55294 Rev No. 00 Page 1 of 15
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED, It must not be used directly or indirectly in any way detrimental to the interest of the company. TECHNICAL SPECIFICATION FOR 33kV GAS INSULATED SWITCHGEAR PROJECT 75MW VISAKH REFINERY MODERNIZATION PROJECT (VRMP) CUSTOMER M/S HINDUSTAN PETROLEUM CORPORATION LIMITED,VIZAG,A.P CONSULTANT ENGINEERS INDIA LIMITED					
Ref. Doc	Revisions Refer to record of revisions	Prepared  G.MONICA/ A.V.SURESH	Checked  P.SURESH	Approved  J.K.PATTANAIAK	Date 16-05-2018

TD-201 Rev No. 00 Form No.		PRODUCT STANDARD PROJECT ENGINEERING & SYSTEMS DIVISION, HYDERABAD	PY55294																																																																																			
			Rev No. 00																																																																																			
			Page 2 of 15																																																																																			
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.	TABLE OF CONTENTS <table border="1"> <thead> <tr> <th>Sl. No.</th> <th>Description</th> </tr> </thead> <tbody> <tr><td>1.0</td><td>Intent of Specification</td></tr> <tr><td>2.0</td><td>Site Conditions</td></tr> <tr><td>3.0</td><td>Scope of Work</td></tr> <tr><td>4.0</td><td>Codes and Standards</td></tr> <tr><td>5.0</td><td>Order of Priority</td></tr> <tr><td>6.0</td><td>General Requirements</td></tr> <tr><td>7.0</td><td>Technical Requirements</td></tr> <tr><td>8.0</td><td>Inspection, Testing and Acceptance</td></tr> <tr><td>9.0</td><td>Documentation</td></tr> <tr><td>10.0</td><td>Guarantee</td></tr> <tr><td>11.0</td><td>Quality Plan</td></tr> <tr><td>12.0</td><td>Packing and Dispatch</td></tr> <tr><td>13.0</td><td>Special Conditions</td></tr> <tr><td>14.0</td><td>Check List for Bid Submission</td></tr> <tr><td>15.0</td><td>List of Material codes as per enquiry</td></tr> </tbody> </table> LIST OF ANNEXURES <table border="1"> <thead> <tr> <th>Sl. No.</th> <th>Annexure</th> <th>Description</th> </tr> </thead> <tbody> <tr><td>1</td><td>Annexure-1A</td><td>Standard Specification for HV Gas Insulated Switchboards</td></tr> <tr><td>2</td><td>Annexure-1B</td><td>Standard Specification for Numerical Relays</td></tr> <tr><td>3</td><td>Annexure-1C</td><td>Data Sheet for HV Gas Insulated Switchgear</td></tr> <tr><td>4</td><td>Annexure-2A</td><td>Reference Schematics</td></tr> <tr><td>5</td><td>Annexure-2B</td><td>Electrical Control Philosophy</td></tr> <tr><td>6</td><td>Annexure-3</td><td>Switchboard SLD</td></tr> <tr><td>7</td><td>Annexure-4</td><td>I/O Signals List</td></tr> <tr><td>8</td><td>Annexure-5</td><td>Sub-vendor List</td></tr> <tr><td>9</td><td>Annexure-6</td><td>Feeder List</td></tr> <tr><td>10</td><td>Annexure-7</td><td>Deviation Format</td></tr> <tr><td>11</td><td>Annexure-8</td><td>Inspection Test Requirements</td></tr> <tr><td>12</td><td>Annexure-9</td><td>Price Format</td></tr> <tr><td>13</td><td>Annexure-10</td><td>Package Execution Milestones/ Schedule</td></tr> <tr><td>14</td><td>Annexure-11</td><td>List of Spares and Tools & Tackles</td></tr> <tr><td>15</td><td>Annexure-12</td><td>Documents to be submitted after award of contract</td></tr> <tr><td>16</td><td>Annexure-13</td><td>Check List for Bid Submission</td></tr> </tbody> </table>			Sl. No.	Description	1.0	Intent of Specification	2.0	Site Conditions	3.0	Scope of Work	4.0	Codes and Standards	5.0	Order of Priority	6.0	General Requirements	7.0	Technical Requirements	8.0	Inspection, Testing and Acceptance	9.0	Documentation	10.0	Guarantee	11.0	Quality Plan	12.0	Packing and Dispatch	13.0	Special Conditions	14.0	Check List for Bid Submission	15.0	List of Material codes as per enquiry	Sl. No.	Annexure	Description	1	Annexure-1A	Standard Specification for HV Gas Insulated Switchboards	2	Annexure-1B	Standard Specification for Numerical Relays	3	Annexure-1C	Data Sheet for HV Gas Insulated Switchgear	4	Annexure-2A	Reference Schematics	5	Annexure-2B	Electrical Control Philosophy	6	Annexure-3	Switchboard SLD	7	Annexure-4	I/O Signals List	8	Annexure-5	Sub-vendor List	9	Annexure-6	Feeder List	10	Annexure-7	Deviation Format	11	Annexure-8	Inspection Test Requirements	12	Annexure-9	Price Format	13	Annexure-10	Package Execution Milestones/ Schedule	14	Annexure-11	List of Spares and Tools & Tackles	15	Annexure-12	Documents to be submitted after award of contract	16	Annexure-13	Check List for Bid Submission
	Sl. No.	Description																																																																																				
1.0	Intent of Specification																																																																																					
2.0	Site Conditions																																																																																					
3.0	Scope of Work																																																																																					
4.0	Codes and Standards																																																																																					
5.0	Order of Priority																																																																																					
6.0	General Requirements																																																																																					
7.0	Technical Requirements																																																																																					
8.0	Inspection, Testing and Acceptance																																																																																					
9.0	Documentation																																																																																					
10.0	Guarantee																																																																																					
11.0	Quality Plan																																																																																					
12.0	Packing and Dispatch																																																																																					
13.0	Special Conditions																																																																																					
14.0	Check List for Bid Submission																																																																																					
15.0	List of Material codes as per enquiry																																																																																					
Sl. No.	Annexure	Description																																																																																				
1	Annexure-1A	Standard Specification for HV Gas Insulated Switchboards																																																																																				
2	Annexure-1B	Standard Specification for Numerical Relays																																																																																				
3	Annexure-1C	Data Sheet for HV Gas Insulated Switchgear																																																																																				
4	Annexure-2A	Reference Schematics																																																																																				
5	Annexure-2B	Electrical Control Philosophy																																																																																				
6	Annexure-3	Switchboard SLD																																																																																				
7	Annexure-4	I/O Signals List																																																																																				
8	Annexure-5	Sub-vendor List																																																																																				
9	Annexure-6	Feeder List																																																																																				
10	Annexure-7	Deviation Format																																																																																				
11	Annexure-8	Inspection Test Requirements																																																																																				
12	Annexure-9	Price Format																																																																																				
13	Annexure-10	Package Execution Milestones/ Schedule																																																																																				
14	Annexure-11	List of Spares and Tools & Tackles																																																																																				
15	Annexure-12	Documents to be submitted after award of contract																																																																																				
16	Annexure-13	Check List for Bid Submission																																																																																				
Ref. Doc																																																																																						

TD-201 Rev No. 00	Form No.		PRODUCT STANDARD PROJECT ENGINEERING & SYSTEMS DIVISION, HYDERABAD	PY55294 Rev No. 00 Page 3 of 15																												
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.	1.0 INTENT OF SPECIFICATION This specification covers the design, manufacture, assembly and testing at manufacturer's works; packing and transportation to site; supervision of erection, testing and commissioning of 33kV Gas Insulated Switchgear and Substation Automation System complete with all accessories for efficient and trouble-free operation. It is not the intent to specify completely herein all details of the equipment; nevertheless, the equipment shall be complete and operative in all respects and shall confirm to the highest standard of engineering, design and workmanship. 2.0 SITE CONDITIONS <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">Sl. No.</th> <th style="width: 45%;">Description</th> <th style="width: 45%;">Data</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Project</td> <td>75MW Visakh Refinery Modernization Project (VRMP), HPCL Vizag, A.P</td> </tr> <tr> <td>2</td> <td>Site Location</td> <td>Visakhapatnam , Andhra Pradesh</td> </tr> <tr> <td>3</td> <td>Elevation Above MSL</td> <td>Less than 5.56m above Mean Sea Level</td> </tr> <tr> <td>4</td> <td>Maximum Ambient Temperature</td> <td>45°C</td> </tr> <tr> <td>5</td> <td>Minimum Ambient Temperature</td> <td>12.5°C</td> </tr> <tr> <td>6</td> <td>Design Ambient Temperature</td> <td>45°C</td> </tr> <tr> <td>7</td> <td>Site Environment</td> <td>Humid, Highly Corrosive</td> </tr> <tr> <td>8</td> <td>Relative Humidity</td> <td>95%</td> </tr> <tr> <td>9</td> <td>Seismic Zone</td> <td>Zone-III as per IS-1893 Part-1</td> </tr> </tbody> </table> 3.0 SCOPE OF WORK 3.1 33kV GIS Switchgear 3.1.1 Supply of 33kV GIS Switchboard as per enquiry specification. 3.1.2 Supply of Cable termination accessories such as plug in type/Termination kits on GIS end for Incoming cable termination, Cable Glands for HT (if applicable), Cable glands for LT Power cables, lugs for LT, Control and signal cables etc. at 33kV GIS end. 3.1.3 Supply of all commissioning spares required during testing & commissioning shall be in the scope of 33kV GIS vendor. As per Annexure-11 3.1.5 Supply of special tools and tackles as per Annexure-11 3.1.6 Supply of feeder Differential relay, CTs and Differential cable (FO cable/Pilot wire as applicable). The above shall be supplied for both 33kV GIS end as per SLD and customer's 33kV SWGR-270 end by 33kV GIS vendor. 3.1.7 Supply of feeder Transformer cum Differential relay and CTs. The above shall be supplied for 33kV GIS end as per 33kV SLD. On customer side only CTs (11kV level) shall be supplied as loose by 33kV GIS vendor and same will be installed (By others) in customer's 11kV board (SWGR-200). Control cable as required from 33kV GIS to SWGR-200 shall be supplied by BHEL. 3.1.8 Feeder differential relay (P543) in outgoing feeder meant for 71-HV-111 in 33kV GIS SLD will be free issued to 33kV GIS vendor. Further installation and integration in relay network of 33kV GIS by vendor. However, relays for other protections as per SLD is 33kV GIS vendor. 3.1.9 For above 3.1.6 to 3.1.8 distance (for cable) between 33kV GIS and customer switchgear 400Mtrs shall be considered.	Sl. No.	Description	Data	1	Project	75MW Visakh Refinery Modernization Project (VRMP), HPCL Vizag, A.P	2	Site Location	Visakhapatnam , Andhra Pradesh	3	Elevation Above MSL	Less than 5.56m above Mean Sea Level	4	Maximum Ambient Temperature	45°C	5	Minimum Ambient Temperature	12.5°C	6	Design Ambient Temperature	45°C	7	Site Environment	Humid, Highly Corrosive	8	Relative Humidity	95%	9	Seismic Zone	Zone-III as per IS-1893 Part-1	Ref. Doc
Sl. No.	Description	Data																														
1	Project	75MW Visakh Refinery Modernization Project (VRMP), HPCL Vizag, A.P																														
2	Site Location	Visakhapatnam , Andhra Pradesh																														
3	Elevation Above MSL	Less than 5.56m above Mean Sea Level																														
4	Maximum Ambient Temperature	45°C																														
5	Minimum Ambient Temperature	12.5°C																														
6	Design Ambient Temperature	45°C																														
7	Site Environment	Humid, Highly Corrosive																														
8	Relative Humidity	95%																														
9	Seismic Zone	Zone-III as per IS-1893 Part-1																														

TD-201 Rev No. 00	Form No.	 	PRODUCT STANDARD PROJECT ENGINEERING & SYSTEMS DIVISION, HYDERABAD	PY55294 Rev No. 00 Page 4 of 15															
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.	3.2 Supply of Substation Automation System (SAS) a) Complete software and Hardware required for substation automation system such as Redundant Data concentrators for Generator relays, 66kV GIS, 33kV GIS, 11kV Switchgear, Generator Transformers, Grid/Power Transformers, 415V LT switchgear, DC system, UPS, VFD, & Solar roof top etc. with required desktop HMI's, Laptops with software, GPS, FO/Cu cables, UPS, printer and provision for hook-up of electrical control, monitoring and status signals to ECS system & DCS system and other systems as per specification requirements. b) The Dual Redundant data concentrators shall be complete with desktop 2 nos operator stations, 1 no engineering station along with managed ethernet switches including complete computer furniture such as PC and printer table, chairs, GPS for all EHV, HV & MV switchboards, Generator Relays. c) 2 nos Laptop with required software, hardware, accessories and material shall be supplied. System configuration shall be latest proven model and upgradeable. Laptop and HMI PC shall be of the latest configuration and processor as available at the time of purchase subject to approval by BHEL/HPCL. d) Dedicated UPS (2x100%) with UPS Rack trolley for above systems. e) Complete cables such as FO cables outside the HSR red box and FO/CAT6 cables for looping of relays. These cables shall be laid in HDPE duct and same shall be supplied along with cables. Complete accessories required for FO cables/CAT6 cables along LIU/Hub shall be supplied vendor. All the cables FO & Cu shall be armoured type. f) 2 No. Laser Jet-colour A3, A4 printer (1 for HMI & 1 extra) shall be provided configured for line-by-line printing. g) Any other accessories which are not specified here but required for completing SAS system package shall be taken care of vendor. h) Following are minimum Godrej/Pyrotech furniture shall be supplied by vendor. <table border="1" style="margin: 20px auto; width: 60%; text-align: center;"> <thead> <tr> <th>S.No</th> <th>Hardware</th> <th>Quantity</th> </tr> </thead> <tbody> <tr> <td>1.</td> <td>HMI PC Tables</td> <td>3 sets</td> </tr> <tr> <td>2.</td> <td>Laser jet A3 Printer table</td> <td>2 sets</td> </tr> <tr> <td>3.</td> <td>Laptop Tables</td> <td>2 nos.+ 2 nos. extra</td> </tr> <tr> <td>4.</td> <td>Revolving officers chairs</td> <td>7 sets</td> </tr> <tr> <td>5.</td> <td>UPS Rack trolley</td> <td>2 sets</td> </tr> </tbody> </table> 3.3 Services 3.3.1 Supervision of Erection/Installation of 33kV GIS including Substation Automation system. 3.3.2 Complete Testing and Commissioning of 33kV GIS at site by Bidder. For 33kV GIS testing and commissioning, following works to be completed as bare minimum at site i) SF6 Gas filling j) Control voltage and polarity check k) Spring charging Motor checks l) Breaker checks m) Disconnect & Earth Switch checks. n) Position Indicator checks o) Mechanical Interlocking checks p) Busbar conductivity measurement test	S.No	Hardware	Quantity	1.	HMI PC Tables	3 sets	2.	Laser jet A3 Printer table	2 sets	3.	Laptop Tables	2 nos.+ 2 nos. extra	4.	Revolving officers chairs	7 sets	5.	UPS Rack trolley	2 sets
	S.No	Hardware	Quantity																
1.	HMI PC Tables	3 sets																	
2.	Laser jet A3 Printer table	2 sets																	
3.	Laptop Tables	2 nos.+ 2 nos. extra																	
4.	Revolving officers chairs	7 sets																	
5.	UPS Rack trolley	2 sets																	
Ref. Doc																			

TD-201 Rev No. 00		Form No.		PRODUCT STANDARD PROJECT ENGINEERING & SYSTEMS DIVISION, HYDERABAD	PY55294 Rev No. 00 Page 6 of 15																																																								
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.			<table><tr><th>Standard</th><th>Description</th></tr><tr><td>IS: 1248</td><td>Direct acting indicating analogue electrical measuring instruments and their accessories</td></tr><tr><td>IS: 2071</td><td>High Voltage Test Technique</td></tr><tr><td>IS: 2705</td><td>Current transformers</td></tr><tr><td>IS: 3156</td><td>Voltage transformers</td></tr><tr><td>IS: 5082</td><td>Material data for aluminium bus bars</td></tr><tr><td>IS: 5578</td><td>Guide for marking of insulated conductors</td></tr><tr><td>IS: 9920</td><td>Switches and switch isolators for voltages above 1000 V</td></tr><tr><td>IS: 9921</td><td>AC disconnectors (isolators) and earthing switches for voltage above 1000V</td></tr><tr><td>IS: 11353</td><td>Guide for uniform system of marking and identification of conductors & apparatus terminals</td></tr><tr><td>IS: 12729</td><td>Common high voltage switchgear and control gear standard</td></tr><tr><td>IS: 13118</td><td>General requirements for circuit breakers for voltages above 1000 V</td></tr><tr><td>IS: 13703</td><td>Low voltage fuses for voltages not exceeding 1000V AC or 1500V DC.</td></tr><tr><td>IEC 60059</td><td>IEC Standard Current Rating</td></tr><tr><td>IEC 60060</td><td>High voltage test techniques</td></tr><tr><td>IEC 60099-4</td><td>Metal - Oxide surge arresters without gaps for a.c. systems</td></tr><tr><td>IEC 60114</td><td>Recommendation for heat treated al alloy bus bar material of al. Magnesium —silicon type.</td></tr><tr><td>IEC 60137</td><td>Bushings for alternating voltages above 1000 V</td></tr><tr><td>IEC 60255</td><td>Electrical Relays</td></tr><tr><td>IEC 60270</td><td>High voltage test techniques - Partial discharge measurement</td></tr><tr><td>IEC 60376</td><td>Specification of technical grade sulphur hexafluoride (SF6) for use in electrical equipment</td></tr><tr><td>IEC 60480</td><td>Guidelines for the checking and treatment of sulphur hexafluoride (SF6) taken from electrical equipment and specification for its re-use</td></tr><tr><td>IEC 60529</td><td>Degrees of protection provided by enclosures (IP Code)</td></tr><tr><td>IEC 60694</td><td>Common specification for high voltage switchgear and control gear standards</td></tr><tr><td>IEC 61243-1</td><td>Live working - Voltage detectors — capacitive type to be used for voltages exceeding 1 kV a.c.</td></tr><tr><td>IEC 61869-1</td><td>Instrument transformers/General requirements</td></tr><tr><td>IEC 61869-2</td><td>Additional requirements for current transformers</td></tr><tr><td>IEC 61869-3</td><td>Additional requirements for inductive voltage transformers</td></tr></table>			Standard	Description	IS: 1248	Direct acting indicating analogue electrical measuring instruments and their accessories	IS: 2071	High Voltage Test Technique	IS: 2705	Current transformers	IS: 3156	Voltage transformers	IS: 5082	Material data for aluminium bus bars	IS: 5578	Guide for marking of insulated conductors	IS: 9920	Switches and switch isolators for voltages above 1000 V	IS: 9921	AC disconnectors (isolators) and earthing switches for voltage above 1000V	IS: 11353	Guide for uniform system of marking and identification of conductors & apparatus terminals	IS: 12729	Common high voltage switchgear and control gear standard	IS: 13118	General requirements for circuit breakers for voltages above 1000 V	IS: 13703	Low voltage fuses for voltages not exceeding 1000V AC or 1500V DC.	IEC 60059	IEC Standard Current Rating	IEC 60060	High voltage test techniques	IEC 60099-4	Metal - Oxide surge arresters without gaps for a.c. systems	IEC 60114	Recommendation for heat treated al alloy bus bar material of al. Magnesium —silicon type.	IEC 60137	Bushings for alternating voltages above 1000 V	IEC 60255	Electrical Relays	IEC 60270	High voltage test techniques - Partial discharge measurement	IEC 60376	Specification of technical grade sulphur hexafluoride (SF6) for use in electrical equipment	IEC 60480	Guidelines for the checking and treatment of sulphur hexafluoride (SF6) taken from electrical equipment and specification for its re-use	IEC 60529	Degrees of protection provided by enclosures (IP Code)	IEC 60694	Common specification for high voltage switchgear and control gear standards	IEC 61243-1	Live working - Voltage detectors — capacitive type to be used for voltages exceeding 1 kV a.c.	IEC 61869-1	Instrument transformers/General requirements	IEC 61869-2	Additional requirements for current transformers	IEC 61869-3	Additional requirements for inductive voltage transformers
			Standard	Description																																																									
IS: 1248	Direct acting indicating analogue electrical measuring instruments and their accessories																																																												
IS: 2071	High Voltage Test Technique																																																												
IS: 2705	Current transformers																																																												
IS: 3156	Voltage transformers																																																												
IS: 5082	Material data for aluminium bus bars																																																												
IS: 5578	Guide for marking of insulated conductors																																																												
IS: 9920	Switches and switch isolators for voltages above 1000 V																																																												
IS: 9921	AC disconnectors (isolators) and earthing switches for voltage above 1000V																																																												
IS: 11353	Guide for uniform system of marking and identification of conductors & apparatus terminals																																																												
IS: 12729	Common high voltage switchgear and control gear standard																																																												
IS: 13118	General requirements for circuit breakers for voltages above 1000 V																																																												
IS: 13703	Low voltage fuses for voltages not exceeding 1000V AC or 1500V DC.																																																												
IEC 60059	IEC Standard Current Rating																																																												
IEC 60060	High voltage test techniques																																																												
IEC 60099-4	Metal - Oxide surge arresters without gaps for a.c. systems																																																												
IEC 60114	Recommendation for heat treated al alloy bus bar material of al. Magnesium —silicon type.																																																												
IEC 60137	Bushings for alternating voltages above 1000 V																																																												
IEC 60255	Electrical Relays																																																												
IEC 60270	High voltage test techniques - Partial discharge measurement																																																												
IEC 60376	Specification of technical grade sulphur hexafluoride (SF6) for use in electrical equipment																																																												
IEC 60480	Guidelines for the checking and treatment of sulphur hexafluoride (SF6) taken from electrical equipment and specification for its re-use																																																												
IEC 60529	Degrees of protection provided by enclosures (IP Code)																																																												
IEC 60694	Common specification for high voltage switchgear and control gear standards																																																												
IEC 61243-1	Live working - Voltage detectors — capacitive type to be used for voltages exceeding 1 kV a.c.																																																												
IEC 61869-1	Instrument transformers/General requirements																																																												
IEC 61869-2	Additional requirements for current transformers																																																												
IEC 61869-3	Additional requirements for inductive voltage transformers																																																												
Ref. Doc																																																													

TD-201 Rev No. 00	Form No.		PRODUCT STANDARD PROJECT ENGINEERING & SYSTEMS DIVISION, HYDERABAD	PY55294 Rev No. 00 Page 7 of 15										
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.		<table border="1" data-bbox="414 231 1323 651"> <tr> <td>IEC 62271- 4</td> <td>Handling procedures for sulphur hexafluoride (SF6) and its mixtures</td> </tr> <tr> <td>IEC 62271-100</td> <td>High voltage alternating current circuit breakers</td> </tr> <tr> <td>IEC 62271-102</td> <td>Alternating current disconnectors (isolators) and earthing switches</td> </tr> <tr> <td>IEC 62271-110</td> <td>High voltage switchgear and controlgear - Inductive load switching</td> </tr> <tr> <td>IEC 62271-200</td> <td>AC metal-enclosed switchgear & control gear for rated voltages Above 1 kV and up to and including 52 kV</td> </tr> <tr> <td>IEEE 80</td> <td>IEEE Guide for safety in AC substation grounding</td> </tr> </table> 4.2 In case of imported equipments, Standards of the country of origin shall be applicable if these standards are equivalent or stringent than the applicable Indian Standards. 4.3 The equipment shall also confirm to the provisions of Indian Electricity Rules and other statutory regulations currently in force in the country. 4.4 In case Indian Standards are not available for any equipment, Standards issued by the IEC/ BS/ VDE/ IEEE/ NEMA or equivalent agency shall be applicable. 5.0 ORDER OF PRIORITY 5.1 In case of any contradictions between various referred Standards/ Specifications/ Data Sheets/ Statutory Regulations/ enclosed annexures, the following sequence shall be followed as order of priority. In case of conflict between requirements specified in various documents, the more stringent one shall be followed. 1. Statutory Regulations 2. This specification: (i) PY55294 (ii) Standard Specification of HT Gas Insulated Switchboards (Annexure-1A) / Standard Specification of Numerical relays & SAS (Annexure-1B) (iii) Feeder List (Annexure-6) (Refer Notes below) (iv) Switchboard SLDs (Annexure-3) (Refer Notes below) (v) Other Annexures 3. Codes and Standards Note: For metering, protection and fitments, details as provided in Switchboard SLDs and PY55294 , Annexure-1A&1B have to be followed. 5.2 In case of further contradiction among above documents, it is bidder's responsibility to highlight the same during bid stage itself. Else, BHEL's decision shall be final during execution. The same shall be complied without any time / cost implication to BHEL. 6.0 GENERAL REQUIREMENTS 6.1 The offered equipment shall be brand new with state of art technology and proven field track record. No prototype equipment shall be offered.	IEC 62271- 4	Handling procedures for sulphur hexafluoride (SF6) and its mixtures	IEC 62271-100	High voltage alternating current circuit breakers	IEC 62271-102	Alternating current disconnectors (isolators) and earthing switches	IEC 62271-110	High voltage switchgear and controlgear - Inductive load switching	IEC 62271-200	AC metal-enclosed switchgear & control gear for rated voltages Above 1 kV and up to and including 52 kV	IEEE 80	IEEE Guide for safety in AC substation grounding
		IEC 62271- 4	Handling procedures for sulphur hexafluoride (SF6) and its mixtures											
		IEC 62271-100	High voltage alternating current circuit breakers											
IEC 62271-102	Alternating current disconnectors (isolators) and earthing switches													
IEC 62271-110	High voltage switchgear and controlgear - Inductive load switching													
IEC 62271-200	AC metal-enclosed switchgear & control gear for rated voltages Above 1 kV and up to and including 52 kV													
IEEE 80	IEEE Guide for safety in AC substation grounding													
Ref. Doc														

TD-201 Rev No. 00	Form No.		PRODUCT STANDARD PROJECT ENGINEERING & SYSTEMS DIVISION, HYDERABAD		PY55294																										
					Rev No. 00																										
					Page 8 of 15																										
6.2 Vendor shall ensure availability of spare parts and maintenance support services for the offered equipment at least for 15 years from the date of supply. 6.3 Vendor shall give a notice of at least one year to the end user of equipment and BHEL before phasing out the product/ spares to enable the end user for placement of order for spares and services. 6.4 In case of relays manufactured outside India, the Relay manufacturer through their Indian establishment or associate in India shall provide application, testing, commissioning, after sales service and other necessary support for minimum of 15 years to customer. Their Indian establishment or associate company in India shall also maintain adequate inventory of each type of relay or spares to meet the requirement arising during project execution and plant operation. Relay manufacturer shall possess a signed MOU with their Indian associate for providing customer support. 6.5 Only major relays, meters and controls are indicated in the Switchboard SLDs. Any auxiliary relays, timers, switches, contactors, contacts, indications etc. as required while developing the control schematics or felt necessary for safe operation, even if these are not specifically mentioned, shall be supplied without any time and price implications. 7.0 TECHNICAL REQUIREMENTS 7.1 Operating Conditions <table><tr><th>Sl. No.</th><th>Description</th><th>Data</th></tr><tr><td>1</td><td>Voltage</td><td>As specified in Switchboard SLD (with voltage variation +10% to -10%)</td></tr><tr><td>2</td><td>Number of Phases & Wires</td><td>3-phase, 3-wire</td></tr><tr><td>3</td><td>Frequency</td><td>50Hz $\pm$ 3%</td></tr><tr><td>4</td><td>Switchboard Fault Level</td><td>40kA for 1 sec.</td></tr><tr><td>5</td><td>System Earthing</td><td>Solidly Earthed</td></tr><tr><td>6</td><td>Auxiliary Supply</td><td>240V $\pm$ 10%, 1-ph, 50Hz AC; 110V -15% +10% DC</td></tr><tr><td>7</td><td>Control Supply</td><td> i. 110V DC- for protection metering and control ii. 110V DC- circuit breaker spring charging motor iii. 110V DC- Motor drive for disconnectors and earth switches iv. 415V AC TPN- gas handling and filling unit/ cart v. 240V AC SPN—for space heaters, cubicle lamps etc. </td></tr><tr><td>8</td><td>Power supply for spring charging motor</td><td>110V DC -15% +10%</td></tr></table> 7.1.1 The 33kV Gas insulated switchboard shall be suitable for continuous operation of two incomers and bus coupler under NC (Normally closed) condition. 7.2 33kV Gas Insulated Switchboard 7.2.1 The switchgear shall be an indoor gas-insulated, Copper Bus-bar material, metal clad cubicle design with single bus bar system as per datasheet, assembled to form free standing, self supporting dead front structure. Vertical units shall be assembled to form a continuous line-up of uniform height. It shall be suitable for local and remote control through Local/ Remote selector switch. It shall be designed to ensure optimum continuity and					Sl. No.	Description	Data	1	Voltage	As specified in Switchboard SLD (with voltage variation +10% to -10%)	2	Number of Phases & Wires	3-phase, 3-wire	3	Frequency	50Hz $\pm$ 3%	4	Switchboard Fault Level	40kA for 1 sec.	5	System Earthing	Solidly Earthed	6	Auxiliary Supply	240V $\pm$ 10%, 1-ph, 50Hz AC; 110V -15% +10% DC	7	Control Supply	i. 110V DC- for protection metering and control ii. 110V DC- circuit breaker spring charging motor iii. 110V DC- Motor drive for disconnectors and earth switches iv. 415V AC TPN- gas handling and filling unit/ cart v. 240V AC SPN—for space heaters, cubicle lamps etc.	8	Power supply for spring charging motor	110V DC -15% +10%
					Sl. No.	Description	Data																								
					1	Voltage	As specified in Switchboard SLD (with voltage variation +10% to -10%)																								
2	Number of Phases & Wires	3-phase, 3-wire																													
3	Frequency	50Hz $\pm$ 3%																													
4	Switchboard Fault Level	40kA for 1 sec.																													
5	System Earthing	Solidly Earthed																													
6	Auxiliary Supply	240V $\pm$ 10%, 1-ph, 50Hz AC; 110V -15% +10% DC																													
7	Control Supply	i. 110V DC- for protection metering and control ii. 110V DC- circuit breaker spring charging motor iii. 110V DC- Motor drive for disconnectors and earth switches iv. 415V AC TPN- gas handling and filling unit/ cart v. 240V AC SPN—for space heaters, cubicle lamps etc.																													
8	Power supply for spring charging motor	110V DC -15% +10%																													
Ref. Doc																															

TD-201 Rev No. 00	Form No.	 	PRODUCT STANDARD PROJECT ENGINEERING & SYSTEMS DIVISION, HYDERABAD	PY55294					
				Rev No. 00					
				Page 9 of 15					
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.		reliability of supply as well as safety during operation.33kV GIS will be located in the Air-conditioned room.							
	7.2.2	Minimum degree of enclosure protection:	<table><tr><th>Switchboard</th><th>IP Class</th></tr><tr><td>For low voltage compartments</td><td>IP 4X</td></tr><tr><td>For gas compartments</td><td>IP 65</td></tr></table>	Switchboard	IP Class	For low voltage compartments	IP 4X	For gas compartments	IP 65
	Switchboard	IP Class							
	For low voltage compartments	IP 4X							
	For gas compartments	IP 65							
	7.2.3	All the equipment described in this specification is intended for continuous duty at the specified ratings under the specified ambient conditions.							
	7.2.4	33kV Gas Insulated Switchboards shall be suitable for 3-phase, 3-wire system. Three phase buses shall be provided. The vertical dropper/interconnection bus bars shall be suitably sized for short time current rating of the main bus bar or circuit current rating, whichever is higher.							
	7.2.5	Indication Lamps shall be of Clustered LED type.							
	7.2.6	Protection relays shall be numerical type as specified on the Switchboard SLDs. All other relays shall be electromagnetic type.							
	7.2.7	The enclosure for the SF6 gas and associated circuit elements shall be made from non-magnetic material. The type of material and thickness shall also be such so as to keep heating due to induced circulating currents to a minimum. Enclosures of the same phase shall be electrically interconnected, and shall be earthed at appropriate places.							
	7.2.8	Need for Inter panel wiring of all switchboards at site shall be minimized and such wiring shall be plug type only for ease of installation at site.							
	7.2.9	Breaker control switches, Selector switches shall be hardwired type.							
	7.2.10	Suitable terminals shall be provided in the respective panels for interfacing incoming contacts from remote (ECP, SCAP). Current rating of these remote contacts shall be 5A, 110V DC or 240V AC.							
	7.2.11	The ECS & SCAP interface signals shall be marshalled individually for each feeder of the Switchboards.							
	7.2.12	Signals shall be provided as per attached ECS typical I/O lists. <i>These lists duly filled up with TB nos. and/or address details, for each Feeder/Bus Coupler/PT shall be furnished by the vendor during detailed engineering.</i>							
	7.2.13	All potential free contacts and analogue input signals including unused contacts/ports shall be duly wired to the terminal block in the respective panel.							
	7.2.14	Painting shall be as per the specification, Paint shade shall be <u>RAL 7032 for exterior</u> .							
7.2.15	Cable glands for LT power 3-core cables shall be weatherproof double compression nickel plated brass type (ET) with check nuts and PVC shrouds. Cable glands for 1-core cables shall be weatherproof double compression aluminium type (ET) with check nuts and PVC shrouds. Cable lugs shall be of tinned copper heavy duty crimped type.								
7.2.16	Voltage transformers will have continuous over voltage of 1.2 and over voltage factor of 1.9 for 30secs.								
7.2.17	Positive indications will be provided for breaker closing and opening status								

TD-201 Rev No. 00	Form No.	 	PRODUCT STANDARD PROJECT ENGINEERING & SYSTEMS DIVISION, HYDERABAD	PY55294 Rev No. 00 Page 10 of 15
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.		7.2.18 Control & Operation Philosophy 33kV GIS will be controlled from remote control panel SCAP/ECS. 33 kV GIS switchboards shall have one local/remote control selector switch. When selector switch is selected in remote mode, control shall be transferred to hard-wired synchronizing panel (SCAP). All the control, monitoring and annunciation functions shall be realized in the 33kV GIS as per Electrical Control Philosophy attached as Annexure 2B and I/O list as per Annexure-04. Necessary Synchronization equipment shall be considered in 33kV GIS for synchronization of Incomers/Bus-coupler for parallel operation. 7.3 Numerical Relays & Ethernet Switches 7.3.1 All numerical relay shall have RS232/RJ45/USB port on the front for hooking laptop. The rear numerical relays shall have dual ports suitable for IEC 61850 HSR for communication with HSR Box & further communication with Data concentrator/HMI through Managed Ethernet switch. 7.3.2 Communication between relay and IEC61850 HSR Box/switches shall be provided as Redundant communication architecture as per attached architecture in Annexure-1B. Each Numerical Relay shall be provided with <i>dual port</i> for ensuring full redundant communication with <i>required number of redundant</i> Ethernet switches, provided in switchboard. Numerical relays shall communicate using IEC 61850-HSR protocol. For hooking up to Data Concentrator/ HMI/gateway for upper level connectivity, redundant communication link through two switches within the ring. Ethernet switch shall have dual DC power supply. Ethernet switches shall be suitable for satisfactory operation inside the switchboards taking account of switchboard temperature rise and the site conditions specified. 20% ports in each Ethernet switch shall be kept as spare. 7.3.3 The requirement of Numerical relays and integration shall be in compliance with the requirements given in specification of Numerical relays (Annexure-1B). 7.3.4 Numerical Relays shall be of latest version, communicable type with non-volatile memory, comprehensive unit providing protection, metering and control. 7.3.5 Laptop shall be of the latest configuration and processor as available at the time of purchase subject to approval by BHEL.. 7.3.6 The no. of Digital Inputs (DIs) / Digital Outputs (DOs) in the Numerical Relays shall be <i>sufficient</i> for implementing all necessary logics (see Annexure-2A) and providing signals indicated in I/O Lists (see Annexures-4 & 2B). In view of the possibility of change in breaker logics during detailed engineering, <i>20% extra DIs/DOs</i> shall be considered in Numerical Relays over <i>what is deemed sufficient</i> to implement the supplied logic diagrams. No price/time implication on account of change in breaker logics or change in NR DIs/DOs during detailed engineering will be entertained. <i>However, minimum 24 DIs and 12 DOs shall be provided for numerical relays envisaged in incomers, bus couplers and outgoing feeders.</i> 7.3.7 All cables and associated accessories required for implementing a functional Ethernet Switch with the prescribed architecture shall be provided by the Vendor. All cabling required for the interconnection of Numerical Relays with the HSR Switches shall be done at the vendor works itself. <u><i>In case, it is not possible to supply the Switchboard to site with all NRs interconnected to the HSR Switches and some Inter panel cabling is required to be done at site, then the same shall be done by the Vendor at site without any time and cost implication to BHEL.</i></u>		
Ref. Doc				

TD-201 Rev No. 00		Form No.	 PRODUCT STANDARD PROJECT ENGINEERING & SYSTEMS DIVISION, HYDERABAD		PY55294					
					Rev No. 00					
					Page 11 of 15					
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.						8.0 INSPECTION, TESTING AND ACCEPTANCE				
						8.1	Inspection, testing and acceptance requirements shall confirm to Standard Specifications of 33kV Gas Insulated switchboard (Annexure-1A) and Numerical Relays(Annexure-1B).			
						8.2	Before raising inspection call, manufacturer shall submit all the test reports/ certificates for the equipment.			
						8.3	During fabrication, the switchgear package shall be subjected to inspection by Owner or by an agency authorized by the Owner. Manufacturer shall furnish all necessary information concerning the supply to Owner’s inspectors. Owner/BHEL may make multiple visits during manufacturing and testing for review of progress, quality documents verification, verification of materials in compliance to specifications/standards. Owner/BHEL may make final visit for final inspection and verification of shipment documents. The same shall be included in the manufacturing quality assurance plan. Actual visits and inspection shall be as per the approved manufacturing quality assurance plan.			
						8.4	All routine and acceptance tests as per IS standards and Standard Manufacturing Quality Plan shall be carried out at manufacturer’s works under his care and expense.			
						8.5	All equipments supplied by vendor shall be of proven design and shall be type tested as per IS, IEC standards. The requisite type test certificates shall be submitted during technical bid submission and type test certificates shall not be older than 5 years from the date of bid submission. In case valid test certificates are not available or are older than 5 years, vendor shall conduct tests free of cost and without any delivery implications. In case BHEL / Customer / Consultant insist the tests, the tests shall be done with price implication. Unit rates shall be quoted by vendor as optional.			
						8.6	Inspection of switchgear HV portion coming from principal (Manufacturer) shall be at works of (principal) manufacturer before dispatch to india. The inspection team shall comprise customer/consultant/BHEL for inspection duration of 7 days. Travel expenses, accommodation expenses, local traveling expenses food charges etc shall be arranged by EIL/BHEL/Owner on their own cost. Routine test will be carried out on each type of the panel not on complete lot.			
						8.7	For Numerical Relays, the following tests shall be performed and/ or Test Certificates submitted for concurrence by BHEL:			
							1. Temperature withstand 2. Electromagnetic compatibility (EMC) 3. Disturbance immunity 4. HV withstands test for insulation 5. Impulse voltage test 6. Functional tests and Communication integrity 7. Relay characteristics verification 8. Degree of protection 9. Mechanical stress/ vibration test			
							9.0 DOCUMENTATION			
	9.1	Documents to be submitted along with the technical bid/ offer:								
		1. Deviation schedule (Refer Annexure-7) 2. Switchboard GA with dimensions and weights 3. Un-priced price format (Refer Annexure- 09) 4. Type test certificates as per IS standards not older than 5 years for switchboards which are similar in configuration to the switchboards present in this Project. 5. Check List (Refer Annexure-13). Details are specified at Cl. 14.0 of this specification.								
Ref. Doc										

TD-201 Rev No. 00	Form No.	 	PRODUCT STANDARD PROJECT ENGINEERING & SYSTEMS DIVISION, HYDERABAD	PY55294 Rev No. 00 Page 12 of 15
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.		Technical offer of the bidder will be evaluated only on the basis of deviation schedule and Price Format. Nature of Deviations shall only be of Design/ Manufacturing constraints and non-availability of items/ components/ makes in market. Switchboard dimensions are for fixing Purchaser's tentative room layout. Un-priced price format consists of Items of Main offer and Unit rates for additions/ deletions of supplies/ services/ spares during execution. All fields shall be quoted in this format only. Note: No price implications shall be entertained for deviations withdrawn during the technical scrutiny. If any deviation is accepted by BHEL during technical scrutiny even then there will be no price implication. Hence, in no case there will be consideration of price implications. 9.2 Offer is liable for rejection when • The offer is incomplete with respect to above clauses. • The above documents are not submitted in BHEL's formats. • Any field is left blank in the Price format. • Discrepancy is observed between Un-priced and Priced bid. 9.3 Documents to be submitted after award of contract: Refer Annexure - 12. 10.0 GUARANTEE 10.1 The supplier shall be fully responsible in respect of design, selection of components, manufacture, and quality of workmanship and operation of all the equipments, accessories etc. supplied under this scope of contract up to the Guarantee period. 10.2 Guarantee period shall be as per the commercial terms and conditions of the NIT. 11.0 QUALITY PLAN 11.1 Quality Assurance Program 11.1.1 The successful Bidder shall provide and implement a documented Quality Assurance Programme. The Program shall be capable of providing assurance that design, purchasing, manufacturing, loading, shipping, storage, erection, construction, testing and examination of Scope of Supply comply with the requirements of the specifications and documents. 11.1.2 The quality control organization shall follow-up the inspection and testing to ensure adherence to quality of the Scope of Supply and compliance with the Program and with the test procedures. In particular, it shall: 1. Provide all design and engineering Divisions and its Sub vendor with detailed instructions regarding inspection and testing; 2. Organise the tests required in the programme, witness them and issue test certificates; 3. Inspect the Equipment before packing, check the quality of packing and if Equipment and packing are found to comply with the requirements, authorise shipment; 4. Inspect for possible transport damages if any, and prepare and submit repair procedures for approval; 5. Organise and witness all inspection and testing on Site and issue test certificates. 11.1.3 No Equipment shall be packed, prepared for shipment, or dismantled for the purpose of packing for shipment, unless it has been satisfactorily inspected and approved for shipment.		
Ref. Doc				

TD-201 Rev No. 00 Form No.		PRODUCT STANDARD PROJECT ENGINEERING & SYSTEMS DIVISION, HYDERABAD	PY55294																																																								
			Rev No. 00																																																								
			Page 14 of 15																																																								
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.	13.3 Vendor to confirm that all equipments supplied by vendor are of proven design and are type tested. The requisite type test certificates shall be submitted during technical bid submission/ detailed engineering & type test certificates shall not be older than 5 years from the date of bid submission. In case valid test certificates are not available or are older than 5 years, vendor shall conduct tests free of cost & without any delivery implications. In case BHEL / Customer / Consultant insist the tests, the tests shall be done with price implication. Unit rates shall be quoted by vendor. 13.4 All cabling required for the interconnection of Numerical Relays with the Ethernet Switches in HT Gas insulated switchgear, shall be done at the vendor works itself. In case, it is not possible to supply the Switchboards to site with all NRs interconnected to the Ethernet Switches and some Interpanel cabling is required to be done at site, then the same shall be done by the Vendor at site without any time and cost implication to BHEL. 14.0 CHECK LIST FOR BID SUBMISSION 14.1 Check List for Bid Submission is provided as Annexure-13 to this Specification. This Check List shall be followed for submitting the Bid documents. The Check List itself <i>shall be filled</i> by the Bidder in entirety and <i>mandatorily submitted</i> along with the Offer. 15.0 LIST OF MATERIAL CODES AS PER ENQUIRY <table border="1"> <thead> <tr> <th>Sl.No.</th> <th>Description</th> <th>Quantity</th> <th>Material code</th> </tr> </thead> <tbody> <tr> <td>1)</td> <td>Supply of 33kV GIS Switchgear as per enquiry specification</td> <td>1-Set</td> <td>PY9755294015</td> </tr> <tr> <td>2)</td> <td>Supply of Substation Automation system</td> <td>1-Set</td> <td>PY9755294023</td> </tr> <tr> <td>3)</td> <td>Supervision of Erection/Installation of 33kV GIS including Substation Automation system</td> <td>1-Set</td> <td>PY9855294033</td> </tr> <tr> <td>4)</td> <td>Complete Testing and Commissioning of 33kV GIS at site</td> <td>1-Set</td> <td>PY9855294041</td> </tr> <tr> <td>5)</td> <td>Complete Testing and Commissioning of protection relays and Substation Automation system at site</td> <td>1-Set</td> <td>PY9855294050</td> </tr> <tr> <td>6)</td> <td>33kV Cable Plug & socket / Kit Erection & Termination at 33kV GIS end.</td> <td>1-Set</td> <td>PY9755294066</td> </tr> <tr> <td>7)</td> <td>Training for Six OWNER's Engineers for a period of at least seven days for each at manufacturer's works for 33kV GIS Switchgear</td> <td>1-Each</td> <td>PY9855294076</td> </tr> <tr> <td>8)</td> <td>Training for Six OWNER's Engineers for a period of at least seven days for each at manufacturer's works for Numerical relays</td> <td>1-Each</td> <td>PY9855294084</td> </tr> <tr> <td>9)</td> <td>Training for Six OWNER's Engineers for a period of at least seven days for each at manufacturer's works for Data concentrators.</td> <td>1-Each</td> <td>PY9755294090</td> </tr> <tr> <td>10)</td> <td>Training for TEN OWNER' s Engineers for a period of at least seven days for each at Site for 33kV GIS Switchgear</td> <td>1-Each</td> <td>PY9855294106</td> </tr> <tr> <td>11)</td> <td>Training for TEN OWNER' s Engineers for a period of at least seven days for each at Site for Numerical relays</td> <td>1-Each</td> <td>PY9855294114</td> </tr> <tr> <td>12)</td> <td>Training for TEN OWNER' s Engineers for a period of at least seven days for each at Site for Data concentrators</td> <td>1-Each</td> <td>PY9855294122</td> </tr> <tr> <td>13)</td> <td>Supply of Mandatory Spares</td> <td>1-Set</td> <td>PY9755294139</td> </tr> </tbody> </table>			Sl.No.	Description	Quantity	Material code	1)	Supply of 33kV GIS Switchgear as per enquiry specification	1-Set	PY9755294015	2)	Supply of Substation Automation system	1-Set	PY9755294023	3)	Supervision of Erection/Installation of 33kV GIS including Substation Automation system	1-Set	PY9855294033	4)	Complete Testing and Commissioning of 33kV GIS at site	1-Set	PY9855294041	5)	Complete Testing and Commissioning of protection relays and Substation Automation system at site	1-Set	PY9855294050	6)	33kV Cable Plug & socket / Kit Erection & Termination at 33kV GIS end.	1-Set	PY9755294066	7)	Training for Six OWNER's Engineers for a period of at least seven days for each at manufacturer's works for 33kV GIS Switchgear	1-Each	PY9855294076	8)	Training for Six OWNER's Engineers for a period of at least seven days for each at manufacturer's works for Numerical relays	1-Each	PY9855294084	9)	Training for Six OWNER's Engineers for a period of at least seven days for each at manufacturer's works for Data concentrators.	1-Each	PY9755294090	10)	Training for TEN OWNER' s Engineers for a period of at least seven days for each at Site for 33kV GIS Switchgear	1-Each	PY9855294106	11)	Training for TEN OWNER' s Engineers for a period of at least seven days for each at Site for Numerical relays	1-Each	PY9855294114	12)	Training for TEN OWNER' s Engineers for a period of at least seven days for each at Site for Data concentrators	1-Each	PY9855294122	13)	Supply of Mandatory Spares	1-Set	PY9755294139
	Sl.No.	Description	Quantity	Material code																																																							
1)	Supply of 33kV GIS Switchgear as per enquiry specification	1-Set	PY9755294015																																																								
2)	Supply of Substation Automation system	1-Set	PY9755294023																																																								
3)	Supervision of Erection/Installation of 33kV GIS including Substation Automation system	1-Set	PY9855294033																																																								
4)	Complete Testing and Commissioning of 33kV GIS at site	1-Set	PY9855294041																																																								
5)	Complete Testing and Commissioning of protection relays and Substation Automation system at site	1-Set	PY9855294050																																																								
6)	33kV Cable Plug & socket / Kit Erection & Termination at 33kV GIS end.	1-Set	PY9755294066																																																								
7)	Training for Six OWNER's Engineers for a period of at least seven days for each at manufacturer's works for 33kV GIS Switchgear	1-Each	PY9855294076																																																								
8)	Training for Six OWNER's Engineers for a period of at least seven days for each at manufacturer's works for Numerical relays	1-Each	PY9855294084																																																								
9)	Training for Six OWNER's Engineers for a period of at least seven days for each at manufacturer's works for Data concentrators.	1-Each	PY9755294090																																																								
10)	Training for TEN OWNER' s Engineers for a period of at least seven days for each at Site for 33kV GIS Switchgear	1-Each	PY9855294106																																																								
11)	Training for TEN OWNER' s Engineers for a period of at least seven days for each at Site for Numerical relays	1-Each	PY9855294114																																																								
12)	Training for TEN OWNER' s Engineers for a period of at least seven days for each at Site for Data concentrators	1-Each	PY9855294122																																																								
13)	Supply of Mandatory Spares	1-Set	PY9755294139																																																								
Ref. Doc																																																											

COPYRIGHT AND CONFIDENTIAL
The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED,
It must not be used directly or indirectly in any way detrimental to the interest of the company.