

Enquiry No : 2661900237

Description : Brake linings for cranes

COMMON SPECIFICATIONS FOR ALL ITEMS (SL NO.10 TO 100)

- (1) COMPRESSIVE STRENGTH (Kg/Cm²) : 550 (MINIMUM)
- (2) TENSILE STRENGTH (Kgs/Cm²) : 240 (MINIMUM)
- (3) CO-EFFICIENT OF FRICTION : 0.30(MINIMUM)
- (4) RIVET HOLDING CAPACITY(Kg/Cm²) : 850 (MINIMUM)

NOTE:

- (1) THE SUPPLIER SHOULD SUBMIT THE TECHNICAL DATA SHEET / CATALOGUE ALONG WITH THEIR OFFER OTHER WISE OFFER WILL BE REJECTED.
- (2) APPLICATION: INDUSTRIAL DRUM BRAKE-CRANE APPLICATION.

VENDOR QUALIFICATION CRITERIA:

(1)THE BIDDER(S) / VENDOR(S) SHALL BE A MANUFACTURER OR AN AUTHORIZED DEALER OF BRAKE LININGS. IN CASE OF AUTHORIZED DEALERS, LATEST AUTHORIZATION FROM THE MANUFACTURER SHALL BE SUBMITTED ALONG WITH THE OFFER.

(2) BHEL RESERVES THE RIGHT TO VERIFY THE INFORMATION PROVIDED BY VENDOR.IN CASE THE INFORMATION PROVIDED BY VENDOR IS FOUND TO BE FALSE/ INCORRECT, THE OFFER SHALL BE REJECTED.